



Sikafloor[®] Marine VEM

VISCO-ELASTIC VIBRATION DAMPING MORTAR

- Remarkable vibration damping
- Isocyanate-free
- Great pumpability

BUILDING TRUST



Sikafloor® Marine VEM

VISCO-ELASTIC VIBRATION DAMPING MORTAR

Sikafloor® Marine VEM is a one-component visco-elastic mortar based on polymer modified cement and is used as a vibration damping system. It is applied on interior decks in combination with Sikafloor® Marine-18 as well as with Sikafloor® Marine-118 FC.

For specific applications consult the product data sheet or Sika technical service.

PRODUCT BENEFITS

- Great vibration damping factor
- Excellent visco-elastic effect
- Extremely environment-friendly

Technical Properties

Chemical base	1-Component polymer
Density	1.3 kg/m ² /mm
Applied thickness	1 – 2 mm
Ready to walk on	8 – 12 hr.
Elongation at break	55%
Tensile strength	0.6 N/mm ²
Shore A	75
Shelf life	12 months

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.



SIKA SERVICES AG
Tueffenwies 16
8048 Zurich
Switzerland

Contact
Phone: +41 58 436 40 40
Fax: +41 58 436 55 30
www.sika.com/marine

BUILDING TRUST

