

Version 11.2

Print Date 31.05.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

Sikaflex<sup>®</sup>-291i

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

+31-57-0854201

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

nazaru piciograms	·		
Signal word	:	Warning	
Hazard statements	:	H317	May cause an allergic skin reaction.
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.
		P102	Keep out of reach of children.
		Prevention	:





Revision Date: 31.05.2024 Date of last issue: 25.05.2023	Version 11.2		Print Date 31.05.2024
	P261 P280	Avoid breathing mist or vapours Wear protective gloves.	5.
	<b>Response:</b> P302 + P352	IF ON SKIN: Wash with plenty	of water.
	Disposal:		
	P501	Dispose of contents/container in with local regulation.	n accordance

#### Hazardous components which must be listed on the label:

Hardener LI (Isophoronedialdimine) Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane Pentamethyl piperidylsebacate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate 4,4'-methylenediphenyl diisocyanate

#### Additional Labelling

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not
	breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Version 11.2

Print Date 31.05.2024

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Urea,N,N"-(methylenedi-4,1-	77703-56-1	Aquatic Chronic 4;	>= 2,5 - < 5
phenylene)bis[N'-butyl-	416-600-4	H413	
	01-0000016345-72-		
	XXXX		
Hardener LI (Isophoronedial-	932742-30-8	Skin Sens. 1B; H317	>= 0,5 - < 1
dimine)	700-071-4	Aquatic Chronic 3;	
	01-2119880654-28-	H412	
	XXXX		
Reaction product of Hexameth-	192526-20-8	Skin Sens. 1A; H317	>= 0,1 - < 0,25
ylene diisocyanate, oligomers with	924-669-1	Aquatic Chronic 4;	
Mercaptopropyltrimethoxysilane	01-2120768758-32-	H413	
	XXXX		
Pentamethyl piperidylsebacate	1065336-91-5	Skin Sens. 1A; H317	>= 0,1 - < 0,25
Contains:	915-687-0	Repr. 2; H361f	
bis(1,2,2,6,6-pentamethyl-4-	01-2119491304-40-	Aquatic Acute 1;	
piperidyl) sebacate	XXXX	H400	
methyl 1,2,2,6,6-pentamethyl-4-		Aquatic Chronic 1;	
piperidyl sebacate		H410	
		M-Factor (Acute	
		aquatic toxicity): 1	
		M-Factor (Chronic	
		aquatic toxicity): 1	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikaflex®-291i



sion Date: 31.05.2024 of last issue: 25.05.2023	Version 11	1.2	Print Date 31.05
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411	>= 0,025 - < 0,1
		specific concentration limit Resp. Sens. 1; H334 >= $0.5 \%$ Skin Sens. 1; H317 >= $0.5 \%$	
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 0,031 mg/l	
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 $\longrightarrow$ specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 %	< 0,1
		Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	



Revision Date: 31.05.2024	Version 11.2	Print Date 31.05.2024
Date of last issue: 25.05.2023		

Substances with a workplace exposure limit :		
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17- XXXX	>= 2,5 - < 5

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms and	d e	ffects, both acute and delayed
Symptoms	:	Allergic reactions See Section 11 for more detailed information on health effects and symptoms.
Risks	:	sensitising effects
		May cause an allergic skin reaction.
4.3 Indication of any immediate m	ned	ical attention and special treatment needed
Treatment	:	Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-



Revision Date: 31.05.2024	Version 11.2	Print Date 31.05.2024
Date of last issue: 25.05.2023		

ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known ucts

#### 5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

<b>6.1 Personal precautions, protec</b> Personal precautions		e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
6.3 Methods and material for containment and cleaning up		
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections		

For personal protection see section 8.

# SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Follow standard hygiene measures when handling chemical products



Revision Date: 31.05.2024 Date of last issue: 25.05.2023		Version 11.2	Print Date 31.05.2024
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygier practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the en	using do not
7.2 Conditions for safe storage, in	าต	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Store in accordance with local regulations	
Further information on stor-	:	No decomposition if stored and applied as directed	əd.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet pluse.	rior to any

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercap- topropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l



Sikaflex<sup>®</sup>-291i

Revision Date: 31.05.2024 Date of last issue: 25.05.2023 Version 11.2

Print Date 31.05.2024

Marine water	0,01 mg/l
Intermittent use/release	1 mg/l
Fresh water sediment	23,28 mg/kg
Marine sediment	2,33 mg/kg
Sewage treatment plant	100 mg/l
Soil	4,58 mg/kg

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection		Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice

: Do not flush into surface water or sanitary sewer system.



Version 11.2

Print Date 31.05.2024

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	::	liquid paste various
Odour	:	very faint
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	vn	Josivo limits
••	-	
Upper explosion limit / Up- per flammability limit	•	NO data avallable
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 150 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble



# Sikaflex®-291i

Revision Date: 31.05.2024 Date of last issue: 25.05.2023		Version 11.2	Print Date 31.05.2024
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,38 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	
0.2 Other information			

#### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

# 10.5 Incompatible materials

Materials to avoid : No data available

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.



sion Date: 31.05.2024 of last issue: 25.05.2023		Version 11.2	Print Date 31.05.2024
Components:			
Urea,N,N"-(methylenedi-4	,1-ph	enylene)bis[N'-butyl-:	
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402	
Hardener LI (Isophoroned	dialdi	mine):	
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg	
Reaction product of Hexa ysilane:	methy	ylene diisocyanate, oligomers with Merca	ptopropyltrimethox-
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423	
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402	
Pentamethyl piperidylseb	acate	:	
Acute oral toxicity		LD50 Oral (Rat): 3.230 mg/kg	
3-isocyanatomethyl-3,5,5-	trime	thylcyclohexyl isocyanate:	
Acute oral toxicity	:	LD50 Oral (Rat): 4.814 mg/kg	
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l	
		Exposure time: 4 h Test atmosphere: dust/mist	
		Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	:	LD50 Dermal (Rat): > 7.000 mg/kg	
4,4'-methylenediphenyl di	isocy	anate:	
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401	
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
		Acute toxicity estimate: 1,5 mg/l	
		roate toniony commute. 1,0 mg/r	



Version 11.2

Print Date 31.05.2024

Test atmosphere: dust/mist Method: Calculation method

### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

2

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Version 11.2

Print Date 31.05.2024

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Components:

#### Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h

#### Hardener LI (Isophoronedialdimine):

Toxicity to fish	:	LC50 (Fish): 87,2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l Exposure time: 72 h

#### Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

<b>,</b>		
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Pentamethyl piperidylsebac	ate	:
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1

M-Factor (Chronic aquatic

: 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikaflex<sup>®</sup>-291i

**Jika**®

Revision Date: 31.05.2024 Date of last issue: 25.05.2023 Version 11.2

Print Date 31.05.2024

toxicity)

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

<u>Product:</u> Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	

#### Product:

Additional ecological infor- : There is no data available for this product. mation

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with



Revision Date: 31.05.2024 Date of last issue: 25.05.2023		Version 11.2	Print Date 31.05.2024
		soil, waterways, drains and sewers.	
European Waste Catalogue	:	08 04 09* waste adhesives and sealants of solvents or other dangerous substances	ontaining organic
Contaminated packaging	:	15 01 10* packaging containing residues of by dangerous substances	or contaminated

# **SECTION 14: Transport information**

14.1 UN number or ID number					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.2 UN proper shipping name					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.3 Transport hazard class(es)					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.4 Packing group					
ADR : Not regulated as a dangerous good					
IMDG	:	Not regulated as a dangerous good			
IATA (Cargo)	:	Not regulated as a dangerous good			
IATA (Passenger)	:	Not regulated as a dangerous good			
14.5 Environmental hazards					
Not regulated as a dangerous good					
14.6 Special precautions for user Not applicable					
<b>14.7 Maritime transport in bulk according to IMO instruments</b> Not applicable for product as supplied.					

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance of	or mixture
Country NL 000000131725	15 / 18

# Sikaflex<sup>®</sup>-291i

\_



Revision Date: 31.05.2024 Date of last issue: 25.05.2023	Version 1	1.2		Print Date 31.05.2024
International Chemical Weapons		:	Not applicable	
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	trea /or gula	im suppliers, and/or tion, and/or	
REACH - Restrictions on the man the market and use of certain dan mixtures and articles (Annex XVII	gerous substances,	:	Conditions of restriction lowing entries should Number on list 75, 3	
			3-isocyanatomethyl-3 trimethylcyclohexyl iso (Number on list 74) 4,4'-methylenediphen (Number on list 74, 56 1,2-Benzenedicarboxy 11-branched alkyl est (Number on list 52)	ocyanate yl diisocyanate s) ylic acid, di-C9-
REACH - Candidate List of Substa Concern for Authorisation (Article		:	None of the compone (=> 0.1 %).	nts are listed
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable	
Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de-	:	Not applicable	
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu-	:	Not applicable	
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable	
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar		nent	and of the Council on	the control of ma-

Volatile organic compounds : Law on the incentive tax for volatile organic compounds



Version 11.2

Print Date 31.05.2024

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

manganese ferrite black spinel dibutyltin dilaurate

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H361f	:	Suspected of damaging fertility.
H373	:	May cause damage to organs through prolonged or repeated
		exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
11440		Many serves low a losting beautiful offects to serve the life
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbrevia	: ntions	May cause long lasting narmful effects to aquatic life.
	: ntions :	Acute toxicity
Full text of other abbrevia	tions	
Full text of other abbrevia Acute Tox.	tions	Acute toxicity
<b>Full text of other abbrevia</b> Acute Tox. Aquatic Acute	itions	Acute toxicity Short-term (acute) aquatic hazard
<b>Full text of other abbrevia</b> Acute Tox. Aquatic Acute Aquatic Chronic	itions : : :	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc.	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit.	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr.	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr. Resp. Sens.	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity Respiratory sensitisation
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr. Resp. Sens. Skin Irrit.	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity Respiratory sensitisation Skin irritation
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr. Resp. Sens. Skin Irrit. Skin Sens.	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity Respiratory sensitisation Skin irritation Skin sensitisation
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr. Resp. Sens. Skin Irrit. Skin Sens. STOT RE	itions	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr. Resp. Sens. Skin Irrit. Skin Sens. STOT RE STOT SE	ations	Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure
Full text of other abbrevia Acute Tox. Aquatic Acute Aquatic Chronic Carc. Eye Irrit. Repr. Resp. Sens. Skin Irrit. Skin Sens. STOT RE STOT SE DE TRGS 900		Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Carcinogenicity Eye irritation Reproductive toxicity Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Germany. TRGS 900 - Occupational exposure limit values.

# Sikaflex<sup>®</sup>-291i



evision Date: 31.05.2024 ate of last issue: 25.05.2023		Version 11.2	Print Date 31.05.2024
		Dangaraus Goods by Bood	
CAS		Dangerous Goods by Road Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
IATA	:	International Air Transport Association	
IMDG	:	International Maritime Code for Dangerou	is Goods
LD50	÷	Median lethal dosis (the amount of a mate	
	-	once, which causes the death of 50% (on	
		test animals)	) <u>9</u>
LC50	:	Median lethal concentration (concentratio	ns of the chemical in
		air that kills 50% of the test animals during	
		period)	-
MARPOL	:	International Convention for the Preventio	on of Pollution from
		Ships, 1973 as modified by the Protocol of	of 1978
OEL	:	Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the Eur	
		and of the Council of 18 December 2006	
		istration, Evaluation, Authorisation and Re	
		cals (REACH), establishing a European C	Chemicals Agency
SVHC	:	Substances of Very High Concern	
vPvB	:	Very persistent and very bioaccumulative	
Further information			
Cleasification of the minter		Classification n	

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN