Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikaflex<sup>®</sup>-Tank N

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

#### 1.4 Emergency telephone number

+31-57-0854201

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H317 H334	May cause an allergic skin reaction. May cause allergy or asthma symptoms or

## Sikaflex<sup>®</sup>-Tank N

Print Date 03.04.2024

Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0

	H412	breathing difficulties if inhaled. Harmful to aquatic life with long lasting ef- fects.
Precautionary statements :	Prevention:	
	P261 P273 P280 P284	Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves. In case of inadequate ventilation wear respir- atory protection.
	Response:	
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

## Hazardous components which must be listed on the label:

4,4`-Methylenediphenyl diisocyanate, oligomers Pentamethyl piperidylsebacate 4,4'-methylenediphenyl diisocyanate m-tolylidene diisocyanate

#### Additional Labelling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 21.07.2023 Date of last issue: 05.06.2023



Version 10.0

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Components		Cleasification	Concentration
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
N,N-dibenzyliden polyoxypropyl- ene diamine (polymer)	136855-71-5 Not Assigned	Skin Irrit. 2; H315	>= 5 - < 10
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
4,4`-Methylenediphenyl diisocya- nate, oligomers	25686-28-6 500-040-3 01-2119457013-49- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	>= 0,1 - < 0,5
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25

# Sikaflex<sup>®</sup>-Tank N

Revision Date: 21.07.2023 Date of last issue: 05.06.2023



Version 10.0

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5	>= 0,1 - < 0,5
m-tolylidene diisocyanate	26471-62-5 247-722-4 01-2119454791-34- XXXX	mg/lAcute Tox. 1; H330Skin Irrit. 2; H315Eye Irrit. 2; H319Resp. Sens. 1; H334Skin Sens. 1; H317Carc. 2; H351STOT SE 3; H335(Respiratory system)Aquatic Chronic 3;H412specific concentrationlimitResp. Sens. 1; H334>= 0,1 %Acute toxicity estimateAcute inhalation toxicity (vapour): 0,107mg/l	>= 0,025 - < 0,1



Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0

ethylenebis(oxyethylene) bis[3-(5- tert-butyl-4-hydroxy-m- tolyl)propionate]	36443-68-2 253-039-2 01-2119956160-44- XXXX	Aquatic Chronic 1; H410	>= 0,0025 - < 0,025
	^^^^	M-Factor (Chronic aquatic toxicity): 10	
Substances with a workplace expo	sure limit :		
titanium dioxide; [in powder form	13463-67-7		>= 2,5 - < 5
containing 1 % or more of parti-	236-675-5		
cles with aerodynamic diameter ≤	01-2119489379-17-		
10 µm]	XXXX		

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

4.1 Description of first aid measures				
General advice	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.			
If inhaled :	Move to fresh air. Consult a physician after significant exposure.			
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.			
In case of eye contact	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.			
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.			
4.2 Most important symptoms and	effects, both acute and delayed			
Symptoms :	Asthmatic appearance Allergic reactions See Section 11 for more detailed information on health effects and symptoms.			
Risks :	sensitising effects			
	May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.			



Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

<b>5.1 Extinguishing media</b> Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from Hazardous combustion prod- ucts		e substance or mixture No hazardous combustion products are known
<ul><li>5.3 Advice for firefighters</li><li>Special protective equipment for firefighters</li><li>Further information</li></ul>	:	In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

	e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contai	nment and cleaning up
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections	
For personal protection see section	on 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).

# Sikaflex<sup>®</sup>-Tank N

Revision Date: 21.07.2023

Date of last issue: 05.06.2023

Print Date 03.04.2024

Version 10.0

		Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
Advice on protection again fire and explosion	ist :	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage	ge, incl	luding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Further information on stor age stability	·- :	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter ≤ 10 μm]	13463-67-7	TWA	10 mg/m3	DE TRGS 900
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake			
	through the skin, Indicative       STEL     100 ppm     2000/39/EC       442 mg/m3     442 mg/m3			
		TLV-8hr	210 mg/m3	NL WG
	Further information: Skin notation			
		TLV-15 min	442 mg/m3	NL WG

\*The above mentioned values are in accordance with the legislation in effect at the date of the re-

Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0



lease of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipm	ent	
Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Print Date 03.04.2024

Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Appearance Colour	:	paste various
	•	
Odour	:	characteristic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	axe	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-	:	No data available

# Print Date 03.04.2024

Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0

a atomal/water	
octanol/water	

Vapour pressure	:	0,01 hPa
Density	:	ca. 1,47 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

## 10.4 Conditions to avoid

Conditions to avoid : No data available

#### **10.5 Incompatible materials**

Materials to avoid : No data available

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### **Components:**

#### Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

# Sikaflex<sup>®</sup>-Tank N



Revision Date: 21.07.2023 Date of last issue: 05.06.2023	Version 10.0	Print Date
	Method: OECD Test Guideline 401	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402	
reaction mass of ethylbenze	ne and xylene:	
Acute oral toxicity	: LD50 Oral (Rat): 3.523 mg/kg	
4,4`-Methylenediphenyl diiso	cyanate, oligomers:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	: LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
	Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 9.400 mg/kg	
Pentamethyl piperidylsebaca	ate:	
Acute oral toxicity	: LD50 Oral (Rat): 3.230 mg/kg	
4,4'-methylenediphenyl diiso	cyanate:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401	
Acute inhalation toxicity	: LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
	Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
m-tolylidene diisocyanate:		
Acute inhalation toxicity	: LC50 (Rat): 0,107 mg/l Exposure time: 4 h Test atmosphere: vapour	
	Acute toxicity estimate: 0,107 mg/l Test atmosphere: vapour Method: Calculation method	
Skin corrosion/irritation		

#### Skin corrosion/irritation

Not classified based on available information.

Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0



#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Components:

#### Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h



Revision Date: 21.07.2023 Date of last issue: 05.06.2023		Version 10.0 Print Date 0			
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater 100 mg/l Exposure time: 72 h	r green alga)): >		
reaction mass of ethylbenze	ene	and xylene:			
Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow tro	ut)		
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)			
Pentamethyl piperidylsebac	ate	:			
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h			
M-Factor (Acute aquatic tox- icity)	:	1			
M-Factor (Chronic aquatic toxicity)	:	1			
athylanahis(ayyathylana) hi	c[3	-(5-tert-butyl-4-hydroxy-m-tolyl)propionate	1.		
Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish Exposure time: 96 h	-		
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 Exposure time: 48 h	mg/l		
Toxicity to algae/aquatic plants	:	(Desmodesmus subspicatus (green algae)) Exposure time: 72 h	: > 100 mg/l		
M-Factor (Chronic aquatic toxicity)	:	10			
12.2 Persistence and degradabil	ity				
<b>12.3 Bioaccumulative potential</b> No data available					
<b>12.4 Mobility in soil</b> No data available					
12.5 Results of PBT and vPvB as	sse	ssment			
Product:					
Assessment	:	This substance/mixture contains no comport to be either persistent, bioaccumulative and very persistent and very bioaccumulative (vertice)	toxic (PBT), or		
Country NL_00000601852			13		

Revision Date: 21.07.2023 Date of last issue: 05.06.2023 Version 10.0



0.1% or higher..

#### 12.6 Endocrine disrupting properties

	Product:		
	Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7	Other adverse effects		
	Product:		
	Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible.
		Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
		Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
		Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

<b>Jika</b> ®
Print Date 03.04.2024

Revision Date: 21.07.2023 Date of last issue: 05.06.2023

ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

4,4`-Methylenediphenyl diisocyanate, oligomers (Number on list 74, 56)
4,4'-methylenediphenyl diisocyanate (Number on list 74, 56)
m-tolylidene diisocyanate (Number on list 74)
1,2-Benzenedicarboxylic acid, di-C9-

11-branched alkyl esters, C10-rich

# Sikaflex®-Tank N



Revision Date: 21.07.2023 Date of last issue: 05.06.2023	Version 1	0.0	Print Date 03.04.		
			(Number on list 52)		
	International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors				
	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).				
REACH - List of substances subject to authorisation (Annex XIV)			Not applicable		
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer			Not applicable		
Regulation (EU) 2019/1021 on pe tants (recast)	Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)				
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			Not applicable		
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	trea /or gula	am suppliers, and/or tion, and/or		
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable					
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 1,22% w/w		
	emissions (integrated p	oollu	4 November 2010 on industrial ution prevention and control) ds (VOC) content: 1,22% w/w		
Other regulations:					

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Revision Date: 21.07.2023

Date of last issue: 05.06.2023

Print Date 03.04.2024

Version 10.0

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

reaction mass of ethylbenzene and xylene manganese ferrite black spinel salicylic acid

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 H304 H312 H315 H317 H319	: : : : : : : : : : : : : : : : : : : :	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.	
H330	:	Fatal if inhaled.	
H332	:	Harmful if inhaled.	
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.	
H335	:	May cause respiratory irritation.	
H351	:	Suspected of causing cancer.	
H361f	:	Suspected of damaging fertility.	
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.	
H400	:	Very toxic to aquatic life.	
H410	:	Very toxic to aquatic life with long lasting effects.	
H412	:	Harmful to aquatic life with long lasting effects.	
H413	:	May cause long lasting harmful effects to aquatic life.	
Full text of other abbreviations			
Acute Tox.	:	Acute toxicity	
Aquatic Acute	:	Short-term (acute) aquatic hazard	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard	
Asp. Tox.	:	Aspiration hazard	
Carc.	:	Carcinogenicity	
Eye Irrit.	:	Eye irritation	
Flam. Liq.	:	Flammable liquids	
Repr.	:	Reproductive toxicity	
Resp. Sens.	:	Respiratory sensitisation	
Skin Irrit.	:	Skin irritation	
Skin Sens.	:	Skin sensitisation	
STOT RE	:	Specific target organ toxicity - repeated exposure	
STOT SE	:	Specific target organ toxicity - single exposure	
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values	
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.	
NL WG	:	Netherlands. Law on Labour conditions - Occupational Expo-	
-		sure Limits	
2000/39/EC / TWA	:	Limit Value - eight hours	

# Sikaflex<sup>®</sup>-Tank N

Revision Date: 21.07.2023 Date of last issue: 05.06.2023



Version 10.0

2000/39/EC / STEL DE TRGS 900 / TWA	:	Short term exposure limit Time Weighted Average
NL WG / TLV-8hr		Time Weighted Average
NL WG / TLV-15 min	÷	
ADR	:	European Agreement concerning the International Carriage of
ABR .	•	Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL		Derived no-effect level
EC50		Half maximal effective concentration
GHS		Globally Harmonized System
IATA		International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL		International Convention for the Prevention of Pollution from
-		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

#### **Further information**

Classification of the mixture:		Classification procedure:	
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN