

Version 11.0

Print Date 23.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-264 LO Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)					
Skin irritation, Category 2	H315: Causes skin irritation.				
Eye irritation, Category 2	H319: Causes serious eye irritation.				
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.				
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.				

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Warning

Sikafloor[®]-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024	Ve	rsion 11.0	Print Date 23.07.2024
Hazard statements :	H317 May H319 Cau	uses skin irritation. / cause an allergic skin reaction. uses serious eye irritation. ic to aquatic life with long lasting e	effects.
Precautionary statements :	Prevention: P261 P264 P273 P280	Avoid breathing mist or vapours. Wash skin thoroughly after hand Avoid release to the environmen Wear protective gloves/ eye prot protection.	ling. t.
	Response: P333 + P313	If skin irritation or rash occurs: G	et medical
	P391	advice/ attention. Collect spillage.	

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Reaction mass of isomers of epoxy resin BFDGE oxirane, mono[(C12-14-alkyloxy)methyl] derivs. p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Country NL 000000121797

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

CAS-No.

1675-54-3

216-823-5

Registration number

EC-No.

SECTION 3: Composition/information on ingredients

Sikafloor[®]-264 LO Part A

epoxipropoxi)phenyl]propane

Revision Date: 23.07.2024 Date of last issue: 10.06.2024

3.2 Mixtures

Components Chemical name

bis-[4-(2,3-

Version 11.0

Classification

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Print Date 23.07.2024

Concentration

(% w/w)

>= 25 - < 40

oponiproponijpropano	01-2119456619-26- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 2,5 - < 5
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317	>= 1 - < 2,5
		Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5





Print Date 23.07.2024

Sikafloor®-264 LO Part A

Revision Date: 23.07.2024

Date of last issue: 10.06.2024

Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX	>= 5 - < 10
For explanation of abbrevia	tions see section 16.	
ECTION 4: First aid measu	ires	
1 Description of first aid mea	asures	
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the docto	or in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exp	oosure.
In case of skin contact	: Take off contaminated clothing and sho Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	 Immediately flush eye(s) with plenty of Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a special 	
If swallowed	: Do not induce vomiting without medical Rinse mouth with water. Do not give milk or alcoholic beverages Never give anything by mouth to an unc	
2 Most important symptoms	and effects, both acute and delayed	
Symptoms	: Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed inform and symptoms.	nation on health effects
Risks	: irritant effects sensitising effects	

Version 11.0

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.



Version 11.0

Print Date 23.07.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

nedia :	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
g from the	e substance or mixture
fire- :	Do not allow run-off from fire fighting to enter drains or water courses.
prod- :	No hazardous combustion products are known
oment :	In the event of fire, wear self-contained breathing apparatus.
:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
	g from the fire- : prod- :

SECTION 6: Accidental release measures

6.1	Personal precautions, protect	tive	equipment and emergency procedures
	Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2	Environmental precautions		
	Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3	Methods and material for cor	ntair	nment and cleaning up
	Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.



Version 11.0

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage,	inc	luding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900



Version 11.0

Print Date 23.07.2024

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment					
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.				
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.				
Environmental exposure controls					
General advice :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Sikafloor®-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024		Version 11.0	Print Date 23.07.2024
Physical state Appearance Colour	:	liquid viscous various	
Odour	:	epoxy-like	
Melting point/ range / Freez- ing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	plosive limits	
Upper explosion limit / Up- per flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	ca. 86 °C Method: closed cup	
Auto-ignition temperature	:	ca. 436 °C	
Decomposition temperature	:	No data available	
рН	:	ca. 6,5 Concentration: 100 %	
Viscosity			
Viscosity, dynamic	:	ca. 3.600 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Couptry NI 00000121707			0 / 17

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor®-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024	Version 11.0	Print Date 23.07.2024				
Density	: ca. 1,6 g/cm3 (20 °C)					
Relative vapour density	: No data available					
Particle characteristics	: No data available					
9.2 Other information No data available						
SECTION 10: Stability and reactivity						
10.1 Reactivity No dangerous reaction known under conditions of normal use.						
10.2 Chemical stability The product is chemically sta	10.2 Chemical stability The product is chemically stable.					
10.3 Possibility of hazardous re	10.3 Possibility of hazardous reactions					

10.3 Possibility of hazardous reactions

Hazardous reactions :		Stable under recommended storage conditions.
-----------------------	--	--

10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	
Not classified due to lack	of data.
Components:	
bis-[4-(2,3-epoxipropoxi	phenyl]propane:
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg

Sikafloor®-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024	Version 11.0	Print Date 23.07.2024
oxirane, mono[(C12-14-all	/loxv)methvl1 derivs.:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/	/kg
benzyl alcohol:		
Acute oral toxicity	: Acute toxicity estimate: 1.200 Method: Acute toxicity estima No. 1272/2008	0 mg/kg ate according to Regulation (EC)
	LD50 Oral (Rat): 1.200 mg/kg	g
p-tert-butylphenyl 1-(2,3-e	oxy)propyl ether:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/	/kg
Acute inhalation toxicity	: LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rabbit): 6.000) mg/kg
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye i Causes serious eye irritation		
Respiratory or skin sensit	sation	
Skin sensitisation May cause an allergic skin r	action.	
Respiratory sensitisation Not classified due to lack of	lata.	
Germ cell mutagenicity Not classified due to lack of	lata.	
Carcinogenicity Not classified due to lack of	lata.	
Reproductive toxicity Not classified due to lack of	lata.	
STOT - single exposure Not classified due to lack of	lata.	
STOT - repeated exposure Not classified due to lack of	lata.	
Aspiration toxicity Not classified due to lack of		



Version 11.0

Print Date 23.07.2024

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

	bis-[4-(2,3-epoxipropoxi)phenyl]propane:					
	Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h			
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h			
	Reaction mass of isomers of	fep	poxy resin BFDGE:			
	Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h			
	Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h			
	Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h			
	benzyl alcohol:					
	Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h			
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h			
12.2	Persistence and degradabili	ty				
	No data available					

No data available

12.3 Bioaccumulative potential

No data available

Sikafloor®-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024 Version 11.0

Print Date 23.07.2024

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---

12.7 Other adverse effects

n		.	ict:	
г	ro	au	ICT.	

Troduot.		
Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances



Version 11.0

Print Date 23.07.2024

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082
14.2 UN proper shipping name		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
14.3 Transport hazard class(es)		
		Class Subsidiary risks
ADR	:	9
IMDG	:	9
ΙΑΤΑ	:	9
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	:	III M6 90 9 (-) Transport in accordance with special provision 375
IMDG Packing group Labels EmS Code Remarks IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group	:::::::::::::::::::::::::::::::::::::::	III 9 F-A, S-F Transport in accordance with 2.10.2.7 of the IMDG-Code 964 Y964 III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024		Version 11.0	Print Date 23.07.2024
Labels Remarks	:	Miscellaneous Transport in accordance with special regulation A	A 197
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	yes	
IMDG Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	
IATA (Cargo) Environmentally hazardous	:	yes	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH Information: All s

All substances contained in our Products are

- registered by our upstream suppliers, and/or

: Not applicable

- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on
the market and use of certain dangerous substances,
mixtures and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 75:

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor®-264 LO Part A



Revision Date: 23.07.2024 Date of last issue: 10.06.2024	Version 11	.0	Print Date 23.07.2024	4
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).	
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable	
Regulation (EC) on substances the layer	nat deplete the ozone	:	Not applicable	
Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu-	:	Not applicable	
Netherlands. Substances of very	high concern (ZZS-list)	:	Quartz (SiO2)	
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable	
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar E2			t and of the Council on the control of ma- RDS	
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 3,27% w/w	
	emissions (integrated po	ollu	4 November 2010 on industrial ution prevention and control) ds (VOC) content: 3,27% w/w	
Other regulations: Take note of Directive 92/85/EEC where applicable.	c regarding maternity prot	ect	tion or stricter national regulations,	
Contains a substance which is su carcinogenic substances (Ministry Employment).			ethanol	
Contains a substance which is su reproductive toxic substances (M and Employment).			ethanol reaction mass of ethylbenzene and xylene	



Version 11.0

Print Date 23.07.2024

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements	
H302 :	Harmful if swallowed.
H315 :	
H317 :	May cause an allergic skin reaction.
H319 :	Causes serious eye irritation.
H332 :	
H360F	May damage fertility.
H411 :	Toxic to aquatic life with long lasting effects.
Full text of other abbreviations	
Acute Tox. :	Acute toxicity
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Eye Irrit. :	Eye irritation
Repr. :	Reproductive toxicity
Skin Irrit. :	Skin irritation
Skin Sens. :	Skin sensitisation
DE TRGS 900 :	Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / TWA :	Time Weighted Average
ADR :	European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS :	Chemical Abstracts Service
DNEL :	Derived no-effect level
EC50 :	Half maximal effective concentration
GHS :	Globally Harmonized System
IATA :	International Air Transport Association
IMDG :	International Maritime Code for Dangerous Goods
LD50 :	Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50 :	Median lethal concentration (concentrations of the chemical in
	air that kills 50% of the test animals during the observation
	period)
MARPOL :	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL :	Occupational Exposure Limit
PBT :	Persistent, bioaccumulative and toxic
PNEC :	Predicted no effect concentration
REACH :	Regulation (EC) No 1907/2006 of the European Parliament
REAGIN .	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC :	Substances of Very High Concern
vPvB	
	Very persistent and very bioaccumulative



Version 11.0

Print Date 23.07.2024

Further information

Classification of the	Classification procedure:	
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN