

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikagard®-675 W ElastoColor

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Surfaces protection, Acrylate coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	72/2008)
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)				
Hazard pictograms	:		•	
Signal word	:	Warning		
Hazard statements	:	H317	May cause an allergic skin reaction.	
Precautionary statements	:	Preventior P261	n: Avoid breathing mist or vapours.	
		P272	Contaminated work clothing should not be allowed out of the workplace.	
		P280	Wear protective gloves.	



Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one (BIT) 2-methyl-2H-isothiazol-3-one (MIT) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: mixture of: 5-chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 55965-84-9, 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5, 2-methyl-2Hisothiazol-3-one (MIT), 2682-20-4. Please use treated articles responsibly.

Sikagard[®]-675 W ElastoColor

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9 01-2120761540-60- XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 specific concentration	>= 0,0025 - < 0,025
		limit Skin Sens. 1; H317 >= 0,05 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 597 mg/kg Acute inhalation tox- icity (dust/mist): 0,4 mg/l	

Sikagard[®]-675 W ElastoColor

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0



2-methyl-2H-isothiazol-3-one (MIT)	2682-20-4 220-239-6 01-2120764690-50- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	>= 0,0025 - < 0,025
		Acute toxicity esti- mate	
		Acute oral toxicity: 200 mg/kg	

Sikagard[®]-675 W ElastoColor

Revision Date: 28.03.2024 Date of last issue: 27.03.2023



mixture of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247- 500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239- 6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9 911-418-6 01-2120764691-48- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 0,0015 - < 0,0025
		Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
		specific concentration limit Skin Corr. 1C; H314 >= $0,6\%$ Skin Irrit. 2; H315 0,06 - < 0,6%	
		0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	
Substances with a workplace expos	sure limit :		
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17-		>= 10 - < 20

Version 4.0

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.



evision Date: 28.03.2024 ate of last issue: 27.03.2023	Version 4.0	Print Date 03.04.202
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a speci	ialist.
If swallowed	: Do not induce vomiting without medica Rinse mouth with water. Do not give milk or alcoholic beverages Never give anything by mouth to an un	S.
.2 Most important symptoms a	d effects, both acute and delayed	
Symptoms	: Allergic reactions See Section 11 for more detailed inforr and symptoms.	mation on health effects
Risks	: sensitising effects	
•	May cause an allergic skin reaction.	needed
A.3 Indication of any immediate Treatment SECTION 5: Firefighting measure	nedical attention and special treatment r : Treat symptomatically.	needed
Treatment	nedical attention and special treatment r : Treat symptomatically.	needed
Treatment	nedical attention and special treatment r : Treat symptomatically.	vater jet/carbon diox-
Treatment SECTION 5: Firefighting meas	 medical attention and special treatment r Treat symptomatically. Sures In case of fire, use water/water spray/wide/sand/foam/alcohol resistant foam/c extinction. 	vater jet/carbon diox-
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from	 medical attention and special treatment r Treat symptomatically. Sures In case of fire, use water/water spray/wide/sand/foam/alcohol resistant foam/c extinction. 	vater jet/carbon diox- hemical powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod-	 medical attention and special treatment r Treat symptomatically. sures In case of fire, use water/water spray/w ide/sand/foam/alcohol resistant foam/c extinction. the substance or mixture 	vater jet/carbon diox- hemical powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- ucts	 medical attention and special treatment r Treat symptomatically. sures In case of fire, use water/water spray/wide/sand/foam/alcohol resistant foam/c extinction. the substance or mixture No hazardous combustion products are 	vater jet/carbon diox- chemical powder for e known

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

Print Date 03.04.2024

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.



Revision Date: 28.03.2024 Date of last issue: 27.03.2023

Version 4.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls



Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

General advice

: Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	ап : :	liquid various
Odour	:	sweet
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	ca. 120 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	vn	losivo limite
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
рН	:	8,5 Concentration: 100 %
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies) Water solubility	:	completely soluble
Partition coefficient: n- octanol/water	:	No data available

Sikagard[®]-675 W ElastoColor



Revision Date: 28.03.2024	
Date of last issue: 27.03.2023	

Version 4.0

Vapour pressure	: 23 hPa
Density	: ca. 1,31 g/cm3 (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	•	No hazards to be specially mentioned.
	-	

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0



2-methyl-2H-isothiazol-3-one (MIT):

Acute oral toxicity : LD50 (Rat): 200 mg/kg

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Assessment : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikagard[®]-675 W ElastoColor

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0



SECTION 12: Ecological information

12.1 Toxicity

Components:

	1,2-benzisothiazol-3(2H)-one (BIT):				
		EC50 (Daphnia (water flea)): 3 mg/l			
	aquatic invertebrates	Exposure time: 48 h			
	2-methyl-2H-isothiazol-3-one (I	MIT):			
	M-Factor (Acute aquatic tox- : icity)	10			
	M-Factor (Chronic aquatic : toxicity)	1			
	mixture of: 5-chloro-2-methyl-4-is one [EC no. 220-239-6] (3:1) (C(I	oothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- M)IT/MIT (3:1)):			
	M-Factor (Acute aquatic tox- : icity)	100			
	M-Factor (Chronic aquatic : toxicity)	100			
12.2	Persistence and degradability				
	No data available				
12.3	Bioaccumulative potential				
	No data available				
12.4	Mobility in soil				
	No data available				
12.5	Results of PBT and vPvB asse	ssment			
	Product:				
	Assessment :	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher			
12.6	Endocrine disrupting propertie	es			
	Product:				
	Assessment :	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation			



Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or minimize wherever possible. Empty containers or liners may retain some product re This material and its container must be disposed of in way. Dispose of surplus and non-recyclable products via a waste disposal contractor. Disposal of this product, solutions and any by-product at all times comply with the requirements of environme protection and waste disposal legislation and any regi local authority requirements. Avoid dispersal of spilled material and runoff and cont soil, waterways, drains and sewers.	esidues. a safe licensed s should ental onal
European Waste Catalogue	08 01 11* waste paint and varnish containing organic vents or other dangerous substances	sol-
Contaminated packaging	15 01 10* packaging containing residues of or contam by dangerous substances	inated

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		

Sikagard[®]-675 W ElastoColor

Print Date 03.04.2024

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

ADR	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
ΙΑΤΑ	: Not regulated as a dangerous good
14.4 Packing group	
ADR	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA (Cargo)	: Not regulated as a dangerous good
IATA (Passenger)	: Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

- All substances contained in our Products are registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable

Sikagard[®]-675 W ElastoColor



Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Version 4.0

tants (recast)								
Netherlands. Substances of very	high concern (ZZS-list)	:	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspeci- fied					
Regulation (EU) No 649/2012 of the European Parlia- : Not applicable ment and the Council concerning the export and import of dangerous chemicals								
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable								
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 0,71% w/w no VOC duties							
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,81% w/w							

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

	H301	:	Toxic if swallowed.			
	H302	:	Harmful if swallowed.			
	H310	:	Fatal in contact with skin.			
	H311	:	Toxic in contact with skin.			
	H314	:	Causes severe skin burns and eye damage.			
	H315	:	Causes skin irritation.			
	H317	:	May cause an allergic skin reaction.			
	H318	:	Causes serious eye damage.			
	H330	:	Fatal if inhaled.			
	H400	:	Very toxic to aquatic life.			
	H410	:	Very toxic to aquatic life with long lasting effects.			
Full text of other abbreviations						
	Acute Tox.	:	Acute toxicity			
	Aquatia Aquita		Chart term (agute) equatio herord			

Sikagard[®]-675 W ElastoColor

Revision Date: 28.03.2024 Date of last issue: 27.03.2023 Print Date 03.04.2024

Version 4.0

Aquatic Chronic Eye Dam. Skin Corr. Skin Irrit. Skin Sens. DE TRGS 900 DE TRGS 900 / TWA ADR CAS	 Long-term (chronic) aquatic hazard Serious eye damage Skin corrosion Skin irritation Skin sensitisation Germany. TRGS 900 - Occupational exposure limit values. Time Weighted Average European Agreement concerning the International Carriage or Dangerous Goods by Road Chemical Abstracts Service 	f
DNEL	Derived no-effect level	
EC50	: Half maximal effective concentration	
GHS	Globally Harmonized System	
IATA	: International Air Transport Association	
IMDG	International Maritime Code for Dangerous Goods	
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)	
LC50	 Median lethal concentration (concentrations of the chemical ir air that kills 50% of the test animals during the observation period) 	ı
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978	
OEL	: Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and toxic	
PNEC	Predicted no effect concentration	
REACH	 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency 	-
SVHC vPvB	Substances of Very High ConcernVery persistent and very bioaccumulative	

Further information

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN