Sikadur-Combiflex[®] CF adhesive rapid Part A



Revision Date: 25.02.2025	
Date of last issue: 09.01.2025	

Version 4.1

Print Date 28.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikadur-Combiflex[®] CF adhesive rapid Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Skin irritation, Category 2	H315: Causes skin irritation.			
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.			
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.			

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Warning

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikadur-Combiflex® CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025	Y	/ersion 4.1	Print Date 28.02.2025
Hazard statements :	H317 M H319 Ca	auses skin irritation. ay cause an allergic skin reaction. auses serious eye irritation. oxic to aquatic life with long lasting	effects.
Precautionary statements :	Prevention: P261 P264 P273 P280	Avoid breathing mist or vapours Wash skin thoroughly after hand Avoid release to the environme Wear protective gloves/ eye pro protection.	dling. nt.
	Response: P333 + P313 P391	If skin irritation or rash occurs: 0 advice/ attention. Collect spillage.	Get medical

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikadur-Combiflex® CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025 Version 4.1

Print Date 28.02.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 %	>= 25 - < 40
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10
(1-methylethyl)-1,1'-biphenyl Contains: diisopropyl-1,1'-biphenyl >= 9,9 %	25640-78-2 247-156-8 01-2119982993-17- XXXX	Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 1 - < 2,5
Substances with a workplace exposure limit :			4 0 5
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 1 - < 2,5

For explanation of abbreviations see section 16.

1

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A



Revision Date: 25.02.2025 Date of last issue: 09.01.2025	Version 4.1	Print Date 28.02.2025
If inhaled	: Move to fresh air. Consult a physician after significant	t exposure.
In case of skin contact	: Take off contaminated clothing and Wash off with soap and plenty of wa If symptoms persist, call a physiciar	ater.
In case of eye contact	 Immediately flush eye(s) with plenty Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a space. 	
If swallowed	 Do not induce vomiting without med Rinse mouth with water. Do not give milk or alcoholic bevera Never give anything by mouth to an 	ages.
4.2 Most important symptoms and	l effects, both acute and delayed	
Symptoms	 Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed in and symptoms. 	formation on health effects
Risks	: Causes skin irritation. May cause an allergic skin reaction Causes serious eye irritation.	
	irritant effects sensitising effects	
4.3 Indication of any immediate m	edical attention and special treatme	ent needed
Treatment	: Treat symptomatically.	
SECTION 5: Firefighting measure	ures	
5.1 Extinguishing media		
Suitable extinguishing media	: In case of fire, use water/water spra ide/sand/foam/alcohol resistant foar extinction.	
5.2 Special hazards arising from t	he substance or mixture	
Specific hazards during fire- fighting	: Do not allow run-off from fire fightin courses.	g to enter drains or water
Hazardous combustion prod-	: No hazardous combustion products	s are known

ucts

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878





Revision Date: 25.02.2025	Version 4.1	Print Date 28.02.2025
Date of last issue: 09.01.2025		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :	Use personal protective equipment. Deny access to unprotected persons.
------------------------	---

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	products

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A



Revision Date: 25.02.2025 Date of last issue: 09.01.2025		Version 4.1	Print Date 28.02.2025
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygien practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the end	sing do not
7.2 Conditions for safe storage, in	ncl	uding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Store in accordance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and applied as directed	ed.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet pr use.	ior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.



Sikadur-Combiflex[®] CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025	Version 4.1	Print Date 28.02.2025
Skin and body protection	: Protective clothing (e.g. Safety shoes a long-sleeved working clothing, long tro and protective boots are additionally re and stirring work.	ousers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear Respirator selection must be based or exposure levels, the hazards of the pro- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: Ensure adequate ventilation. This can exhaust extraction or by general ventil ods for determining inhalation exposur ticular to the mixing / stirring area. In c to keep the concentrations under the c limits then respiration protection meas 	 < 10000 ppm be achieved by local ation. (EN 689 - Meth- re). This applies in par- case this is not sufficent occupational exposure
Environmental exposure cor	trols	
General advice	: Do not flush into surface water or sanit If the product contaminates rivers and respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste grey
Odour	:	epoxy-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikadur-Combiflex[®] CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025	Version 4.1	Print Date 28.02.2025
Flash point	: > 101 °C Method: closed cup	
Auto-ignition temperature	: Not applicable	
Decomposition temperature	: No data available	
рН	: ca. 6 (20 °C) Concentration: 500 g/l 50 %	
Viscosity Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,73 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikadur-Combiflex[®] CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025		Version 4.1	Print Date 28.02.202
10.4 Conditions to avoid			
Conditions to avoid	: No	data available	
10.5 Incompatible materials			
Materials to avoid	: No	data available	
10.6 Hazardous decomposition	n products	ì	
	: No	hazardous decomposition produc	cts are known.
SECTION 11: Toxicological			
	isses as de	efined in Regulation (EC) No 12	72/2008
Acute toxicity Not classified due to lack of	data.		
Components:			
bis-[4-(2,3-epoxipropoxi)p Acute oral toxicity		pane: i0 Oral (Rat): > 5.000 mg/kg	
Acute dermal toxicity	: LD5	i0 Dermal (Rabbit): > 5.000 mg/kg	g
p-tert-butylphenyl 1-(2,3-e	epoxy)prog	ovl ether:	
Acute oral toxicity		0 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	Exp	i0 (Rat): 3.466 mg/l osure time: 4 h t atmosphere: dust/mist	
Acute dermal toxicity	: LD5	i0 Dermal (Rabbit): 6.000 mg/kg	
(1-methylethyl)-1,1'-biphe	nyl:		
Acute oral toxicity		i0 Oral (Rat): 4.650 mg/kg hod: OECD Test Guideline 401	
Skin corrosion/irritation			
Causes skin irritation.			
Serious eye damage/eye i			
Causes serious eye irritation			
Respiratory or skin sensit	isation		
Skin sensitisation			
May cause an allergic skin i	reaction.		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A



Revision Date: 25.02.2025 Ve Date of last issue: 09.01.2025

Version 4.1

Print Date 28.02.2025

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other	:	LC50 (Daphnia magna (Water flea)): 0,167 mg/l
aquatic invertebrates		Exposure time: 48 h

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A



Version 4.1	Print Date 28.02.2025
у	
sessment	
to be either persistent, bioac	ains no components considered cumulative and toxic (PBT), or accumulative (vPvB) at levels of
ties	
ered to have endocrine disru REACH Article 57(f) or Comr	not contain components consid- pting properties according to mission Delegated regulation ion Regulation (EU) 2018/605 at
: An environmental hazard car unprofessional handling or di Toxic to aquatic life with long	
ss	 to be either persistent, bioactivery persistent and very bioa 0.1% or higher erties The substance/mixture does ered to have endocrine disru REACH Article 57(f) or Commit (EU) 2017/2100 or Commiss levels of 0.1% or higher. An environmental hazard car unprofessional handling or displacements.

3.1 Waste treatment methods	
Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.





Revision Date: 25.02.2025 Date of last issue: 09.01.2025	Version 4.1	Print Date 28.02.2025
European Waste Catalogue	: 08 01 11* waste paint and varnish conv vents or other dangerous substances	taining organic sol-
Contaminated packaging	: 15 01 10* packaging containing residue by dangerous substances	es of or contaminated

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 3077	
IMDG	:	UN 3077	
ΙΑΤΑ	:	UN 3077	
14.2 UN proper shipping name			
ADR	:	ENVIRONMENTALL N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, SOLID,
IMDG	:	ENVIRONMENTALL N.O.S. (epoxy resin)	Y HAZARDOUS SUBSTANCE, SOLID,
ΙΑΤΑ	:	Environmentally hazardous substance, solid, n.o.s., Environ- mentally hazardous substance, solid, n.o.s. (epoxy resin)	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	9	
IMDG	:	9	
ΙΑΤΑ	:	9	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks		III M7 90 9 (-) Transport in accorda	nce with special provision 375
IMDG Packing group Labels EmS Code Remarks	: : :	III 9 F-A, S-F Transport in accorda	nce with 2.10.2.7 of the IMDG-Code

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikadur-Combiflex[®] CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025		Version 4.1	Print Date 28.02.2025
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels Remarks	:	956 Y956 III Miscellaneous Transport in accordance with special regulation	A 197
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels 14.5 Environmental hazards	:	956 Y956 III Miscellaneous	
ADR Environmentally hazardous IMDG Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	
IATA (Cargo) Environmentally hazardous 14.6 Special precautions for use	:	yes	
itio opeciai precautions for use			

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

- All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A



vision Date: 25.02.2025 te of last issue: 09.01.2025	Version 4	1.1	Print Date 28.02.20
REACH - Restrictions on the manu the market and use of certain dang mixtures and articles (Annex XVII)	gerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
			Number on list 75
REACH - Candidate List of Substa Concern for Authorisation (Article s		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject (Annex XIV)	ct to authorisation	:	Not applicable
Regulation (EU) No 2024/590 on s plete the ozone layer	substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on per tants (recast)	rsistent organic pollu-	:	Not applicable
Netherlands. Substances of very h	nigh concern (ZZS-list)	:	Quartz (SiO2)
Regulation (EU) No 649/2012 of th ment and the Council concerning t of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EU o jor-accident hazards involving dan E2	gerous substances.		t and of the Council on the control of ma-
	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 0,06% w/w no VOC duties		
	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,06% w/w		

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A



Revision Date: 25.02.2025	Version 4.1	Print Date 28.02.2025
Date of last issue: 09.01.2025		

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

reaction mass of ethylbenzene and xylene

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H400	:	Very toxic to aquatic life.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / TWA	:	Time Weighted Average
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
Nuptry NI 00000119901		15 / -

Country NL 000000118801

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur-Combiflex[®] CF adhesive rapid Part A

Revision Date: 25.02.2025 Date of last issue: 09.01.2025	Version 4.1	Print Date 28.02.2025

: Very persistent and very bioaccumulative

vPvB

Classification of th	Classification procedure:	
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN

