

Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor®-381 ECF Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1C	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2	H341: Suspected of causing genetic defects.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

tion (EU) 2020/878

Sikafloor®-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023		V	ersion 6.0	Print Date 23.07.2024
Hazard pictograms	:			>
Signal word	:	Danger		
Hazard statements	:	H317 Ma H341 Sus H360F Ma	uses severe skin burns and eye d y cause an allergic skin reaction. spected of causing genetic defect y damage fertility. kic to aquatic life with long lasting	S.
Precautionary statements	:	Prevention: P201 P273 P280	Obtain special instructions befo Avoid release to the environme Wear protective gloves/ protect eye protection/ face protection.	nt.
		Response: P303 + P361 + P P304 + P340 + P	ately all contaminated clothing. with water.	Rinse skin erson to fresh eathing. Im-
		P305 + P351 +		se cautiously Remove con- to do. Con-
		P308 + P313 P391	IF exposed or concerned: Get r vice/ attention. Collect spillage.	nedical ad-

Hazardous components which must be listed on the label:

Reaction mass of isomers of epoxy resin BFDGE Trimethylolpropane triglycidylether bis-[4-(2,3-epoxipropoxi)phenyl]propane p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 10 - < 20
Trimethylolpropane triglycidylether	Not Assigned 701-135-4 01-2120078341-60- XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Muta. 2; H341 Repr. 1B; H360F Aquatic Chronic 2; H411	>= 5 - < 10
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 2,5 - < 5

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor®-381 ECF Part A

Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 2,5 - < 5
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
p-tert-butylphenyl 1-(2,3- epoxy)propyl ether	3101-60-8 221-453-2 01-2119959496-20- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,5 - < 1
Substances with a workplace expo	sure limit :		
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023		Version 6.0	Print Date 23.07.2024
	In of Co Re	e damage and blindness. the case of contact with eyes, rinse im water and seek medical advice. ontinue rinsing eyes during transport to emove contact lenses. eep eye wide open while rinsing.	
If swallowed	Ri Do	o not induce vomiting without medical a nse mouth with water. o not give milk or alcoholic beverages. ever give anything by mouth to an unco	
4.2 Most important symptoms an	d effe	cts, both acute and delayed	
Symptoms	: Al De Se	ergic reactions ermatitis ee Section 11 for more detailed informa d symptoms.	ation on health effects
Risks	CC SE	ealth injuries may be delayed. rrosive effects nsitising effects kic effects for reproduction	
	Ca Su Ma	ay cause an allergic skin reaction. auses serious eye damage. Ispected of causing genetic defects. ay damage fertility. auses severe burns.	
4.3 Indication of any immediate n Treatment		Il attention and special treatment ne eat symptomatically.	eded
mediment	. 11	ear symptomatically.	
SECTION 5: Firefighting meas	ures		
5.1 Extinguishing media			
Suitable extinguishing media	ide	case of fire, use water/water spray/wa e/sand/foam/alcohol resistant foam/che tinction.	
5.2 Special hazards arising from	the su	bstance or mixture	
Specific hazards during fire- fighting		o not allow run-off from fire fighting to e urses.	enter drains or water
Hazardous combustion prod- ucts	: No	hazardous combustion products are l	known



Revision Date: 23.07.2024 Date of last issue: 30.11.2023		Version 6.0	Print Date 23.07.2024
5.3 Advice for firefighters Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ning apparatus.
Further information	:	Collect contaminated fire extinguishing water must not be discharged into drains. Fire residues and contaminated fire extinguisl	

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
2 Environmental precautions		

6.2 Environmental precautions ontol pr Do not fluch into · · ·

Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
-----------------------------	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Pregnant women or women of child-bearing age should not be exposed to this product.
	Follow standard hygiene measures when handling chemical products



Revision Date: 23.07.2024 Date of last issue: 30.11.2023	Version 6.0	Print Date 23.07.2024
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.	
Hygiene measures :	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for safe storage, inc	luding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-v place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Sto ance with local regulations.	refully re-
Further information on stor- : age stability	No decomposition if stored and applied as direc	ted.
7.3 Specific end use(s)		
Specific use(s) :	Consult most current local Product Data Sheet puse.	prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further informative through the ski	ation: Identifies the in, Indicative	possibility of signi	ficant uptake
		STEL	100 ppm 442 mg/m3	2000/39/EC
		TLV-8hr	47,5 ppm 210 mg/m3	NL WG
	Further information: Skin notation			
		TLV-15 min	100 ppm 442 mg/m3	NL WG

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Sikafloor®-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023	Version 6.	0 Print	Date 23.07.2024
Eye/face protection	: Safety glasses with side Eye wash bottle with pu Wear eye/face protectio		
Hand protection	proved standard must b	ervious gloves complying with a e worn at all times when handlir erence number EN 374. Follow r	ng
	Suitable for short time u Butyl rubber/nitrile rubbe Contaminated gloves sh Suitable for permanent o Viton gloves (0.4 mm), breakthrough time >30 r	nould be removed. exposure:	95:
Skin and body protection	long-sleeved working clo	Safety shoes acc. to EN ISO 20 othing, long trousers). Rubber a additionaly recommended for r	prons
Respiratory protection	Respirator selection mu exposure levels, the haz ing limits of the selected organic vapor filter (Typ A1: < 1000 ppm; A2: < 5 Ensure adequate ventila exhaust extraction or by ods for determining inha ticular to the mixing / stil to keep the concentration		bated e work- bocal Meth- n par- fficent bsure
Environmental exposure c	ntrols		

Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid various
Odour	:	epoxy-like
Melting point/ range / Freez- ing point	:	No data available

Version 6.0

Sikafloor[®]-381 ECF Part A

Revision Date: 23.07.2024



Print Date 23.07.2024

of last issue: 30.11.2023		Version 6.0	Print Date 23.07
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	losive limits	
Upper explosion limit / Up- per flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 101 °C Method: closed cup	
Auto-ignition temperature	:	Not applicable	
Decomposition temperature	:	No data available	
рН	:	ca. 7 Concentration: 100 %	
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
		0,01 hPa	
Density	:	ca. 1,69 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	



Revision Date: 23.07.2024 Date of last issue: 30.11.2023

Version 6.0

Print Date 23.07.2024

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	Stable under recommended storage conditions.

10.4 Conditions to avoid

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified due to lack of da	ıta.				
Components:					
Trimethylolpropane triglycid	yle	ther:			
Acute oral toxicity	:	LD50 Oral (Rat): 3.398 mg/kg			
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg			
bis-[4-(2,3-epoxipropoxi)phenyl]propane:					
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg			
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg			
benzyl alcohol:					
Acute oral toxicity	:	Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008			



Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

LD50 Oral (Rat): 1.200 mg/kg

Acute oral toxicity	: LD50 Oral (Rat): 3.523 mg/kg
p-tert-butylphenyl 1-(2,3-e	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 Dermal (Rabbit): 6.000 mg/kg
Skin corrosion/irritation Causes severe burns.	
Serious eye damage/eye in Causes serious eye damage	
Respiratory or skin sensit	isation
Skin sensitisation May cause an allergic skin r	reaction.
Respiratory sensitisation Not classified due to lack of	data.
Germ cell mutagenicity Suspected of causing genet	tic defects.
Carcinogenicity Not classified due to lack of	data.
Reproductive toxicity May damage fertility.	
STOT - single exposure Not classified due to lack of	data.
STOT - repeated exposure Not classified due to lack of	
Aspiration toxicity Not classified due to lack of	data.
I.2 Information on other haza	ards
Endocrine disrupting prop	perties
Product:	• The substance/mixture does not contain compo

: The substance/mixture does not contain components consid-



Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

- 12.1 Toxicity
 - **Components:**

Reaction mass of isomers of epoxy resin BFDGE:

Toxicity to fish :	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h
Toxicity to daphnia and other : aquatic invertebrates	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h
Toxicity to algae/aquatic : plants	EC50 (algae): 1,8 mg/l Exposure time: 72 h

Trimethylolpropane triglycidylether:

Toxicity to algae/aquatic :	ErC50 (Pseudokirchneriella subcapitata (microalgae)): 9 mg/l
plants	Exposure time: 72 h
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	EC50: 3,7 mg/l Exposure time: 48 d Species: Daphnia magna (Water flea)

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h
benzyl alcohol: Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h

Toxicity to daphnia and other:EC50 (Daphnia magna (Water flea)): > 100 mg/laquatic invertebratesExposure time: 48 h

reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox-	:	NOEC: > 1,3 mg/l
icity)		Exposure time: 56 d
		Species: Oncorhynchus mykiss (rainbow trout)

Sikafloor®-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

Toxicity to daphnia and other	:	NOEC: 1,17 mg/l
aquatic invertebrates (Chron-		Exposure time: 7 d
ic toxicity)		Species: Daphnia (water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessmen	t
Assessmen	ι

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should



Revision Date: 23.07.2024 Date of last issue: 30.11.2023		Version 6.0	Print Date 23.07.2024
	at all times comply with the requirements of protection and waste disposal legislation an local authority requirements. Avoid dispersal of spilled material and runot soil, waterways, drains and sewers.	te disposal legislation and any regional irements. spilled material and runoff and contact with	
European Waste Catalogue	:	08 01 11* waste paint and varnish containinvents or other dangerous substances	ng organic sol-
Contaminated packaging	:	15 01 10* packaging containing residues of by dangerous substances	or contaminated

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	UN 1760		
IMDG	:	UN 1760		
ΙΑΤΑ	:	UN 1760		
14.2 UN proper shipping name				
ADR	:	CORROSIVE LIQUID, N.O.S. (Trimethylolpropane triglycidylether, epoxy resin)		
IMDG	:	CORROSIVE LIQUID, N.O.S. (Trimethylolpropane triglycidylether, epoxy resin)		
ΙΑΤΑ	:	Corrosive liquid, n.o.s. (Trimethylolpropane triglycidylether, epoxy resin)		
14.3 Transport hazard class(es)				
		Class Subsidiary risks		
ADR	:	8		
IMDG	:	8		
ΙΑΤΑ	:	8		
14.4 Packing group				
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III C9 80 8 (E)		
IMDG Packing group Labels EmS Code	:	III 8 F-A, S-B		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor[®]-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023			Version 6.0	F	Print Date 23.07.2024
Remarks	:	Alkalis			
IATA (Cargo) Packing instruction (cargo	:	856			
aircraft) Packing instruction (LQ) Packing group Labels	:	Y841 III Corrosive			
IATA (Passenger) Packing instruction (passen- ger aircraft)	:	852			
Packing instruction (LQ) Packing group Labels	:	Y841 III Corrosive			
14.5 Environmental hazards					
ADR Environmentally hazardous	:	yes			
IMDG Marine pollutant	:	yes			
IATA (Passenger) Environmentally hazardous	:	yes			
IATA (Cargo)					

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

Sikafloor®-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023	Version 6.	0	Print Date 23.07.2024
the market and use of certain dan mixtures and articles (Annex XVII			lowing entries should be considered: Number on list 3
			Number on list 75:
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
Regulation (EC) on substances th layer	at deplete the ozone	:	Not applicable
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu-	:	Not applicable
Netherlands. Substances of very	high concern (ZZS-list)	:	Quartz (SiO2)
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar E2			and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds Is (VOC) content: 6,14% w/w
	emissions (integrated po	ollu	4 November 2010 on industrial ution prevention and control) Is (VOC) content: 6,15% w/w

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

reaction mass of ethylbenzene and xylene



Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H226		Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H302	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	÷	Causes skin irritation.
H317	÷	May cause an allergic skin reaction.
H318	÷	Causes serious eye damage.
H319	÷	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H341	:	Suspected of causing genetic defects.
H360F	:	May damage fertility.
H373	:	May cause damage to organs through prolonged or repeated
		exposure if inhaled.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Muta.	:	Germ cell mutagenicity
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
NL WG	:	Netherlands. Law on Labour conditions - Occupational Expo-
		sure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
DE TRGS 900 / TWA	:	Time Weighted Average
NL WG / TLV-8hr	:	Time Weighted Average
NL WG / TLV-15 min	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of
Suptry NI 10000010727		47/4

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-381 ECF Part A



Revision Date: 23.07.2024 Date of last issue: 30.11.2023 Version 6.0

Print Date 23.07.2024

CAS DNEL EC50 GHS	 Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System 	
IATA	: International Air Transport Association	
IMDG	: International Maritime Code for Dangerous Goods	
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group o test animals)	of
LC50	: Median lethal concentration (concentrations of the chemical air that kills 50% of the test animals during the observation period)	in
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978	
OEL	: Occupational Exposure Limit	
PBT	: Persistent, bioaccumulative and toxic	
PNEC	: Predicted no effect concentration	
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency	•
SVHC	: Substances of Very High Concern	
vPvB	: Very persistent and very bioaccumulative	

Further information

Classification of the mixture:		Classification procedure:
Skin Corr. 1C	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Muta. 2	H341	Calculation method
Repr. 1B	H360F	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN