

Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor® TC 374

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127 Skin corrosion, Sub-category 1B	72/2008) H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger



Sikafloor® TC 374

Revision Date: 02.06.2024 Date of last issue: 18.05.2024		Version 1.2	Print Date 06.06.2024	
Hazard statements :	H314 H317 H411	Causes severe skin burns a May cause an allergic skin Toxic to aquatic life with lor	reaction.	
Precautionary statements :	Prevention	n:		
	P273 P280	Avoid release to the e Wear protective glove eye protection/ face pl	s/ protective clothing/	
	Response	Response:		
	P303 + P3	61 + P353 IF ON SKIN (or ately all contaminated with water.	,	
	P304 + P3	40 + P310 IF INHALED: Re air and keep comforta mediately call a POIS		
	P305 + P3 P391	51 + P338 + P310 IF IN E	YES: Rinse cautiously minutes. Remove con- and easy to do. Con-	

Hazardous components which must be listed on the label:

Reaction product of BADGE with MXDA 1,3-bis[3-(dimethylamino)propyl]urea

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-
tion (EU) 2020/878

CAS-No.

113930-69-1

500-302-7

Registration number

EC-No.

SECTION 3: Composition/information on ingredients

Sikafloor® TC 374

Components Chemical name

Reaction product of BADGE with

3.2 Mixtures

MXDA

Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Classification

Skin Corr. 1B; H314

Eye Dam. 1; H318

Print Date 06.06.2024

Concentration

(% w/w)

>= 40 - < 60

	01-2119965162-39- XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 25 - < 40
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	
Polyoxypropylene diamine	9046-10-0 618-561-0 01-2119557899-12- XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 10 - < 20
1,3-bis[3- (dimethylamino)propyl]urea	52338-87-1 257-861-2 01-2120781639-37- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 5 - < 10
1,3-Cyclohexanedimethanamine	2579-20-6 219-941-5 01-2119543741-41- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 3 - < 5
		Acute toxicity esti- mate	
		Acute oral toxicity: 780 mg/kg Acute dermal toxicity: 1.700 mg/kg	



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor[®] TC 374

Revision Date: 02.06.2024 Date of last issue: 18.05.2024	Version 1.2	2	Print Date 06.06.2024
ethanol	64-17-5 200-578-6 01-2119457610-43- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid meas	ures
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms a	nd effects, both acute and delayed
Symptoms	: Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns.



Revision Date: 02.06.2024 Version 1.2 Print Date 06.06.2024 Date of last issue: 18.05.2024 Health injuries may be delayed. corrosive effects sensitising effects 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction. 5.2 Special hazards arising from the substance or mixture Specific hazards during fire-: Do not allow run-off from fire fighting to enter drains or water fighting courses. Hazardous combustion prod- : No hazardous combustion products are known ucts 5.3 Advice for firefighters Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters Further information Collect contaminated fire extinguishing water separately. This : must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	tive equipment and emergency procedures
Personal precautions	: Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cor	ntainment and cleaning up
Methods for cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Country NI 10000057291	



Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	incl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
Country NL 10000057381				6 / 17



Sikafloor® TC 374

Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

		of exposure)	ters *	
ethanol	64-17-5	TLV-8hr	137 ppm	NL WG
			260 mg/m3	
	Further information: Carcinogenic substances, Skin notation			
		TLV-15 min	1.000 ppm	NL WG
			1.900 mg/m3	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.	
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.	
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.	
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.	

Environmental exposure controls

General advice

: Do not flush into surface water or sanitary sewer system.



Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

•	Physical state Colour		liquid colourless
	Odour	:	amine-like
	Melting point/range / Freezing point	:	No data available
	Boiling point/boiling range	:	No data available
	Flammability (solid, gas)	:	No data available
	Upper/lower flammability or e	avn	losive limits
	Upper explosion limit / Up- per flammability limit	-	
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	> 101 °C Method: closed cup
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	No data available
	рН	:	Not applicable substance/mixture is non-soluble (in water)
	Viscosity		
	Viscosity, dynamic	:	ca. 230 mPa.s (20 °C)
	Viscosity, kinematic	:	No data available
	Solubility(ies)		
	Water solubility	:	partly soluble

egula-



Revision Date: 02.06.2024Version 1.2Print Date 06.06.2024Date of last issue: 18.05.2024

Partition coefficient: n- octanol/water	: No data available
Vapour pressure	: 4,8 hPa
Density	: ca. 1,06 g/cm3 (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

data available
)

10.6 Hazardous decomposition products

No hazardous decomposition products are known.



Revision Date: 02.06.2024 Date of last issue: 18.05.2024

Acute toxicity

Version 1.2

Print Date 06.06.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Not classified due to lack of da	ata.				
Components:					
benzyl alcohol:					
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg			
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method			
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist			
		Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method			
Polyoxypropylene diamine:					
Acute oral toxicity	:	LD50 Oral (Rat): 2.880 mg/kg			
1,3-Cyclohexanedimethanar	min	e.			
Acute oral toxicity	:	LD50 Oral (Rat): 780 mg/kg			
		Acute toxicity estimate: 780 mg/kg Method: Calculation method			
Acute dermal toxicity	:	LD50 Dermal (Rat): 1.700 mg/kg			
		Acute toxicity estimate: 1.700 mg/kg Method: Calculation method			
Skin corrosion/irritation Causes severe burns.					
Serious eye damage/eye irritation					
Causes serious eye damage.					
Respiratory or skin sensitisation					
Skin sensitisation					
May cause an allergic skin rea	actio	on.			
Respiratory sensitisation					

Not classified due to lack of data.

Sikafloor® TC 374

Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Polyoxypropylene diamine: Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity)	:	EC50: 80 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)



Sikafloor[®] TC 374



Revision Date: 02.06.2024 Date of last issue: 18.05.2024

Version 1.2

Print Date 06.06.2024

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

1104401	
Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	
Product:	

Additional ecological infor- mation	u	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Sikafloor® TC 374

Jika®

Revision Date: 02.06.2024 Date of last issue: 18.05.2024

14.1 UN number or ID number

Version 1.2

Print Date 06.06.2024

SECTION 14: Transport information

ADR : UN 2735 IMDG : UN 2735 ΙΑΤΑ : UN 2735 14.2 UN proper shipping name ADR : AMINES, LIQUID, CORROSIVE, N.O.S. (Reaction product of BADGE with MXDA) IMDG : AMINES, LIQUID, CORROSIVE, N.O.S. (Reaction product of BADGE with MXDA) ΙΑΤΑ : Amines, liquid, corrosive, n.o.s. (Reaction product of BADGE with MXDA) 14.3 Transport hazard class(es) Class Subsidiary risks ADR 8 2 IMDG 8 ΙΑΤΑ : 8 14.4 Packing group ADR Packing group Ш · Classification Code C7 Hazard Identification Number : 80 Labels 8 Tunnel restriction code : (E) IMDG Ш Packing group : Labels 2 8 EmS Code : F-A, S-B IATA (Cargo) Packing instruction (cargo 855 : aircraft) Packing instruction (LQ) Y840 : Packing group Ш 2 Labels Corrosive : IATA (Passenger) Packing instruction (passen-851 : ger aircraft) Packing instruction (LQ) Y840 2 Packing group :

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor® TC 374



Revision Date: 02.06.2024 Date of last issue: 18.05.2024		Version 1.2		Print Date 06.06.2024
Labels	:	Corrosive		
14.5 Environmental hazards				
ADR Environmentally hazardous	:	yes		
IMDG Marine pollutant	:	yes		
IATA (Passenger) Environmentally hazardous	:	yes		
IATA (Cargo) Environmentally hazardous	:	yes		
14.6 Special precautions for user				

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the following entries should be considered: the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Number on list 75, 3 **REACH - Candidate List of Substances of Very High** : None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation : Not applicable (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-: Not applicable

Sikafloor® TC 374



Revision Date: 02.06.2024 Date of last issue: 18.05.2024	Version 1.2	Print Date 06.06.2024
plete the ozone layer		
Regulation (EU) 2019/1021 on petants (recast)	ersistent organic pollu- : Not applic	able
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals		able
Seveso III: Directive 2012/18/EU jor-accident hazards involving da E2	of the European Parliament and of the ingerous substances. ENVIRONMENTAL HAZARDS	Council on the control of ma-
Volatile organic compounds :	Law on the incentive tax for volatile of (VOCV) Volatile organic compounds (VOC) co	
	Directive 2010/75/EU of 24 Novembe emissions (integrated pollution prever Volatile organic compounds (VOC) co	ntion and control)
Contains a substance which is su carcinogenic substances (Ministr Employment).		
Contains a substance which is sure reproductive toxic substances (Mand Employment).		
15.2 Chemical safety assessment		

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H302	:	Harmful if swallowed.
H312	:	Harmful in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Sikafloor® TC 374

Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

Full text of other abbreviations

Acute Tox. Aquatic Chronic Eye Dam. Eye Irrit. Flam. Liq. Skin Corr.	:	Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Flammable liquids Skin corrosion
Skin Irrit. Skin Sens.	:	Skin irritation Skin sensitisation
NL WG	:	Netherlands. Law on Labour conditions - Occupational Expo- sure Limits
NL WG / TLV-8hr	:	Time Weighted Average
NL WG / TLV-15 min	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method





Revision Date: 02.06.2024 Date of last issue: 18.05.2024 Version 1.2

Print Date 06.06.2024

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN