

Version 6.0

Print Date 15.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaCure[®]-8100/00 C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single ex-	H335: May cause respiratory irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C

Revision Date: 14.11.2024



Print Date 15.11.2024

Date of last issue: 09.07.2024 posure, Category 3, Respiratory system Specific target organ toxicity - repeated H373: May cause damage to organs through prolonged or repeated exposure. exposure, Category 2 2.2 Label elements Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms Signal word Danger 1 Highly flammable liquid and vapour. Hazard statements H225 H315 Causes skin irritation. H317 May cause an allergic skin reaction. Causes serious eve irritation. H319 H332 Harmful if inhaled. May cause allergy or asthma symptoms or breath-H334 ing difficulties if inhaled. H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336 H351 Suspected of causing cancer. May cause damage to organs through prolonged H373 or repeated exposure. Prevention: Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. If experiencing respiratory symptoms: Call a P342 + P311 POISON CENTER/ doctor. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Hazardous components which must be listed on the label: ethyl acetate Diphenylmethanediisocyanate, isomeres and homologues Isocyanic acid, polymethylenepolyphenylene ester, polymer with 2,2',2"-nitrilotris[ethanol]

Version 6.0

Revision Date: 14.11.2024

Date of last issue: 09.07.2024

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
ethyl acetate	141-78-6 205-500-4 01-2119475103-46- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 60 - < 80



Print Date 15.11.2024

Version 6.0

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure[®]-8100/00 C



Revision Date: 14.11.2024 Date of last issue: 09.07.2024 Version 6.0

Diphenylmethanediisocyanate,	9016-87-9	Acute Tox. 4; H332	>= 10 - < 20
isomeres and homologues	Not Assigned	Skin Irrit. 2; H315	
		Eye Irrit. 2; H319	
		Resp. Sens. 1; H334	
		Skin Sens. 1; H317	
		Carc. 2; H351	
		STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	
		specific concentration	
		limit	
		Eye Irrit. 2; H319	
		>= 5 %	
		specific concentration	
		limit	
		Resp. Sens. 1; H334	
		>= 0,1 %	
		specific concentration	
		limit	
		Skin Irrit. 2; H315	
		>= 5 %	
		specific concentration	
		limit	
		STOT SE 3; H335	
		>= 5 %	
Isocyanic acid, polymethylenepol-	61909-68-0	Acute Tox. 4; H332	>= 10 - < 20
yphenylene ester, polymer with	Not Assigned	Skin Irrit. 2; H315	
2,2',2"-nitrilotris[ethanol]		Eye Irrit. 2; H319	
		Skin Sens. 1; H317	
		Carc. 2; H351 STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	
butanone	78-93-3	Flam. Liq. 2; H225	>= 1 - < 2,5
	201-159-0	Eye Irrit. 2; H319	
	01-2119457290-43-	STOT SE 3; H336	
	XXXX	(Central nervous	
		system)	
		EUH066	

For explanation of abbreviations see section 16.



Version 6.0

Print Date 15.11.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	 Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.
Risks	 irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.



Revision Date: 14.11.2024 Date of last issue: 09.07.2024		Version 6.0	Print Date 15.11.2024
		May cause damage to organs through prolonge exposure.	d or repeated
4.3 Indication of any immediate r	neo	lical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	ur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	:	Water	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	ig apparatus.
Further information	:	Use water spray to cool unopened containers.	
SECTION 6: Accidental releas	e r	neasures	
6.1 Personal precautions, protec	tiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment.	

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions		
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C



Revision Date: 14.11.2024 Date of last issue: 09.07.2024 Version 6.0

Print Date 15.11.2024

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling :	 Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, inc	cluding any incompatibilities
Requirements for storage : areas and containers	Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
Further information on stor- : age stability	No decomposition if stored and applied as directed.
7.3 Specific end use(s)	
Specific use(s) :	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.



Version 6.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m3	2017/164/EU		
	Further inform	Further information: Indicative				
		TWA	200 ppm 734 mg/m3	2017/164/EU		
		TWA	400 ppm 1.500 mg/m3	DE TRGS 900		
		TLV-8hr	200 ppm 734 mg/m3	NL WG		
		TLV-15 min	400 ppm 1.468 mg/m3	NL WG		
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	AGW (Inhalable fraction)	0,05 mg/m3 (MDI)	DE TRGS 900		
	Further information: Senate commission for the review of com- pounds at the work place dangerous for the health has also esta lished a BEI-value for the same OEL value in the 'MAK- and BA' value list'					
butanone	78-93-3	TWA	200 ppm 600 mg/m3	2000/39/EC		
	Further information: Indicative					
		STEL	300 ppm 900 mg/m3	2000/39/EC		
		TLV-8hr	197 ppm 590 mg/m3	NL WG		
	Further information: Skin notation					
		TLV-15 min	300 ppm 900 mg/m3	NL WG		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal	protective	equipment
1 01 001141	p. 0.000.00	oquipinone

Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Cuitable for about time, use or protection excited enlack ex-

Suitable for short time use or protection against splashes:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure[®]-8100/00 C

_



Revision Date: 14.11.2024 Date of last issue: 09.07.2024	Version 6.0	Print Date 15.11.2024
	Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN long-sleeved working clothing, long trousers). Ru and protective boots are additionaly recommend and stirring work.	ubber aprons
Respiratory protection :	In case of inadequate ventilation wear respirator Respirator selection must be based on known or exposure levels, the hazards of the product and ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifyi respirator complying with an approved standard sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 p Ensure adequate ventilation. This can be achiev exhaust extraction or by general ventilation. (EN ods for determining inhalation exposure). This ap ticular to the mixing / stirring area. In case this is to keep the concentrations under the occupation limits then respiration protection measures must Ensure adequate ventilation, especially in confin	r anticipated the safe work- ng or air-fed if a risk as- opm ed by local 689 - Meth- oplies in par- onot sufficent al exposure be used.
Environmental exposure control	ols	
General advice :	Prevent product from entering drains. If the product contaminates rivers and lakes or d	rains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid various
Odour	:	solvent-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	> 50 °C
 Flammability (solid, gas)	:	No data available

SAFETY DATA SHEET according to Regulation (EC) No. 19

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C



Revision Date: 14.11.2024 Date of last issue: 09.07.2024 Version 6.0

Print Date 15.11.2024

Upper/lower flammability or explosive limits Upper explosion limit / Up- : 11,5 %(V) per flammability limit					
Lower explosion limit / Lower flammability limit	:	2,1 %(V)			
Flash point	:	ca4 °C Method: closed cup			
Auto-ignition temperature	:	427 °C			
Decomposition temperature	:	No data available			
рН	:	Not applicable substance/mixture is non-soluble (in water)			
Viscosity Viscosity, dynamic	:	ca. 10 mPa.s (20 °C)			
Viscosity, kinematic	:	No data available			
Solubility(ies) Water solubility	:	No data available			
Partition coefficient: n- octanol/water	:	No data available			
Vapour pressure	:	99,9915 hPa			
Density	:	ca. 1 g/cm3 (20 °C)			
Relative vapour density	:	No data available			
Particle characteristics	:	No data available			

9.2 Other information

No data available



Revision Date: 14.11.2024				
Date of last issue: 09.07.2024				

Version 6.0

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.	
		Vapours may form explosive mixture with air.	
10.4 Conditions to avoid			
Conditions to avoid	:	Heat, flames and sparks.	
		Avoid moisture.	
10.5 Incompatible materials			
Materials to avoid	:	Oxidizing agents Acids Bases	

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if inhaled.		
Components:		
ethyl acetate: Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): ca. 1.600 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg

Diphenylmethanediisocyanate, isomeres and homologues:

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C



Revision Date: 14.11.2024 Date of last issue: 09.07.2024		Version 6.0	Print Date 15.11.2024				
Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg					
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is r short term inhalation.	noderately toxic after				
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg					
butanone:							
Acute oral toxicity	:	LD50 Oral (Rat): 3.300 mg/kg					
Acute inhalation toxicity	:	LC50 (Rat): 36 mg/l Exposure time: 4 h Test atmosphere: vapour					
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg					
Skin corrosion/irritation Causes skin irritation.							
	Serious eye damage/eye irritation Causes serious eye irritation. Respiratory or skin sensitisation						
Respiratory or skin sensitis							
Skin sensitisation May cause an allergic skin re	Skin sensitisation May cause an allergic skin reaction.						
Respiratory sensitisation May cause allergy or asthma							
Germ cell mutagenicity Not classified due to lack of c							
Carcinogenicity Suspected of causing cancer	Carcinogenicity Suspected of causing cancer.						
Reproductive toxicity Not classified due to lack of c	data.						
STOT - single exposure							
May cause respiratory irritation May cause drowsiness or diz		SS.					
STOT - repeated exposure							
	s thr	ough prolonged or repeated exposure.					
Aspiration toxicity Not classified due to lack of c	data.						



Version 6.0

Print Date 15.11.2024

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment


: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid-
	ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation
	(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
	levels of 0.1% or higher.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878





Revision Date: 14.11.2024 Date of last issue: 09.07.2024 Version 6.0

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or mi wherever possible. Empty containers or liners may retain some product This material and its container must be disposed way. Dispose of surplus and non-recyclable products we waste disposal contractor. Disposal of this product, solutions and any by-pro- at all times comply with the requirements of enviro protection and waste disposal legislation and any local authority requirements. Avoid dispersal of spilled material and runoff and soil, waterways, drains and sewers.	uct residues. of in a safe ria a licensed oducts should onmental regional
European Waste Catalogue	08 01 11* waste paint and varnish containing org vents or other dangerous substances	anic sol-
Contaminated packaging	15 01 10* packaging containing residues of or co by dangerous substances	ntaminated

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1866
IMDG	:	UN 1866
ΙΑΤΑ	:	UN 1866
14.2 UN proper shipping name		
ADR	:	RESIN SOLUTION
IMDG	:	RESIN SOLUTION
ΙΑΤΑ	:	Resin solution
14.3 Transport hazard class(es)		

Subsidiary risks

Class

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C



evision Date: 14.11.2024 ate of last issue: 09.07.2024		Version 6.0	Print Date 15.11.202
ADR		3	
IMDG		3	
IATA	:	3	
	·	3	
4.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: : : : : : : : : : : : : : : : : : : :	II F1 33 3 (D/E)	
IMDG Packing group Labels EmS Code	:	II 3 F-E, <u>S-E</u>	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group	:	353 Y341 II	
Labels	:	Flammable Liquids	
4.5 Environmental hazards			
ADR Environmentally hazardous	:	no	
IMDG Marine pollutant	:	no	
IATA (Passenger) Environmentally hazardous	:	no	
IATA (Cargo) Environmentally hazardous	:	no	
4.6 Special precautions for user			

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



Version 6.0

Print Date 15.11.2024

SECTION 15: Regulatory information

15.1 Safety, health and environ International Chemical Wea Schedules of Toxic Chemica	pons Convention (CWC)	tion :	specific for the substance or mixture Not applicable		
REACH Information:	All substances contain - registered by our up - registered by us, and - excluded from the re - exempted from the r	strea d/or ègula	eam suppliers, and/or r lation, and/or		
REACH - Restrictions on the market and use of certa mixtures and articles (Anne:	in dangerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3		
			Number on list 56: Diphenylme- thanediisocyanate, isomeres and homologues		
			Number on list 74: Diphenylme- thanediisocyanate, isomeres and homologues		
			Number on list 75:		
REACH - Candidate List of Concern for Authorisation (A		:	None of the components are listed (=> 0.1 %).		
REACH - List of substances (Annex XIV)	s subject to authorisation	:	Not applicable		
Regulation (EC) on substan layer	ices that deplete the ozone	:	Not applicable		
Regulation (EU) 2019/1021 tants (recast)	on persistent organic pollu-	:	Not applicable		
Regulation (EU) No 649/207 ment and the Council conce of dangerous chemicals		:	Not applicable		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C



Print Date 15.11.2024

Revision Date: 14.11.2024 Date of last issue: 09.07.2024 Version 6.0

Seveso III: Directive 2012/18/ jor-accident hazards involving P5c		of the European Parliament and of the Council on the control of ma- ngerous substances. FLAMMABLE LIQUIDS
Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 65,69% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 65,69% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements			
H225	:	Highly flammable liquid and vapour.	
H315	:	Causes skin irritation.	
H317	:	May cause an allergic skin reaction.	
H319	:	Causes serious eye irritation.	
H332	:	Harmful if inhaled.	
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.	
H335	:	May cause respiratory irritation.	
H336	:	May cause drowsiness or dizziness.	
H351	:	Suspected of causing cancer.	
H373	:	May cause damage to organs through prolonged or repeated exposure.	
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.	
Full text of other abbreviations			
Acute Tox.	:	Acute toxicity	
Carc.	:	Carcinogenicity	
Eye Irrit.	:	Eye irritation	
Flam. Liq.	:	Flammable liquids	
Resp. Sens.	:	Respiratory sensitisation	
Skin Irrit.	:	Skin irritation	
Skin Sens.	:	Skin sensitisation	
STOT RE	:	Specific target organ toxicity - repeated exposure	
STOT SE	:	Specific target organ toxicity - single exposure	
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values	
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values	
DE TRGS 900		Germany. TRGS 900 - Occupational exposure limit values.	
NL WG	:	Netherlands. Law on Labour conditions - Occupational Expo-	
	•	sure Limits	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCure®-8100/00 C

Jika®

Revision Date: 14.11.2024				
Date of last issue: 09.07.2024				

Version 6.0

Print Date 15.11.2024

2000/39/EC / TWA 2000/39/EC / STEL 2017/164/EU / STEL 2017/164/EU / TWA DE TRGS 900 / TWA DE TRGS 900 / AGW NL WG / TLV-8hr NL WG / TLV-15 min		Limit Value - eight hours Short term exposure limit Short term exposure limit Limit Value - eight hours Time Weighted Average Time Weighted Average Time Weighted Average Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation
		period) International Convention for the Prevention of Pollution from
MARPOL	•	Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the	mixture:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 SikaCure[®]-8100/00 C



Revision Date: 14.11.2024 Date of last issue: 09.07.2024 Version 6.0

Print Date 15.11.2024

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN