

Revision Date: 27.09.2024	Version 3.0	Print Date 27.09.2024
Date of last issue: 25.09.2023		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

1.2 Relevant identified uses of the substance or mixture and uses advised against

2

Product use

: Acrylate coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023			Version 3.0	Print Date 27.09.2024
Hazard pictograms	:		<u>(!</u>)	
Signal word	:	Danger		
Hazard statements	:	H225 H315 H317 H335 H412	Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Harmful to aquatic life with long lastin	ng effects.
Precautionary statements	:	Prevention P210 P233 P261 P264 P280	Keep away from heat, hot surfa open flames and other ignition s smoking. Keep container tightly closed. Avoid breathing mist or vapours Wash skin thoroughly after hand Wear protective gloves/ protective eye protection/ face protection.	sources. No dling.
		Response:		
		P370 + P37	8 In case of fire: Use dry sand, dr alcohol-resistant foam to exting	-

Hazardous components which must be listed on the label:

2-ethylhexyl acrylate methyl methacrylate tetramethylene dimethacrylate 2-(N-methyl-p-toluidino)ethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 27.09.2024	Version 3.0	Print Date 27.09.2024
Date of last issue: 25.09.2023		

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
2-ethylhexyl acrylate	103-11-7 203-080-7 01-2119453158-37- XXXX	Skin Irrit. 2; H315 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412	>= 40 - < 60
methyl methacrylate	80-62-6 201-297-1 01-2119452498-28- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 20 - < 25
tetramethylene dimethacrylate	2082-81-7 218-218-1 01-2119967415-30- XXXX	Skin Sens. 1B; H317	>= 1 - < 2,5
2-(N-methyl-p-toluidino)ethanol	2842-44-6 220-638-5 01-2120827830-56- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Do not induce vomiting without medical advice. Rinse mouth with water.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023		Version 3.0	Print Date 27.09.20
		Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsci	ous person.
4.2 Most important symptoms a	nd e	effects, both acute and delayed	
Symptoms	:	Cough Respiratory disorder Allergic reactions Erythema Dermatitis See Section 11 for more detailed information and symptoms.	on health effects
Risks	:	irritant effects sensitising effects	
		Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.	
I.3 Indication of any immediate	me	dical attention and special treatment needed	ł
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting mea	sur	es	
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	:	Water High volume water jet	
5.2 Special hazards arising from	n the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may sca fire.	atter and spread
Hazardous combustion prod- ucts	:	No hazardous combustion products are know	'n
3.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breath	ning apparatus.
Further information	:	Use water spray to cool unopened containers	



Revision Date: 27.09.2024Version 3.0Print Date 27.09.2024Date of last issue: 25.09.2023Version 3.0Print Date 27.09.2024

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

. Rem Den Bew	personal protective equipment. hove all sources of ignition. y access to unprotected persons. are of vapours accumulating to form explosive concentra- s. Vapours can accumulate in low areas.
---------------------	--

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023		Version 3.0	Print Date 27.09.2024
		measures against electrostatic discharges.	
Hygiene measures	:	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for safe storage, i	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Store in cool place. Containers which are opened carefully resealed and kept upright to prevent le in accordance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and applied as direc	ted.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet puse.	prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
2-ethylhexyl acrylate	103-11-7	TWA	5 ppm 38 mg/m3	DE TRGS 900
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
	Further infor	Further information: Indicative		
		STEL	100 ppm	2009/161/EU
		TLV-8hr	50 ppm 205 mg/m3	NL WG
		TLV-15 min	100 ppm 410 mg/m3	NL WG

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023	Version 3.0	Print Date 27.09.2024
	facturer specifications.	
	Suitable for short time use or protection against Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	splashes:
Skin and body protection	Protective clothing (e.g. Safety shoes acc. to Ell long-sleeved working clothing, long trousers). R and protective boots are additionaly recommend and stirring work.	lubber aprons
Respiratory protection	 In case of inadequate ventilation wear respirator Respirator selection must be based on known of exposure levels, the hazards of the product and ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 Ensure adequate ventilation. This can be achieved exhaust extraction or by general ventilation. (EN ods for determining inhalation exposure). This at ticular to the mixing / stirring area. In case this is to keep the concentrations under the occupation limits then respiration protection measures must 	pr anticipated I the safe work- ppm ved by local N 689 - Meth- applies in par- s not sufficent nal exposure
Environmental exposure con	rols	
General advice	: Prevent product from entering drains. If the product contaminates rivers and lakes or o	drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid off-white
Odour	:	unpleasant
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	100 °C
Flammability (solid, gas)	:	No data available

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023	Version 3.0	Print Date 27.09.2024
Upper/lower flammability or	plosive limits	
Upper explosion limit / Upper flammability limit	ca. 12,5 %(V)	
Lower explosion limit / Lower flammability limit	ca. 0,8 %(V)	
Flash point	ca. 10 °C Method: closed cup	
Auto-ignition temperature	ca. 245 °C	
Decomposition temperature	No data available	
рН	not determined substance/mixture is non-soluble ((in water)
Viscosity		
Viscosity, dynamic	ca. 800 mPa.s	
Viscosity, kinematic	> 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	insoluble	
Partition coefficient: n- octanol/water	No data available	
Vapour pressure	ca. 38,7 hPa (20 °C)	
Density	ca. 0,98 g/cm3 (20 °C)	
Relative vapour density	No data available	
Particle characteristics	No data available	

9.2 Other information

No data available



Revision Date: 27.09.2024 Date of last issue: 25.09.2023		Version 3.0	Print Date 27.09.2024
SECTION 40. Stability and read	- 41		
SECTION 10: Stability and read	CTI	vity	
10.1 Reactivity			
No dangerous reaction known u	uno	der conditions of normal use.	
10.2 Chemical stability			
The product is chemically stable	e.		
10.3 Possibility of hazardous read	ctic	ons	
Hazardous reactions	:	Stable under recommended storage conditions.	
		Vapours may form explosive mixture with air.	
10.4 Conditions to avoid			
Conditions to avoid	:	Heat, flames and sparks.	
10.5 Incompatible materials			
Materials to avoid	:	No data available	
10.6 Hazardous decomposition pr	oo	lucts	
No decomposition if stored and	l ap	oplied as directed.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

2-ethylhexyl acrylate:

Acute oral toxicity	:	LD50 Oral (Rat): 4.435 mg/kg
methyl methacrylate: Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 29,8 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg

2-(N-methyl-p-toluidino)ethanol:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
---------------------	---	--------------------------------

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023	Version 3.0	Print Date 27.09.2024
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye irritat Not classified due to lack of data		
Respiratory or skin sensitisation	on	
Skin sensitisation May cause an allergic skin reacti	on.	
Respiratory sensitisation Not classified due to lack of data		
Germ cell mutagenicity Not classified due to lack of data		
Carcinogenicity Not classified due to lack of data		
Reproductive toxicity Not classified due to lack of data		
STOT - single exposure May cause respiratory irritation.		
STOT - repeated exposure Not classified due to lack of data		
Aspiration toxicity Not classified due to lack of data		
11.2 Information on other hazards		
Endocrine disrupting propertie	es	
Product:		
Assessment :	The substance/mixture does not contain ered to have endocrine disrupting proper REACH Article 57(f) or Commission De (EU) 2017/2100 or Commission Regular levels of 0.1% or higher.	erties according to elegated regulation

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-ethylhexyl acrylate:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): 1,81 mg/l Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023		Version 3.0	Print Date 27.09.2024
Toxicity to daphnia and other : aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,3 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic : plants	:	ErC50 (Desmodesmus subspicatus (green algae Exposure time: 72 h	e)): 1,71 mg/l
methyl methacrylate:			
Toxicity to fish :	:	NOEC (Danio rerio (zebra fish)): 9,4 mg/l	
Toxicity to daphnia and other : aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202	
		NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202	
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 37 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)	
12.2 Persistence and degradability No data available	у		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB ass	ses	ssment	
Product:			
Assessment :	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	c (PBT), or
12.6 Endocrine disrupting properti	tie	S	
Product: Assessment :	:	The substance/mixture does not contain compor ered to have endocrine disrupting properties acc REACH Article 57(f) or Commission Delegated r (EU) 2017/2100 or Commission Regulation (EU) levels of 0.1% or higher.	ording to egulation
12.7 Other adverse effects		č	

Product:

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023	Version 3.0	Print Date 27.09.2024
Additional ecological infor- mation	: An environmental hazard cannot be exc unprofessional handling or disposal. Harmful to aquatic life with long lasting e	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1866	
	IMDG	:	UN 1866	
	ΙΑΤΑ	:	UN 1866	
14.2	2 UN proper shipping name			
	ADR	:	RESIN SOLUTION	
	IMDG	:	RESIN SOLUTION	
	ΙΑΤΑ	:	Resin solution	
14.:	3 Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023	Version 3.0	Print Date 27.09.2024
ΙΑΤΑ	: 3	
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: II : F1 : 33 : 3 : (D/E)	
IMDG Packing group Labels EmS Code	: II : 3 : F-E, <u>S-E</u>	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 364 : Y341 : II : Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 353 : Y341 : II : Flammable Liquids	
14.5 Environmental hazards		
ADR Environmentally hazardous	: no	
IMDG Marine pollutant	: no	
IATA (Passenger) Environmentally hazardous	: no	
IATA (Cargo) Environmentally hazardous	: no	
14.6 Special precautions for user	rouided boroin are for informational nurner	and and aclaly based

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



Revision Date: 27.09.2024 Date of last issue: 25.09.2023	Version	3.0	Print Date 27.09.2024
SECTION 15: Regulatory inform	mation		
15.1 Safety, health and environme International Chemical Weapon Schedules of Toxic Chemicals	ns Convention (CWC)	tion specific for th : Not applicable	
REACH Information:	All substances contain - registered by our up - registered by us, and - excluded from the re- - exempted from the re-	stream suppliers, a d/or egulation, and/or	
REACH - Restrictions on the m the market and use of certain d mixtures and articles (Annex X)	angerous substances,		restriction for the fol- s should be considered: st 3
		Number on lis	st 75:
REACH - Candidate List of Sub Concern for Authorisation (Artic		: None of the c (=> 0.1 %).	components are listed
REACH - List of substances su (Annex XIV)	bject to authorisation	: Not applicable	e
Regulation (EC) on substances layer	that deplete the ozone	: Not applicable	e
Regulation (EU) 2019/1021 on tants (recast)	persistent organic pollu-	: Not applicable	e
Regulation (EU) No 649/2012 c ment and the Council concernir of dangerous chemicals		: Not applicable	e
Seveso III: Directive 2012/18/E jor-accident hazards involving c P5c			uncil on the control of ma-
Volatile organic compounds	: Law on the incentive (VOCV) Volatile organic comp no VOC duties	-	



Revision Date: 27.09.2024	Version 3.0	Print Date 27.09.2024
Date of last issue: 25.09.2023		

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements	
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319 :	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411 :	Toxic to aquatic life with long lasting effects.
H412 :	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	
Aquatic Chronic	Long-term (chronic) aquatic hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT SE	Specific target organ toxicity - single exposure
2009/161/EU	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing
	a third list of indicative occupational exposure limit values in
	implementation of Council Directive 98/24/EC and amending
	Commission Directive 2000/39/EC
DE TRGS 900	Germany. TRGS 900 - Occupational exposure limit values.
NLWG	Netherlands. Law on Labour conditions - Occupational Expo- sure Limits
2009/161/EU / TWA	Limit Value - eight hours
2009/161/EU / STEL	Short term exposure limit
DE TRGS 900 / TWA	
NL WG / TLV-8hr	Time Weighted Average
NL WG / TLV-15 min	Short Term Exposure Limit
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at
	once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in
2000	air that kills 50% of the test animals during the observation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 27.09.2024 Date of last issue: 25.09.2023		Version 3.0)	Print Date 27.09.2024
MARPOL OEL PBT PNEC	:	period) International Convention Ships, 1973 as modified Occupational Exposure I Persistent, bioaccumulat	by the Protocol of 1978 Limit tive and toxic	
REACH	:	Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency		
SVHC vPvB	:	Substances of Very High Concern Very persistent and very bioaccumulative		0 7
Further information				
Classification of the mixtu	re:		Classification proced	ure:
Flam. Liq. 2	H2	25	Based on product data	or assessment
Skin Irrit. 2	H3	315	Calculation method	

Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

Aquatic Chronic 2	H412	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN