

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikafloor®-410

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.  
Zonnebaan 56  
3542 EG Utrecht  
Nederland  
Telephone : +31-30-2410120  
Telefax : +31-30-2414482  
E-mail address of person : EHS@nl.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National emergency contact NL: National Poisons Information Center +31-88-755-8000

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

|  |  |
|--|--|
| Flammable liquids, Category 3  | H226: Flammable liquid and vapour.                                       |
| Acute toxicity, Category 4   | H332: Harmful if inhaled.  |
| Skin irritation, Category 2  | H315: Causes skin irritation.  |
| Eye irritation, Category 2   | H319: Causes serious eye irritation.                                     |
| Skin sensitisation, Category 1   | H317: May cause an allergic skin reaction.                               |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation.                                  |
| Specific target organ toxicity - repeated exposure, Category 2, hearing organs   | H373: May cause damage to organs through prolonged or repeated exposure. |
| Long-term (chronic) aquatic hazard, Category 3                                   | H412: Harmful to aquatic life with long lasting effects.                 |

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

|                          |   |  |
|--------------------------|---|--|
| Signal word              | : | Warning  |
| Hazard statements        | : | H226 Flammable liquid and vapour.<br>H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H319 Causes serious eye irritation.<br>H332 Harmful if inhaled.<br>H335 May cause respiratory irritation.<br>H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure.<br>H412 Harmful to aquatic life with long lasting effects.   |
| Precautionary statements | : | <b>Prevention:</b><br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P260 Do not breathe mist or vapours.<br>P264 Wash skin thoroughly after handling.<br>P273 Avoid release to the environment.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.<br><br><b>Response:</b><br>P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

### Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene  
Hexamethylene diisocyanate, oligomers  
isobutyl methacrylate  
dibutyltin dilaurate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number   | Classification  | Concentration<br>(% w/w) |
|--|---|---|--------------------------|
| reaction mass of ethylbenzene and xylene   | Not Assigned<br>905-588-0<br>601-022-00-9<br>01-2119488216-32-XXXX                                      | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>STOT SE 3; H335<br>(Respiratory system)<br>STOT RE 2; H373<br>(hearing organs)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 3; H412 | >= 25 - < 40             |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics                        | Not Assigned<br>919-857-5<br>649-327-00-6<br>01-2119463258-33-XXXX [corresponding group CAS 64742-48-9] | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>Asp. Tox. 1; H304<br>EUH066  | >= 10 - < 20             |
| Hexamethylene diisocyanate, oligomers<br>Contains:<br>hexamethylene-di-isocyanate <= 0,3 % | 28182-81-2<br>931-288-4<br>500-060-2<br>01-2119488177-26-XXXX   | Acute Tox. 3; H331<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>(Respiratory system)<br><br>Acute toxicity estimate<br><br>Acute inhalation toxicity (dust/mist):<br>0,5001 mg/l   | >= 10 - < 20             |
| 2-methoxy-1-methylethyl acetate<br>Contains:<br>2-methoxypropyl acetate <= 1 %             | 108-65-6<br>203-603-9<br>607-195-00-7<br>01-2119475791-29-XXXX  | Flam. Liq. 3; H226<br>STOT SE 3; H336   | >= 2,5 - < 5             |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025

Version 9.0

Print Date 05.09.2025

Date of last issue: 07.05.2024

|                             |   |   |                     |
|-----------------------------|---|---|---------------------|
| Hydrocarbons, C9, aromatics | Not Assigned<br>265-199-0<br>649-356-00-4<br>01-2119455851-35-XXXX [corresponding group CAS 64742-95-6] | Flam. Liq. 3; H226<br>STOT SE 3; H336<br>(Central nervous system)<br>STOT SE 3; H335<br>(Respiratory system)<br>Asp. Tox. 1; H304<br>Aquatic Chronic 2; H411<br>EUH066  | $\geq 2,5 - < 5$    |
| isobutyl methacrylate       | 97-86-9<br>202-613-0<br>607-113-00-X  | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>Skin Sens. 1B; H317<br>STOT SE 3; H335<br>(Respiratory system)   | $\geq 0,1 - < 0,5$  |
| dibutyltin dilaurate        | 77-58-7<br>201-039-8<br>050-030-00-3<br>01-2119496068-27-XXXX   | Muta. 2; H341<br>Repr. 1B; H360FD<br>STOT RE 1; H372<br>(Immune system)<br>Aquatic Acute 1; H400<br>Aquatic Chronic 1; H410<br><br>M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1 | $\geq 0,1 - < 0,25$ |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough  
Respiratory disorder  
Allergic reactions  
Excessive lachrymation  
Erythema  
Headache  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.

Risks : irritant effects  
sensitising effects  
  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus for firefighters

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

(which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

| Components                               | CAS-No.  | Value type (Form of exposure) | Control parameters *  | Basis *    |
|--|--|-------------------------------|-----------------------|------------|
| reaction mass of ethylbenzene and xylene | Not Assigned   | TWA                           | 50 ppm<br>221 mg/m3   | 2000/39/EC |
|  | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                       |            |
|  |  | STEL                          | 100 ppm<br>442 mg/m3  | 2000/39/EC |
|  |  | TLV-8hr                       | 47,5 ppm<br>210 mg/m3 | NL WG      |
|  | Further information: Skin notation   |                               |                       |            |
|  |  | TLV-15 min                    | 100 ppm<br>442 mg/m3  | NL WG      |
| 2-methoxy-1-methylethyl acetate          | 108-65-6   | STEL                          | 100 ppm<br>550 mg/m3  | 2000/39/EC |
|  | Further information: Identifies the possibility of significant uptake through the skin, Indicative |                               |                       |            |
|  |  | TWA                           | 50 ppm<br>275 mg/m3   | 2000/39/EC |
|  |  | TLV-8hr                       | 100 ppm<br>550 mg/m3  | NL WG      |

\*The above mentioned values are in accordance with the legislation in effect at the date of the re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

lease of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.  
Ensure adequate ventilation, especially in confined areas.

#### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Colour : various



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

Odour : hydrocarbon-like

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 6 %(V)

Lower explosion limit / Lower flammability limit : 0,7 %(V)

Flash point : ca. 33 °C  
Method: closed cup

Auto-ignition temperature : 255 °C

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 7,9993 hPa

Density : ca. 0,95 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Avoid moisture.

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Harmful if inhaled.

##### Components:

##### reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

##### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.160 mg/kg

##### Hexamethylene diisocyanate, oligomers:

Acute oral toxicity : LD50 Oral (Rat): > 5.665 mg/kg

Acute inhalation toxicity : LC50: > 0,5 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

Test atmosphere: dust/mist  
Method: Expert judgement

Acute toxicity estimate: 0,5001 mg/l  
Test atmosphere: dust/mist  
Method: ATE value derived from LD50/LC50 value

### 2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

### dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2.071 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

#### Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

### STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure.

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l  
Exposure time: 7 d  
Species: Daphnia (water flea)

##### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l  
Exposure time: 48 h

##### Hexamethylene diisocyanate, oligomers:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus quadricauda (Green algae)): > 50 - 100 mg/l  
Exposure time: 72 h

##### Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

### dibutyltin dilaurate:

|   |   |  |
|---|---|--|
| Toxicity to fish                                    | : | LC50 (Fish): 3,1 mg/l<br>Exposure time: 96 h                                       |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): 1 mg/l<br>Exposure time: 48 h                         |
| Toxicity to algae/aquatic plants                    | : | EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l<br>Exposure time: 72 h |
| M-Factor (Acute aquatic toxicity)                   | : | 1  |
| M-Factor (Chronic aquatic toxicity)                 | : | 1  |

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

|            |   |   |
|------------|---|---|
| Assessment | : | This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. |
|------------|---|---|

### 12.6 Endocrine disrupting properties

#### Product:

|            |   |   |
|------------|---|---|
| Assessment | : | The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. |
|------------|---|---|

### 12.7 Other adverse effects

#### Product:

|                                   |   |   |
|-----------------------------------|---|---|
| Additional ecological information | : | An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.<br>Harmful to aquatic life with long lasting effects. |
|-----------------------------------|---|---|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 UN proper shipping name

- ADR : PAINT  
IMDG : PAINT  
IATA : Paint

#### 14.3 Transport hazard class(es)

- |      | Class | Subsidiary risks |
|------|-------|------------------|
| ADR  | : 3   |                  |
| IMDG | : 3   |                  |
| IATA | : 3   |                  |

#### 14.4 Packing group

- ADR

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

---

REACH Information: All substances contained in our Products are  
Country NL 000000101354

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 40: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Netherlands. Substances of very high concern (ZZS-list) : dibutyltin dilaurate

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : dibutyltin dilaurate

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 49,33% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

and control)  
Volatile organic compounds (VOC) content: 49,33% w/w

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

reaction mass of ethylbenzene and xylene dibutyltin dilaurate

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

|        |   |   |
|--------|---|---|
| H226   | : | Flammable liquid and vapour.  |
| H304   | : | May be fatal if swallowed and enters airways.                                 |
| H312   | : | Harmful in contact with skin.   |
| H315   | : | Causes skin irritation.   |
| H317   | : | May cause an allergic skin reaction.  |
| H319   | : | Causes serious eye irritation.  |
| H331   | : | Toxic if inhaled.   |
| H332   | : | Harmful if inhaled.   |
| H335   | : | May cause respiratory irritation.   |
| H336   | : | May cause drowsiness or dizziness.  |
| H341   | : | Suspected of causing genetic defects.   |
| H360FD | : | May damage fertility. May damage the unborn child.                            |
| H372   | : | Causes damage to organs through prolonged or repeated exposure.               |
| H373   | : | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H400   | : | Very toxic to aquatic life.   |
| H410   | : | Very toxic to aquatic life with long lasting effects.                         |
| H411   | : | Toxic to aquatic life with long lasting effects.                              |
| H412   | : | Harmful to aquatic life with long lasting effects.                            |

### Full text of other abbreviations

|                 |   |                                    |
|-----------------|---|------------------------------------|
| Acute Tox.      | : | Acute toxicity                     |
| Aquatic Acute   | : | Short-term (acute) aquatic hazard  |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Asp. Tox.       | : | Aspiration hazard                  |
| Eye Irrit.      | : | Eye irritation                     |
| Flam. Liq.      | : | Flammable liquids                  |
| Muta.           | : | Germ cell mutagenicity             |
| Repr.           | : | Reproductive toxicity              |
| Skin Irrit.     | : | Skin irritation                    |
| Skin Sens.      | : | Skin sensitisation                 |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

|                    |  |
|--------------------|--|
| STOT RE            | : Specific target organ toxicity - repeated exposure   |
| STOT SE            | : Specific target organ toxicity - single exposure   |
| 2000/39/EC         | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values   |
| NL WG              | : Netherlands. Law on Labour conditions - Occupational Exposure Limits   |
| 2000/39/EC / TWA   | : Limit Value - eight hours  |
| 2000/39/EC / STEL  | : Short term exposure limit  |
| NL WG / TLV-8hr    | : Time Weighted Average  |
| NL WG / TLV-15 min | : Short Term Exposure Limit  |
| ADR                | : European Agreement concerning the International Carriage of Dangerous Goods by Road  |
| CAS                | : Chemical Abstracts Service   |
| DNEL               | : Derived no-effect level  |
| EC50               | : Half maximal effective concentration   |
| GHS                | : Globally Harmonized System   |
| IATA               | : International Air Transport Association  |
| IMDG               | : International Maritime Code for Dangerous Goods  |
| LD50               | : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)   |
| LC50               | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL             | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL                | : Occupational Exposure Limit  |
| PBT                | : Persistent, bioaccumulative and toxic  |
| PNEC               | : Predicted no effect concentration  |
| REACH              | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC               | : Substances of Very High Concern  |
| vPvB               | : Very persistent and very bioaccumulative   |

### Further information

#### Classification of the mixture:

|                   |      |
|-------------------|------|
| Flam. Liq. 3      | H226 |
| Acute Tox. 4      | H332 |
| Skin Irrit. 2     | H315 |
| Eye Irrit. 2      | H319 |
| Skin Sens. 1      | H317 |
| STOT SE 3         | H335 |
| STOT RE 2         | H373 |
| Aquatic Chronic 3 | H412 |

#### Classification procedure:

|                                     |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |
| Calculation method                  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikafloor®-410



Revision Date: 02.09.2025  
Date of last issue: 07.05.2024

Version 9.0

Print Date 05.09.2025

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

NL / EN