according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard® M 790 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.

Zonnebaan 56 3542 EG Utrecht Nederland

 Telephone
 : +31-30-2410120

 Telefax
 : +31-30-2414482

 E-mail address of person
 : EHS@nl.sika.com

responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure, Category 2, Kidney, Liver

H373: May cause damage to organs through pro-

longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage.H335 May cause respiratory irritation.

H373 May cause damage to organs (Kidney, Liver)

through prolonged or repeated exposure.

Precautionary statements : Prevention:

P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P314 Get medical advice/ attention if you feel un-

well.

Hazardous components which must be listed on the label:

calcium dihydroxide ethanediol

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)		
	Registration number				
calcium dihydroxide	1305-62-0	Skin Irrit. 2; H315	>= 25 - < 40		
	215-137-3	Eye Dam. 1; H318			
	01-2119475151-45-	STOT SE 3; H335			
	XXXX	(Respiratory system)			
ethanediol	107-21-1	Acute Tox. 4; H302	>= 10 - < 20		
	203-473-3	STOT RE 2; H373			
	01-2119456816-28-	(Kidney, Liver)			
	XXXX				
Naphtha (petroleum), heavy alkyl-	64741-65-7	Flam. Liq. 3; H226	>= 1 - < 2,5		
ate; Low boiling point modified	265-067-2	Asp. Tox. 1; H304			
naphtha	01-2119471991-29-	Aquatic Chronic 2;			
·	XXXX	H411			
		EUH066			
Substances with a workplace exposure limit :					
Titanium dioxide (> 10 µm)	13463-67-7		>= 2,5 - < 5		
	236-675-5				
	01-2119489379-17-				
	XXXX				

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Revision Date: 02.05.2024 Version 1.1 Print Date 03.05.2024

Date of last issue: -

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Cough

> Respiratory disorder **Excessive lachrymation**

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks Causes skin irritation.

> Causes serious eve damage. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure.

irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

Country NL 100000053584

4 / 14

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Revision Date: 02.05.2024 Version 1.1 Print Date 03.05.2024

Date of last issue: -



Environmental precautions Try to prevent the material from entering drains or water

courses.

6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

: Handle in accordance with good industrial hygiene and safety Hygiene measures

> practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) Consult most current local Product Data Sheet prior to any

use.

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
calcium dihydroxide	1305-62-0	TWA (Respirable	1 mg/m3	2017/164/EU
calcium dinydroxide	1303-02-0	fraction)	i ilig/ilio	2017/104/20
	Further information: Indicative			
		STEL (Respirable	4 mg/m3	2017/164/EU
		fraction)	J	
		TLV-8hr (Respira-	1 mg/m3	NL WG
		ble)		
		TLV-15 min (Res-	4 mg/m3	NL WG
		pirable)		
ethanediol	107-21-1	STEL	40 ppm	2000/39/EC
			104 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the s	through the skin, Indicative		
		TWA	20 ppm	2000/39/EC
			52 mg/m3	
		TLV-8hr	10 mg/m3	NL WG
		(Droplets)		
	Further information: Skin notation			
		TLV-8hr (Vapour)	20 ppm	NL WG
		,	52 mg/m3	
		TLV-15 min (Va-	40 ppm	NL WG
		pour)	104 mg/m3	
Titanium dioxide (> 10 μm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Revision Date: 02.05.2024 Version 1.1 Print Date 03.05.2024

Date of last issue: -

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water

courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour grey

Odour aliphatic

Melting point/range / Freezing : No data available

point

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Revision Date: 02.05.2024 Version 1.1 Print Date 03.05.2024

Date of last issue: -

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 1.000 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 23 hPa

Density : ca. 1,27 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Causes skin irritation.

Components:

Naphtha (petroleum), heavy alkylate; Low boiling point modified naphtha:

Assessment : Repeated exposure may cause skin dryness or cracking. Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

Country NL 100000053584

10 / 14

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Revision Date: 02.05.2024 Version 1.1 Print Date 03.05.2024

Date of last issue: -

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or - exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75, 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 1,64% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 1,64% w/w

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H335 : May cause respiratory irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

NL WG : Netherlands. Law on Labour conditions - Occupational Expo-

sure Limits

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 Part A

Date of last issue: -

DE TRGS 900 / TWA : Time Weighted Average
NL WG / TLV-8hr : Time Weighted Average
NL WG / TLV-15 min : Short Term Exposure Limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NL / EN