Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1 Product identifier**

Trade name

: SikaTack<sup>®</sup> Ultrafast

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive, For professional users only.

## 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V. Zonnebaan 56 3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person responsible for the SDS	:	EHS@nl.sika.com

#### 1.4 Emergency telephone number

+31-57-0854201

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

	·		
Signal word	:	Danger	
Hazard statements	:	H334	May cause allergy or asthma symptoms or breath- ing difficulties if inhaled.
Precautionary statements	:	Prevention P261 P284	: Avoid breathing mist or vapours. In case of inadequate ventilation wear respir-

## SikaTack<sup>®</sup> Ultrafast

Print Date 03.04.2024

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0

atory protection.

Response:	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

## Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

## **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SikaTack® Ultrafast

Revision Date: 26.03.2024 Date of last issue: 27.01.2024



Version 4.0

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

## Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2,5 - < 5
Urea,N,N"-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 1 - < 2,5
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 $\longrightarrow$ specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate	>= 0,5 - < 1
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	

## SikaTack<sup>®</sup> Ultrafast

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0



3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	>= 0,1 - < 0,25
		Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 0,031 mg/l	

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>

## 4.2 Most important symptoms and effects, both acute and delayed



Revision Date: 26.03.2024 Date of last issue: 27.01.2024		Version 4.0	Print Date 03.04.20
Symptoms	Al Se	sthmatic appearance lergic reactions se Section 11 for more detailed informatio nd symptoms.	n on health effects
Risks	: se	ensitising effects	
		ay cause allergy or asthma symptoms or l es if inhaled.	breathing difficul-
4.3 Indication of any immediate m	nedica	al attention and special treatment need	ed
Treatment	: Tr	eat symptomatically.	
SECTION 5: Firefighting meas	ures		
5.1 Extinguishing media			
Suitable extinguishing media	id	case of fire, use water/water spray/water e/sand/foam/alcohol resistant foam/chemi ttinction.	
5.2 Special hazards arising from t	the su	Ibstance or mixture	
Hazardous combustion prod- ucts	: No	o hazardous combustion products are kno	own
5.3 Advice for firefighters			
Special protective equipment for firefighters	: In	the event of fire, wear self-contained brea	athing apparatus.
Further information	: St	andard procedure for chemical fires.	
SECTION 6: Accidental release	e mea	asures	
6.1 Personal precautions, protect	ive eo	quipment and emergency procedures	
Personal precautions		se personal protective equipment. eny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	: Do	o not flush into surface water or sanitary s	ewer system.
6.3 Methods and material for cont	tainm	ent and cleaning up	
Methods for cleaning up	ac	bak up with inert absorbent material (e.g. s sid binder, universal binder, sawdust). Beep in suitable, closed containers for dispo	-

Keep in suitable, closed containers for disposal.

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0



## 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

7.1	Precautions for safe handling		
	Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, in	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame- ters *	Basis *
		of exposure)	leis	
reaction mass of ethylbenzene and xy-	Not Assigned	TWA	50 ppm	2000/39/EC
lene			221 mg/m3	
	Further information: Identifies the possibility of significant uptake			ficant uptake



Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0

through the sk	in, Indicative		
	STEL	100 ppm 442 mg/m3	2000/39/EC
	TLV-8hr	47,5 ppm 210 mg/m3	NL WG
Further inform	ation: Skin notation	l	
	TLV-15 min	100 ppm 442 mg/m3	NL WG

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## 8.2 Exposure controls

## **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

,,						
Personal protective equipment						
Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water					
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.					
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.					
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.					
Respiratory protection	<ul> <li>In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. organic vapor filter (Type A) A1: &lt; 1000 ppm; A2: &lt; 5000 ppm; A3: &lt; 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.</li> </ul>					

Print Date 03.04.2024

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0

## Environmental exposure controls

General advice

: Do not flush into surface water or sanitary sewer system.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

••••	Physical state Appearance Colour	:	liquid paste black
	Odour	:	odourless
	Melting point/range / Freezing point	:	No data available
	Boiling point/boiling range	:	No data available
	Flammability (solid, gas)	:	No data available
	Upper/lower flammability or e	<u>-xn</u>	losive limits
	Upper explosion limit / Up- per flammability limit	-	
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	ca. 84 °C Method: closed cup
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	No data available
	рН	:	Not applicable substance/mixture is non-soluble (in water)
	Viscosity		
	Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
	Solubility(ies)		
	Water solubility	:	insoluble

## SikaTack<sup>®</sup> Ultrafast



Revision Date: 26.03.2024 Date of last issue: 27.01.2024	Version 4.0	Print Date 03.04.2024
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,15 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information		
No data available		
SECTION 10: Stability and r	eactivity	
10.1 Reactivity		
No dangerous reaction know	vn under conditions of normal use.	

## 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

## 10.4 Conditions to avoid

Conditions to avoid : No data available

## **10.5 Incompatible materials**

Materials to avoid	: No data available

## **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

Not classified due to lack of data.

# SikaTack® Ultrafast

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0



## Components:

reaction mass of ethylbenzene and xylene:					
Acute oral toxicity	:	LD50 Oral (Rat): 3.523 mg/kg			
Urea,N,N"-(methylenedi-4,1	-nh	envlene)bis[N'-butyl-			
Acute oral toxicity	-pin :				
Notice of all toxicity	•	Method: OECD Test Guideline 401			
Acute dermal toxicity		LD50 Dermal (Rabbit): > 2.000 mg/kg			
noute dominar toxicity	•	Method: OECD Test Guideline 402			
4,4'-methylenediphenyl diis	-				
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401			
Acute inhalation toxicity	:	LC50: 1,5 mg/l			
		Exposure time: 4 h Test atmosphere: dust/mist			
		Method: Expert judgement			
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist			
		Method: Calculation method			
3-isocyanatomethyl-3,5,5-tr	rime				
Acute oral toxicity	:	LD50 Oral (Rat): 4.814 mg/kg			
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l			
		Exposure time: 4 h Test atmosphere: dust/mist			
		rest atmosphere. dust/mist			
		Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist			
		Method: Calculation method			
Acute dermal toxicity		LD50 Dermal (Rat): > 7.000 mg/kg			
Acute definal toxicity	:	EDS0 Definal (Rat). > 7.000 mg/kg			
Skin corrosion/irritation					
Not classified due to lack of data.					
Serious eye damage/eye irritation					
Not classified due to lack of data.					
Respiratory or skin sensitisation					
Skin sensitisation					
Not classified due to lack of data.					
Respiratory sensitisation					
May cause allergy or asthma symptoms or breathing difficulties if inhaled.					

Revision Date: 26.03.2024 Date of last issue: 27.01.2024

Version 4.0



## Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

## STOT - single exposure

Not classified due to lack of data.

## STOT - repeated exposure

Not classified due to lack of data.

## Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

## **Endocrine disrupting properties**

## Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

## Components:

## reaction mass of ethylbenzene and xylene:

Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)
Urea,N,N"-(methylenedi-4,1-	phe	enylene)bis[N'-butyl-:
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): >
Country NL 000000019858		

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0



plants

100 mg/l Exposure time: 72 h

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### **12.6 Endocrine disrupting properties**

<u>Product:</u> Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	

#### Product:

Additional ecological infor- : There is no data available for this product. mation

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product

 The generation of waste should be avoided or minimized wherever possible.
 Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 Avoid dispersal of spilled material and runoff and contact with

# Print Date 03.04.2024

Revision Date: 26.03.2024 Date of last issue: 27.01.2024	Version 4.0	Print Date 03.04.202
	soil, waterways, drains and sewers.	
European Waste Catalogue	: 08 04 09* waste adhesives and sealar solvents or other dangerous substance	
Contaminated packaging	: 15 01 10* packaging containing residue by dangerous substances	es of or contaminated

## **SECTION 14: Transport information**

14.1 UN number or ID number				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.2 UN proper shipping name				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.3 Transport hazard class(es)				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.4 Packing group				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
IATA (Cargo)	:	Not regulated as a dangerous good		
IATA (Passenger)	:	Not regulated as a dangerous good		
14.5 Environmental hazards				
Not regulated as a dangerous good				
14.6 Special precautions for user				
Not applicable				

# 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

Revision Date: 26.03.2024

Date of last issue: 27.01.2024



Version 4.0

International Chemical Weapons Schedules of Toxic Chemicals a		:	Not applicable
REACH Information:	All substances contair - registered by our ups - registered by us, and - excluded from the re - exempted from the re	strea d/or gula	m suppliers, and/or tion, and/or
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	ingerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
			4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)
REACH - Candidate List of Subs Concern for Authorisation (Articl		:	None of the components are listed (=> 0.1 %).
REACH - List of substances sub (Annex XIV)	ject to authorisation	:	Not applicable
Regulation (EC) No 1005/2009 opplete the ozone layer	on substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on p tants (recast)	persistent organic pollu-	:	Not applicable
Regulation (EU) No 649/2012 of ment and the Council concernin of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EL jor-accident hazards involving da		ment	and of the Council on the control of ma-
Volatile organic compounds :	Law on the incentive t (VOCV)	ax fo	or volatile organic compounds

## SikaTack<sup>®</sup> Ultrafast

Print Date 03.04.2024

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0

Volatile organic compounds (VOC) content: <= 3% w/w no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,93% w/w

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

reaction mass of ethylbenzene and xylene

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

#### **Full text of H-Statements**

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbreviat	ions	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation

# SikaTack® Ultrafast

Revision Date: 26.03.2024 Date of last issue: 27.01.2024



Version 4.0

STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
		list of indicative occupational exposure limit values
NL WG	:	Netherlands. Law on Labour conditions - Occupational Expo-
		sure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
NL WG / TLV-8hr	:	Time Weighted Average
NL WG / TLV-15 min	:	Short Term Exposure Limit
ADR		European Agreement concerning the International Carriage of
	-	Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL		Derived no-effect level
EC50		Half maximal effective concentration
GHS		Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
ED30	•	once, which causes the death of 50% (one half) of a group of
		test animals)
LC50		Median lethal concentration (concentrations of the chemical in
2030	•	air that kills 50% of the test animals during the observation
		period)
MARPOL		International Convention for the Prevention of Pollution from
MARPOL	•	
	<u>.</u>	Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT		Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
0.410		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

## **Further information**

Classification of the mixtur	Classification procedure:	
Resp. Sens. 1	H334	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 SikaTack<sup>®</sup> Ultrafast

Revision Date: 26.03.2024 Date of last issue: 27.01.2024 Version 4.0

