# Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025 Version 12.0

Print Date 24.01.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikadur<sup>®</sup>-33 Part A

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V. Zonnebaan 56 3542 EG Utrecht Nederland
Talaphana		+31-30-2410120
Telephone	•	
Telefax	:	+31-30-2414482
E-mail address of person responsible for the SDS	:	EHS@nl.sika.com

#### 1.4 Emergency telephone number

+31-57-0854201

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Version 12.0 Print Date 24.01.2025 Date of last issue: 08.01.2025 Signal word Danger 2 Hazard statements H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eve damage. H360F May damage fertility. H411 Toxic to aquatic life with long lasting effects. Precautionary statements Prevention: P201 Obtain special instructions before use. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eve protection/ face protection. **Response:** P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. IF exposed or concerned: Get medical ad-P308 + P313 vice/ attention. P391 Collect spillage.

### Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Aliphatic glycidyl ether Reaction mass of isomers of epoxy resin BFDGE Cement (chromium reduced) oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

#### Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

The content of soluble Chromium (VI) is not greater than 0,0002% in accordance with Annex XVII, Paragraph 47 of the EU Regulation 1907/2006. The product reacts highly alkaline with water.

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025 Version 12.0

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 25 - < 40
Aliphatic glycidyl ether	74398-71-3 Not Assigned	Skin Sens. 1; H317	>= 5 - < 10
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
Cement (chromium reduced)	65997-15-1 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	>= 3 - < 5
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48- XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 2,5 - < 5
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 2,5 - < 5



# Sikadur<sup>®</sup>-33 Part A

I
- < 2,5
-

### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms an	nd e	ffects, both acute and delayed
Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May damage fertility.
		irritant effects sensitising effects

SAFETY DATA SHEET	
according to Regulation (EC) No. 1907/20 tion (EU) 2020/878	06, as amended by Commission Regula-

# Sikadur<sup>®</sup>-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025		Version 12.0	Print Date 24.01.202
		toxic effects for reproduction	
-	neo	lical attention and special treatment need	ded
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/wate ide/sand/foam/alcohol resistant foam/chemextinction.	
5.2 Special hazards arising from	the	substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to entrourses.	ter drains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are kn	own
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained bre	eathing apparatus.
Further information	:	Collect contaminated fire extinguishing war must not be discharged into drains. Fire residues and contaminated fire extinguished disposed of in accordance with local reg	uishing water must

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, protectiv	e equipment and emergency procedures			
Personal precautions :	Use personal protective equipment. Deny access to unprotected persons.			
6.2 Environmental precautions				
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			
6.3 Methods and material for containment and cleaning up				
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.			

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025 Version 12.0

Print Date 24.01.2025

#### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

	Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Pregnant women or women of child-bearing age should not be exposed to this product.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, in	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025	Version 12.0	Print Date 24.01.2025
Titanium dioxide (> 10 μm) *The above mentioned values an lease of this safety data sheet.	13463-67-7   TWA e in accordance with the legislation in	effect at the date of the re-
8.2 Exposure controls		
<b>Engineering measures</b> Maintain air concentrations belov Ensure adequate ventilation, esp	v occupational exposure standards. ecially in confined areas.	
Personal protective equipment	1	
Eye/face protection :	Safety glasses with side-shields cor Eye wash bottle with pure water	nforming to EN166
Hand protection :	Chemical-resistant, impervious glov proved standard must be worn at al chemical products. Reference numb facturer specifications. Suitable for short time use or protect Butyl rubber/nitrile rubber gloves (> Contaminated gloves should be rem Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	I times when handling ber EN 374. Follow manu- ction against splashes: 0,1 mm)
Skin and body protection :	Protective clothing (e.g. Safety shoe long-sleeved working clothing, long and protective boots are additionaly and stirring work.	trousers). Rubber aprons
Respiratory protection :	In case of inadequate ventilation we Respirator selection must be based exposure levels, the hazards of the ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A Ensure adequate ventilation. This c exhaust extraction or by general ver ods for determining inhalation expositicular to the mixing / stirring area. In to keep the concentrations under th limits then respiration protection me	A3: < 10000 ppm an be achieved by local ntilation. (EN 689 - Meth- sure). This applies in par- n case this is not sufficent e occupational exposure
Environmental exposure contr	ols	
•	Do not flush into surface water or sa If the product contaminates rivers a respective authorities.	

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025	Version 12.0	Print Date 24.01.2025
Physical state Appearance Colour	: liquid : paste : grey	
Odour	: odourless	
Melting point/ range / Freez- ing point	: No data available	
Boiling point/boiling range	: No data available	
Flammability (solid, gas)	: No data available	
Upper/lower flammability or	explosive limits	
Upper explosion limit / Up- per flammability limit	: No data available	
Lower explosion limit / Lower flammability limit	: No data available	
Flash point	: > 101 °C Method: closed cup	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: ca. 7 Concentration: 50 %	
Viscosity		
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: < 1,5 hPa	
Density	: ca. 1,49 g/cm3 (20 °C)	



Print Date 24.01.2025

# Sikadur<sup>®</sup>-33 Part A

Revision Date: 23.01.2025

Date of last issue: 08.01.2025

Relative vapour density	: No data available
Particle characteristics	: No data available
9.2 Other information	
No data available	
SECTION 10: Stability and r	eactivity
10.1 Reactivity	
No dangerous reaction know	wn under conditions of normal use.
10.2 Chemical stability	
The product is chemically s	table.
10.3 Possibility of hazardous r	eactions
Hazardous reactions	: Stable under recommended storage conditions.
10.4 Conditions to avoid	
Conditions to avoid	: No data available
10.5 Incompatible materials	
Materials to avoid	: No data available
10.6 Hazardous decomposition	n products
	: No hazardous decomposition products are known.
	information
SECTION 11: Toxicological	information
11.1 Information on bazard ala	sses as defined in Regulation (EC) No 1272/2008

Version 12.0

Not classified due to lack of data.

# Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:					
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg			

Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
Acute definal toxicity	•	LDS0 Definial (Rabbit). > 5.000 mg/kg

Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025	Version 12.0	Print Date 24.01.2025
bis(isopropyl)naphthalene:		
Acute oral toxicity :	LD50 Oral (Rat): > 3.900 mg/kg	
Acute inhalation toxicity :	LC50 (Rat): > 5,64 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity :	LD50 Dermal (Rat): > 4.500 mg/kg	
oxirane, mono[(C12-14-alkylo	ky)methyl] derivs.:	
Acute oral toxicity :	LD50 Oral (Rat): > 5.000 mg/kg	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye irrita Causes serious eye damage.	tion	
Respiratory or skin sensitisat	on	
<b>Skin sensitisation</b> May cause an allergic skin react	ion.	
Respiratory sensitisation Not classified due to lack of data		
Germ cell mutagenicity Not classified due to lack of data	ı.	
<b>Carcinogenicity</b> Not classified due to lack of data	ı.	
<b>Reproductive toxicity</b> May damage fertility.		
STOT - single exposure Not classified due to lack of data	1.	
STOT - repeated exposure Not classified due to lack of data	ı.	
Aspiration toxicity Not classified due to lack of data	ı.	
11.2 Information on other hazards		
Endocrine disrupting properti	es	
Product:		
Assessment :	The substance/mixture does not contain co ered to have endocrine disrupting propertie REACH Article 57(f) or Commission Deleg (EU) 2017/2100 or Commission Regulatior	es according to ated regulation

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025 Version 12.0

Print Date 24.01.2025

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

12.1 Toxicity

#### **Components:**

bis-[4-(2,3-epoxipropoxi)pher	ny	I]propane:		
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h		
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h		
Reaction mass of isomers of epoxy resin BFDGE:				
Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l		

,		Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

: This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

#### Components:

### bis(isopropyl)naphthalene:

Assessment	:	vPvB substance
------------	---	----------------



Print Date 24.01.2025

# 12.6 Endocrine disrupting properties

Product:	

Revision Date: 23.01.2025

Date of last issue: 08.01.2025

Assessment	<ul> <li>The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.</li> </ul>
12.7 Other adverse effects	

Version 12.0

### Product:

TTOULOU		
Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

# **SECTION 14: Transport information**

# 14.1 UN number or ID number

ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikadur®-33 Part A



Revision Date: 23.01.2025 Version 12.0 Print Date 24.01.2025 Date of last issue: 08.01.2025 14.2 UN proper shipping name ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin) IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, : N.O.S. (epoxy resin) ΙΑΤΑ • Environmentally hazardous substance, liquid, n.o.s. (epoxy resin) 14.3 Transport hazard class(es) Class Subsidiary risks ADR : 9 IMDG 9 ÷ ΙΑΤΑ 9 2 14.4 Packing group ADR Ш Packing group ÷ Classification Code M6 2 Hazard Identification Number 90 . Labels 9 Tunnel restriction code 2 (-) Remarks ÷ Transport in accordance with special provision 375 IMDG Packing group ÷ Labels 2 9 EmS Code F-A, S-F : Remarks Transport in accordance with 2.10.2.7 of the IMDG-Code 1 IATA (Cargo) Packing instruction (cargo : 964 aircraft) Packing instruction (LQ) : Y964 Packing group Ш 1 Labels ÷ Miscellaneous Remarks Transport in accordance with special regulation A 197 2 IATA (Passenger) Packing instruction (passen-: 964 ger aircraft) Packing instruction (LQ) 2 Y964 Packing group Ш 1 Labels ÷ Miscellaneous

#### 14.5 Environmental hazards

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikadur®-33 Part A

Revision Date: 23.01.2025 Date of last issue: 08.01.2025 Version 12.0

Print Date 24.01.2025

ADR Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

**REACH** Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

: Not applicable

- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 30: oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
		Number on list 47: Cement (chromi- um reduced)
		Number on list 75:
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).



# Sikadur<sup>®</sup>-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025	Version 12.0	Print Date 24.01.2025			
REACH - List of substances subj (Annex XIV)	ect to authorisation : Not applicable				
Regulation (EC) on substances t layer	hat deplete the ozone : Not applicable				
Regulation (EU) 2019/1021 on petants (recast)	ersistent organic pollu- : Not applicable				
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals					
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS					
Volatile organic compounds :	<ul> <li>Law on the incentive tax for volatile organic compounds (VOCV)</li> <li>Volatile organic compounds (VOC) content: 0,03% w/w no VOC duties</li> </ul>				
Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,03% w/w					

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

### Full text of H-Statements

H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H360F	: May damage fertility.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikadur<sup>®</sup>-33 Part A



Revision Date: 23.01.2025 Date of last issue: 08.01.2025	Version 12	2.0	Print Date 24.01.2025	
H410	· Vory toxic to equatio lif	e with long lasting effect		
H410	: Toxic to aquatic life wit		.5.	
Full text of other abbreviatio		0 0		
Aquatic Chronic	: Long-term (chronic) aq	uatic hazard		
Asp. Tox.	: Aspiration hazard			
Eye Dam.	: Serious eye damage			
Eye Irrit.	: Eye irritation			
Repr.	: Reproductive toxicity			
Skin Irrit.	: Skin irritation			
Skin Sens.	: Skin sensitisation			
STOT SE		oxicity - single exposure		
DE TRGS 900		Occupational exposure	limit values	
DE TRGS 900 / TWA	: Time Weighted Average			
ADR		concerning the Internation	nal Carriage of	
ABR	Dangerous Goods by F		shar Garnage Or	
CAS	: Chemical Abstracts Se			
DNEL	: Derived no-effect level			
EC50	: Half maximal effective			
GHS	: Globally Harmonized S			
IATA	: International Air Transp			
IMDG		Code for Dangerous Go	ods	
LD50		e amount of a material,		
2200		e death of 50% (one half		
	test animals)			
LC50	,	ation (concentrations of	the chemical in	
		test animals during the		
	period)			
MARPOL		on for the Prevention of I	Pollution from	
-		d by the Protocol of 197		
OEL	: Occupational Exposure			
PBT	: Persistent, bioaccumul			
PNEC	: Predicted no effect cor			
REACH	: Regulation (EC) No 19	07/2006 of the Europea	n Parliament	
		8 December 2006 conce		
	istration, Evaluation, A	uthorisation and Restric	tion of Chemi-	
	cals (REACH), establis	hing a European Chemi	icals Agency	
SVHC	: Substances of Very High		2 1	
vPvB	: Very persistent and ve	ry bioaccumulative		
Further information				
Classification of the mixture	:	Classification proce	dure:	
Skin Irrit. 2	H315	Calculation method		
Eye Dam. 1	H318	Calculation method		
Skin Sens. 1	H317	Calculation method		
Repr. 1B	H360F	Calculation method		
	H411	Calculation method		



Revision Date: 23.01.2025 Date of last issue: 08.01.2025 Version 12.0

Print Date 24.01.2025

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN