according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-701 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.

Zonnebaan 56 3542 EG Utrecht Nederland

 Telephone
 : +31-30-2410120

 Telefax
 : +31-30-2414482

 E-mail address of person
 : EHS@nl.sika.com

responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin corrosion, Sub-category 1B H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Hazard pictograms





Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH071 Corrosive to the respiratory tract.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Im-

mediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

Hazardous components which must be listed on the label:

2-phenoxyethanol
3-aminomethyl-3,5,5-trimethylcyclohexylamine
m-phenylenebis(methylamine)
3.6.9-triazaundecamethylenediamine

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--|---|--|--------------------------|
| 2-phenoxyethanol | 122-99-6 204-589-7 01-2119488943-21- XXXX | Acute Tox. 4; H302 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Acute toxicity estimate Acute oral toxicity: 1.394 mg/kg | >= 25 - < 40 |
| 3-aminomethyl-3,5,5- trimethylcyclohexylamine | 2855-13-2 220-666-8 01-2119514687-32- XXXX | Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 ———————————————————————————————————— | >= 10 - < 20 |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Revision Date: 10.06.2024

| m-phenylenebis(methylamine) | 1477-55-0 216-032-5 01-2119480150-50- XXXX | Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 EUH071 ———————————————————————————————————— | >= 10 - < 20 |
|---|---|--|--------------|
| 2-(2-phenoxyethoxy)ethanol | 104-68-7 203-227-5 01-2119958189-22- XXXX | Eye Dam. 1; H318 | >= 10 - < 20 |
| 3,6,9-triazaundecamethylenediamine | 112-57-2 203-986-2 01-2119487290-37- XXXX (covered by CAS 90640-66-7) | Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411 —————————————————————————————————— | >= 5 - < 10 |
| 2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 % | 90-72-2 202-013-9 01-2119560597-27- XXXX | Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg | >= 5 - < 10 |
| 2-Propenenitrile, reaction products with 2,2,4(or 2,4,4)-trimethyl-1,6-hexanediamine | 90530-20-4 292-059-6 01-2120773937-35- XXXX | Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 2; H411 | >= 3 - < 5 |
| Phenol, ethoxylated | 9004-78-8 500-013-6 | Acute Tox. 4; H302 Eye Irrit. 2; H319 | >= 1 - < 2,5 |

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

| 2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine | 25513-64-8 247-063-2 01-2119560598-25- XXXX | Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 | >= 1 - < 2,5 |
|---|--|--|--------------|
| | | Acute toxicity esti- mate | |
| | | Acute oral toxicity: 910 mg/kg | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Gastrointestinal discomfort

Cough

Respiratory disorder Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Revision Date: 10.06.2024

Risks : Health injuries may be delayed.

corrosive effects irritant effects sensitising effects

Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Corrosive to the respiratory tract.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters * | Basis * |
|-----------------------------|-----------|-------------------------------|---------------------------|-------------|
| 2-phenoxyethanol | 122-99-6 | TWA | 20 ppm 110 mg/m3 | DE TRGS 900 |
| m-phenylenebis(methylamine) | 1477-55-0 | L | 0,02 ppm 0,1 mg/m3 | DK OEL |

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent

Country NL 100000051496

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Revision Date: 10.06.2024 Version 2.1 Print Date 14.06.2024

Date of last issue: 26.05.2024

to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

liquid Physical state Colour yellow

Odour amine-like

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

Flash point : > 101 °C

Method: open cup

Auto-ignition temperature No data available

Decomposition temperature No data available

рН ca. 11

Concentration: 50 %

Viscosity

Viscosity, dynamic ca. 200 mPa.s (20 °C)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0,04 hPa

Density : ca. 1,017 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Revision Date: 10.06.2024 Version 2.1 Print Date 14.06.2024

Date of last issue: 26.05.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Components:

2-phenoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.394 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate: 1.030 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

LD50 (Rabbit): > 2.000 - 5.000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute toxicity estimate: 930 mg/kg Method: Calculation method

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute toxicity estimate: 1,34 mg/l Test atmosphere: dust/mist Method: Calculation method


Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

2-(2-phenoxyethoxy)ethanol:

Acute oral toxicity : LD50 Oral (Rat): 3.526 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Revision Date: 10.06.2024

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 1.716,2 mg/kg

Acute toxicity estimate: 1.716,2 mg/kg

Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): 1.260 mg/kg

Acute toxicity estimate: 1.260 mg/kg

Method: Calculation method

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg

Remarks: Harmful if swallowed.

Annex VI - Harmonised

REGULATION (EC) No 1272/2008

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

Acute toxicity estimate: 910 mg/kg Method: Calculation method

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit Assessment : Corrosive

Method : OECD Test Guideline 404

Assessment : irritating

Remarks : Annex VI - Harmonised

REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit

Assessment : Causes serious eye damage.

Assessment : irritating

Remarks : Annex VI - Harmonised

REGULATION (EC) No 1272/2008



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Revision Date: 10.06.2024 Version 2.1 Print Date 14.06.2024

Date of last issue: 26.05.2024

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation. Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic

mg/l

plants

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l

Exposure time: 72 h

Country NL 100000051496

13 / 19

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae/aquatic

plants

EC50 (Scenedesmus capricornutum (fresh water algae)): 29,5

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

LC50: 174 mg/l Exposure time: 48 h

Species: Leuciscus idus (Golden orfe)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Country NL 100000051496

14 / 19

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Revision Date: 10.06.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

 ADR
 : UN 2735

 IMDG
 : UN 2735

 IATA
 : UN 2735

14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

IATA : Amines, liquid, corrosive, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADR

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

Packing group : II
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : II Labels : 8 EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo : 855

aircraft)

Packing instruction (LQ) : Y840 Packing group : II

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 851

ger aircraft)

Packing instruction (LQ) : Y840 Packing group : II

Labels : Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

Country NL 100000051496

16 / 19

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 75:

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.

H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DK OEL : Denmark. Occupational Exposure Limits

DE TRGS 900 / TWA : Time Weighted Average

DK OEL / L : Ceiling

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-701 Part B



Date of last issue: 26.05.2024

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

| Classification of the mixture: | | Classification procedure: |
|--------------------------------|------|---------------------------|
| Acute Tox. 4 | H302 | Calculation method |
| Skin Corr. 1B | H314 | Calculation method |
| Eye Dam. 1 | H318 | Calculation method |
| Skin Sens. 1 | H317 | Calculation method |
| STOT SE 3 | H335 | Calculation method |
| Aquatic Chronic 3 | H412 | Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NL / EN