

Revision Date: 15.01.2025 Date of last issue: - Version 1.0

Print Date 16.01.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifier**

Trade name

: SikaCor<sup>®</sup> ZP Primer Part A

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Polyurethane coating, Corrosion protection, For professional users only.

## 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

## 1.4 Emergency telephone number

+31-57-0854201

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2, hearing organs	H373: May cause damage to organs through pro- longed or repeated exposure.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: - Version 1.0

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)						
Hazard pictograms :						
Signal word :	Warning					
Hazard statements :	H315 Ca H317 Ma H319 Ca H335 Ma H373 Ma thr	ammable liquid and vapour. Inuses skin irritation. Ay cause an allergic skin reaction. Inuses serious eye irritation. Ay cause respiratory irritation. Ay cause damage to organs (hearing organs) ough prolonged or repeated exposure. xic to aquatic life with long lasting effects.				
Precautionary statements :	Prevention:					
	P210 P260 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe mist or vapours. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.				
	Response:					
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.				
	P391	Collect spillage.				

### Hazardous components which must be listed on the label:

Acrylic copolymer reaction mass of ethylbenzene and xylene

### **Additional Labelling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 SikaCor® ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: - Version 1.0

Print Date 16.01.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Acrylic copolymer	Not Assigned Not Assigned	Skin Irrit. 2; H315 Skin Sens. 1B; H317	>= 10 - < 20
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20
trizinc bis(orthophosphate) Contains: zinc oxide <= 2 %	7779-90-0 231-944-3 01-2119485044-40- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 5 - < 10

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# SikaCor<sup>®</sup> ZP Primer Part A

Revision Date: 15.01.2025 Print Date 16.01.2025 Version 1.0 Date of last issue: zinc oxide 1314-13-2 Aquatic Acute 1; >= 0,1 - < 0,25 215-222-5 H400 01-2119463881-32-Aquatic Chronic 1; XXXX H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 Substances with a workplace exposure limit : Titanium dioxide (> 10 µm) 13463-67-7 >= 5 - < 10 236-675-5 01-2119489379-17-XXXX

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

	General advice :		Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
	If inhaled :	:	Move to fresh air. Consult a physician after significant exposure.
	In case of skin contact :	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
	In case of eye contact :		Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	If swallowed :	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2	Most important symptoms and	l e	ffects, both acute and delayed
	Symptoms :	:	Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaCor<sup>®</sup> ZP Primer Part A



Version 1.0 Revision Date: 15.01.2025 Print Date 16.01.2025 Date of last issue: -Risks Causes skin irritation. ٠ May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. irritant effects sensitising effects 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing media : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Unsuitable extinguishing Water : media High volume water jet 5.2 Special hazards arising from the substance or mixture Specific hazards during fire-5 Do not use a solid water stream as it may scatter and spread fighting fire. Do not allow run-off from fire fighting to enter drains or water courses. Hazardous combustion prod- : No hazardous combustion products are known ucts

## 5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



Revision Date: 15.01.2025 Date of last issue: - Version 1.0

Print Date 16.01.2025

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions		
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

## 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advi	ce on safe handling :	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Take precautionary measures against static discharge.</li> <li>Open drum carefully as content may be under pressure.</li> <li>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
	ce on protection against : ind explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: -		Version 1.0	Print Date 16.01.2025
Hygiene measures	:	Handle in accordance with good industrial hygier practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the er	using do not
7.2 Conditions for safe storage, i	incl	uding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Containers which are opened must be car sealed and kept upright to prevent leakage. Stor ance with local regulations.	efully re-
Further information on stor- age stability	:	No decomposition if stored and applied as direct	ed.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet p use.	rior to any

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
reaction mass of ethylbenzene and xy- lene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further inform	ation: Identifies the	possibility of signi	ficant uptake
	through the sk	in, Indicative	. , , ,	
		STEL	100 ppm 442 mg/m3	2000/39/EC
		TLV-8hr	47,5 ppm 210 mg/m3	NL WG
	Further inform	ation: Skin notation		
		TLV-15 min	100 ppm 442 mg/m3	NL WG
Titanium dioxide (> 10 μm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## 8.2 Exposure controls

### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

:

### Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor<sup>®</sup> ZP Primer Part A



evision Date: 15.01.2025 ate of last issue: -	Version 1.0	Print Date 16.01.2025
Hand protection	<ul> <li>Chemical-resistant, impervious gloves co proved standard must be worn at all times chemical products. Reference number EN facturer specifications.</li> <li>Suitable for short time use or protection a Butyl rubber/nitrile rubber gloves (&gt; 0,1 m Contaminated gloves should be removed Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time &gt;30 min.</li> </ul>	s when handling N 374. Follow manu- ngainst splashes: nm)
Skin and body protection	: Protective clothing (e.g. Safety shoes acc long-sleeved working clothing, long trous and protective boots are additionaly recor and stirring work.	ers). Rubber aprons
Respiratory protection	<ul> <li>In case of inadequate ventilation wear respective respective levels, the hazards of the produing limits of the selected respirator.</li> <li>organic vapor (Type A) and particulate fill A1: &lt; 1000 ppm; A2: &lt; 5000 ppm; A3: &lt; 7</li> <li>P1: Inert material; P2, P3: hazardous sub Ensure adequate ventilation. This can be exhaust extraction or by general ventilation ods for determining inhalation exposure).</li> <li>ticular to the mixing / stirring area. In case to keep the concentrations under the occol limits then respiration protection measure</li> </ul>	nown or anticipated act and the safe work- ter 10000 ppm ostances achieved by local on. (EN 689 - Meth- This applies in par- e this is not sufficent upational exposure
Environmental exposure co	ntrols	
General advice	: Prevent product from entering drains. If the product contaminates rivers and lak	tes or drains inform

respective authorities.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	: : :	liquid viscous liquid various
Odour	:	slight
Melting point/ range / Freez- ing point	:	No data available
		Nuclear a statute

Boiling point/boiling range : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: -		Version 1.0	Print Date 16.01.2025
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	olosive limits	
Upper explosion limit / Up- per flammability limit	:	Upper explosion limit ca. 7 %(V)	
Lower explosion limit / Lower flammability limit	:	Lower explosion limit ca. 0,8 %(V)	
Flash point	:	ca. 34 °C Method: closed cup	
Auto-ignition temperature	:	465 °C	
Decomposition temperature	:	No data available	

1	applicable tance/mixture is non-soluble (in water)
---	---

# Viscosity

## Solubility(ies)

Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available

- Vapour pressure : ca. 7,99 hPa (20 °C)
- Density : ca. 1,5 g/cm3 (20 °C) Relative vapour density : No data available
- Particle characteristics : No data available

## 9.2 Other information

No data available



Revision Date: 15.01.2025 Date of last issue: -	Version 1.0	Print Date 16.01.2025
SECTION 10: Stability and	eactivity	
10.1 Reactivity		
No dangerous reaction kno	n under conditions of normal use.	
10.2 Chemical stability		
The product is chemically s	able.	
10.3 Possibility of hazardous	eactions	
Hazardous reactions	: Stable under recommended storage con	ditions.
	Vapours may form explosive mixture wit	h air.
10.4 Conditions to avoid		
Conditions to avoid	: Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decompositio	products	
	:	
	No hazardous decomposition products a	are known.
SECTION 11: Toxicological	information	

## Ũ

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified due to lack of <u>Components:</u>	data.	
reaction mass of ethylben	zene	and xylene:
Acute oral toxicity		LD50 Oral (Rat): 3.523 mg/kg
Hydrocarbons, C9, aromat		
Acute oral toxicity		LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
trizinc bis(orthophosphate Acute oral toxicity	e): :	LD50 Oral (Rat): > 5.001 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,7 mg/l Exposure time: 4 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor<sup>®</sup> ZP Primer Part A



vision Date: 15.01.2025 te of last issue: -		Version 1.0	Print Date 16.01.2
		Test atmosphere: dust/mist	
zinc oxide:			
Acute oral toxicity	:	LD50 Oral (Rat): > 15.000 mg/kg	
Acute inhalation toxicity	:	LC50 (Rat): > 5,7 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Skin corrosion/irritation Causes skin irritation.			
Components:			
Hydrocarbons, C9, aromatic	s:		
Assessment	:	Repeated exposure may cause skin dryness	or cracking.
Serious eye damage/eye irri Causes serious eye irritation.	tati	on	
Respiratory or skin sensitis	atio	on	
<b>Skin sensitisation</b> May cause an allergic skin rea	acti	on.	
Respiratory sensitisation Not classified due to lack of da	ata.		
Germ cell mutagenicity Not classified due to lack of da	ata.		
<b>Carcinogenicity</b> Not classified due to lack of da	ata.		
Reproductive toxicity Not classified due to lack of da	ata.		
<b>STOT - single exposure</b> May cause respiratory irritation	n.		
<b>STOT - repeated exposure</b> May cause damage to organs	(he	earing organs) through prolonged or repeated e	exposure.
Aspiration toxicity Not classified due to lack of da	ata.		
2 Information on other hazard	s		
Endocrine disrupting proper	rtie	s	
Product: Assessment	:	The substance/mixture does not contain compered to have endocrine disrupting properties a	

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 SikaCor® ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: - Version 1.0

Print Date 16.01.2025

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

12.1 Toxicity

## **Components:**

	reaction mass of ethylbenzene and xylene:Toxicity to fish (Chronic tox-: NOEC: > 1,3 mg/licity)Exposure time: 56 d					
			Species: Oncorhynchus mykiss (rainbow trout)			
	Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)			
	Hydrocarbons, C9, aromatics	:				
	Toxicity to algae/aquatic plants	:	(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l Exposure time: 72 h			
	zinc oxide:					
	Toxicity to algae/aquatic plants	:	EC50 (Selenastrum capricornutum (green algae)): 0,17 mg/l Exposure time: 72 h			
	M-Factor (Acute aquatic tox- icity)	:	1			
	M-Factor (Chronic aquatic toxicity)	:	1			
12.2	Persistence and degradability	v				
	No data available	,				
12.3	Bioaccumulative potential No data available					
12.4	Mobility in soil No data available					
12.5	12.5 Results of PBT and vPvB assessment					
	Product:					
	Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or			

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaCor<sup>®</sup> ZP Primer Part A



Version 1.0	Print Date 16.01.2025
very persistent and very bioaccumula 0.1% or higher	ative (vPvB) at levels of
erties	
: The substance/mixture does not con ered to have endocrine disrupting pr REACH Article 57(f) or Commission (EU) 2017/2100 or Commission Reg levels of 0.1% or higher.	operties according to Delegated regulation
: An environmental hazard cannot be unprofessional handling or disposal. Toxic to aquatic life with long lasting	
	<ul> <li>very persistent and very bioaccumul 0.1% or higher</li> <li>erties</li> <li>The substance/mixture does not cor ered to have endocrine disrupting pr REACH Article 57(f) or Commission (EU) 2017/2100 or Commission Reg levels of 0.1% or higher.</li> <li>An environmental hazard cannot be unprofessional handling or disposal.</li> </ul>

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	wherever possible. Empty containers or liners This material and its contai way. Dispose of surplus and nor waste disposal contractor. Disposal of this product, so at all times comply with the	nould be avoided or minimized may retain some product residues. ner must be disposed of in a safe n-recyclable products via a licensed lutions and any by-products should requirements of environmental
	protection and waste dispo local authority requirement	sal legislation and any regional s. laterial and runoff and contact with

## **SECTION 14: Transport information**

14.1 UN number or ID number		
ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADR	:	PAINT

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: -		Version 1.0		Print Date 16.01.2025
IMDG	:	PAINT (solvent naphtha)		
ΙΑΤΑ	:	Paint		
14.3 Transport hazard class(es)				
		Class	Subsidiary risks	
ADR	:	3		
IMDG	:	3		
ΙΑΤΑ	:	3		
14.4 Packing group				
<b>ADR</b> Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)		
<b>IMDG</b> Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids		
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels		355		
14.5 Environmental hazards				
<b>ADR</b> Environmentally hazardous	:	yes		
IMDG Marine pollutant	:	yes		
IATA (Passenger) Environmentally hazardous	:	yes		
IATA (Cargo) Environmentally hazardous	:	yes		

## SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Date of last issue: - Version 1.0

Print Date 16.01.2025

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or

All substances contained in our Products are

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75:
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Version 1.0 Print Date 16.01.2025 Date of last issue: -Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. **ENVIRONMENTAL HAZARDS** E2 P5c FLAMMABLE LIQUIDS 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) Volatile organic compounds Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 23,17% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 23,25% w/w

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment). reaction mass of ethylbenzene and xylene dibutyltin dilaurate

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

### Full text of H-Statements

H226 :	Flammable liquid and vapour.
H304 :	May be fatal if swallowed and enters airways.
H312 :	Harmful in contact with skin.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H319 :	Causes serious eye irritation.
H332 :	Harmful if inhaled.
	May cause respiratory irritation.
H336 :	May cause drowsiness or dizziness.
H373 :	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400 :	Very toxic to aquatic life.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaCor<sup>®</sup> ZP Primer Part A



Revision Date: 15.01.2025 Version 1.0 Print Date 16.01.2025 Date of last issue: -H410 Very toxic to aquatic life with long lasting effects. : Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412 Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard Asp. Tox. Aspiration hazard : Eve Irrit. Eve irritation : Flam. Liq. Flammable liquids Skin Irrit. : Skin irritation Skin Sens. Skin sensitisation Specific target organ toxicity - repeated exposure STOT RE : STOT SE Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first 2000/39/EC list of indicative occupational exposure limit values Germany. TRGS 900 - Occupational exposure limit values. DE TRGS 900 : Netherlands. Law on Labour conditions - Occupational Expo-NL WG : sure Limits Limit Value - eight hours 2000/39/EC / TWA : 2000/39/EC / STEL Short term exposure limit DE TRGS 900 / TWA **Time Weighted Average** NL WG / TLV-8hr **Time Weighted Average** NL WG / TLV-15 min Short Term Exposure Limit ADR European Agreement concerning the International Carriage of Dangerous Goods by Road **Chemical Abstracts Service** CAS : DNEL Derived no-effect level Half maximal effective concentration EC50 : GHS **Globally Harmonized System** : International Air Transport Association IATA : IMDG International Maritime Code for Dangerous Goods LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) LC50 Median lethal concentration (concentrations of the chemical in : air that kills 50% of the test animals during the observation period) MARPOL International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 OEL Occupational Exposure Limit : Persistent, bioaccumulative and toxic PBT : PNEC Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament REACH and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency SVHC Substances of Very High Concern vPvB Very persistent and very bioaccumulative



Revision Date: 15.01.2025 Date of last issue: - Version 1.0

**Classification procedure:** 

Print Date 16.01.2025

## **Further information**

## Classification of the mixture:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN