

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikagard[®] M 790 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) Acute toxicity, Category 4 H332: Harmful if inhaled. Skin irritation, Category 2 H315: Causes skin irritation. Eye irritation, Category 2 H319: Causes serious eye irritation. Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer. Specific target organ toxicity - single ex-H335: May cause respiratory irritation. posure, Category 3, Respiratory system Specific target organ toxicity - repeated H373: May cause damage to organs through proexposure, Category 2 longed or repeated exposure if inhaled. Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects. egory 2

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Print Date 07.05.2024

Version 2.0

2.2 Label elements

Labelling (REGULATION (EC)	No 1272/200	8)
Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H315 H317 H319 H332 H334 H335 H351 H373 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breath- ing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if inhaled. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention P260 P273 P280	: Do not breathe mist or vapours. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response: P304 + P34 P342 + P31 P391	POISON CENTER/ doctor.
		F 39 I	Collect spillage.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikagard[®] M 790 Part B

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>=80
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48- XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.
Country NL 10000054107	





Revision Date: 03.05.2024 Date of last issue: 02.05.2024	Version 2.0	Print Date 07.05.20
	Consult a physician after significant exposure.	
In case of skin contact	: Take off contaminated clothing and shoes imme Wash off with soap and plenty of water. If symptoms persist, call a physician.	diately.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 	
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsciou 	s person.
4.2 Most important symptoms and	d effects, both acute and delayed	
Symptoms	: Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information on and symptoms.	health effects
Risks	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breaties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonge exposure if inhaled. irritant effects sensitising effects 	-
4.3 Indication of any immediate m	nedical attention and special treatment needed	
Treatment	: Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use v

In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for

Print Date 07.05.2024

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0

extinction.

5.2	Special hazards arising from Specific hazards during fire- fighting		
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for co	ontai	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid formation of aerosol.
		Avoid exceeding the given occupational exposure limits (see
		section 8).
		Do not get in eyes, on skin, or on clothing.
		For personal protection see section 8.
		Persons with a history of skin sensitisation problems or asth-

Sikagard[®] M 790 Part B



Revision Date: 03.05.2024 Date of last issue: 02.05.2024

		ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage,	inc	luding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres	9016-87-9	AGW (Inhalable	0,05 mg/m3	DE TRGS 900
and homologues		fraction)	(MDI)	
	Further information: Senate commission for the review of com- pounds at the work place dangerous for the health has also estab-			
	lished a BEI-va value list'	alue for the same O	EL value in the 'M	IAK- and BAT-

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Sikagard[®] M 790 Part B

Revision Date: 03.05.2024 Date of last issue: 02.05.2024



Version 2.0

Personal protective equipn		
Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	brown

Sikagard[®] M 790 Part B

Print Date 07.05.2024

•		
Revision Date: 03.05.2024 Date of last issue: 02.05.2024		Version 2.0
Odour	:	aliphatic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available

- Decomposition temperature : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)

Viscosity

- Viscosity, dynamic : ca. 2.500 mPa.s (20 °C)
- Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

octanol/water

- Water solubility : insoluble
- Partition coefficient: n- : No data available
- Vapour pressure : 0,01 hPa
- Density : ca. 1,15 g/cm3 (20 °C)

Relative vapour density	:	No data available	
Country NL 100000054107			8 / 16

Sikagard[®] M 790 Part B

Print Date 07.05.2024

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

10.5 Incompatible materials

Materials to avoid	: No data available
--------------------	---------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.

Revision Date: 03.05.2024 Date of last issue: 02.05.2024



Version 2.0 : LD50 Dermal (Rabbit): > 9.400 mg/kg Acute dermal toxicity bis(isopropyl)naphthalene: Acute oral toxicity : LD50 Oral (Rat): > 3.900 mg/kg Acute inhalation toxicity LC50 (Rat): > 5,64 mg/l Exposure time: 4 h Test atmosphere: dust/mist Acute dermal toxicity : LD50 Dermal (Rat): > 4.500 mg/kg Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye irritation Causes serious eye irritation. Respiratory or skin sensitisation Skin sensitisation May cause an allergic skin reaction. **Respiratory sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled. Germ cell mutagenicity Not classified due to lack of data. Carcinogenicity Suspected of causing cancer. **Reproductive toxicity** Not classified due to lack of data. STOT - single exposure May cause respiratory irritation. **STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure if inhaled. Aspiration toxicity Not classified due to lack of data. 11.2 Information on other hazards Endocrine disrupting properties Product: The substance/mixture does not contain components consid-Assessment 1 ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0



SECTION 12: Ecological information

12.1 Toxicity

Diphenylmethanediisocya	nate, isomeres and homologues:
Toxicity to fish	: LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	 EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

	ADR		UN 3082	
	IMDG		UN 3082	
	ΙΑΤΑ	:	UN 3082	
14.2	2 UN proper shipping name			
	N.O.S		ENVIRONMENTALLY N.O.S. (bis(isopropyl)naphtha	(HAZARDOUS SUBSTANCE, LIQUID, alene)
	IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis(isopropyl)naphthalene)	
	ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (bis(isopropyl)naphthalene)	
14.3	B Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	9	
	IMDG	:	9	
	ΙΑΤΑ	:	9	
14.4	Packing group			
	ADR Packing group Classification Code	:	III M6	



Revision Date: 03.05.2024 Date of last issue: 02.05.2024	Version 2.0	Print Date 07.05.20
Hazard Identification Number Labels Tunnel restriction code Remarks	90 9 (-) Transport in accordance with special provision	n 375
IMDG Packing group Labels EmS Code Remarks	III 9 F-A, S-F Transport in accordance with 2.10.2.7 of the I	MDG-Code
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels Remarks	964 Y964 III Miscellaneous Transport in accordance with special regulation	on A 197
ger aircraft) Packing instruction (LQ) Packing group Labels	964 Y964 III Miscellaneous	
14.5 Environmental hazards ADR		
Environmentally hazardous	yes	
IMDG Marine pollutant	yes	
IATA (Passenger) Environmentally hazardous	yes	
IATA (Cargo) Environmentally hazardous	yes	
14.6 Special precautions for user The transport classification(s) p	rovided herein are for informational purposes onl	v. and solelv based

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

Sikagard[®] M 790 Part B

Print Date 07.05.2024

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0

REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.		
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
			Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 74, 56)
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu-	:	Not applicable
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar E2			and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: <= 3% w/w
	emissions (integrated p	oollu	4 November 2010 on industrial ution prevention and control) ds (VOC) content: < 0,01% w/w

Revision Date: 03.05.2024 Date of last issue: 02.05.2024

Version 2.0



15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. : : May cause an allergic skin reaction. H317 Causes serious eye irritation. H319 H332 Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul-H334 ties if inhaled. May cause respiratory irritation. H335 : Suspected of causing cancer. H351 May cause damage to organs through prolonged or repeated H373 exposure if inhaled. H410 Very toxic to aquatic life with long lasting effects. Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Chronic Long-term (chronic) aquatic hazard Asp. Tox. Aspiration hazard Carc. Carcinogenicity : Eve irritation Eve Irrit. : Respiratory sensitisation Resp. Sens. Skin Irrit. : Skin irritation Skin Sens. Skin sensitisation : STOT RE Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure STOT SE DE TRGS 900 Germany. TRGS 900 - Occupational exposure limit values. DE TRGS 900 / AGW **Time Weighted Average** European Agreement concerning the International Carriage of ADR Dangerous Goods by Road CAS **Chemical Abstracts Service** DNEL Derived no-effect level **EC50** Half maximal effective concentration **Globally Harmonized System** GHS : International Air Transport Association IATA International Maritime Code for Dangerous Goods IMDG LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) LC50 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) MARPOL International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 **Occupational Exposure Limit** OEL PBT Persistent, bioaccumulative and toxic

Revision Date: 03.05.2024 Date of last issue: 02.05.2024 Version 2.0



PNEC REACH	 Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi-
SVHC vPvB	 cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification of the	mixture:	Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN