according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PCI® Fugensanierungsfarbe

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.

Zonnebaan 56 3542 EG Utrecht Nederland

 Telephone
 : +31-30-2410120

 Telefax
 : +31-30-2414482

 E-mail address of person
 : EHS@nl.sika.com

responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of 5-chloro-2-

methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May pro-

duce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: bronopol (INN), 52-51-7, 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 55965-84-9. Please use treated articles responsibly.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		, ,
ammonia	1336-21-6	Skin Corr. 1B; H314	>= 0,25 - < 0,5
	215-647-6	Eye Dam. 1; H318	
	01-2119488876-14-	Aquatic Acute 1;	
	XXXX	H400	
		specific concentration limit STOT SE 3; H335 >= 5 %	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

bronopol (INN)	52-51-7 200-143-0 01-2119980938-15- XXXX	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0,025 - < 0,1
		M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9 627-034-4	Acute Tox. 4; H302 Skin Corr. 1B; H314 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aguatic toxicity): 10	>= 0,025 - < 0,1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9 01-2120761540-60- XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,0025 - < 0,025
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
		specific concentration limit Skin Sens. 1A; H317 >= 0,036 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 450 mg/kg Acute inhalation tox- icity (dust/mist): 0,21 mg/l	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 Not Assigned 01-2120764691-48- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % specific concentration limit Eye Irrit. 2; H315 0,06 - < 0,6 % specific concentration limit Eye Irrit. 2; H319 0,06 - < 0,6 % specific concentration limit Eye Irrit. 2; H319 0,06 - < 0,6 %	>= 0,0002 - < 0,0015
Substances with a workplace exposition Titanium dioxide (> 10 µm)	sure limit : 13463-67-7		>= 10 - < 20
For explanation of abbreviations se	236-675-5 01-2119489379-17- XXXX		2 10 120

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

PCI® Fugensanierungsfarbe



Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

Take off contaminated clothing and shoes immediately. In case of skin contact

Wash off with soap and plenty of water.

Remove contact lenses. In case of eye contact

Keep eye wide open while rinsing.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects **Symptoms**

and symptoms.

Risks No known significant effects or hazards.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Further information Standard procedure for chemical fires.

Country NL 000000720128

6 / 17

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour various

Odour slight

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

Flash point Not applicable

No data available Auto-ignition temperature

Decomposition temperature No data available

рΗ ca. 9 - 9,9

Concentration: 100 %

Viscosity

Viscosity, kinematic No data available

Solubility(ies)

Water solubility No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 23 hPa

Density : ca. 1,4 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : Acute toxicity estimate: 450 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 450 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 0,21 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LC50: 0,21 mg/l Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Assessment : May cause sensitisation by skin contact.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bronopol (INN):

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic : 1

toxicity)

C16-18-(even numbered, saturated and unsaturated)-alkylamines:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 10

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 3 mg/l

aquatic invertebrates

Exposure time: 48 h

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic 1

toxicity)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

100

100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®]

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

Netherlands. Substances of very high concern (ZZS-list)

Distillates (petroleum), hydrotreated

heavy naphthenic; Baseoil - un-

specified

Not applicable

Regulation (EU) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 1,31% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed. H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H310 : Fatal in contact with skin. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H330 : Fatal if inhaled. H331 : Toxic if inhaled.

H335 : May cause respiratory irritation.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

PCI® Fugensanierungsfarbe

Revision Date: 14.03.2025 Version 1.0 Print Date 21.03.2025

Date of last issue: -

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / TWA : Time Weighted Average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NL / EN