

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikaflex®-691

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.  
Zonnebaan 56  
3542 EG Utrecht  
Nederland  
Telephone : +31-30-2410120  
Telefax : +31-30-2414482  
E-mail address of person responsible for the SDS : EHS@nl.sika.com

#### 1.4 Emergency telephone number

National emergency contact NL: National Poisons Information Center +31-88-755-8000

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.  
Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
**Prevention:**  
P261 Avoid breathing mist or vapours.  
P273 Avoid release to the environment.  
P280 Wear protective gloves.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

### Disposal:

P501

Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

Hexamethylene-1,6-diisocyanate homopolymer

Pentamethyl piperidylsebacate

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane

4,4'-methylenediphenyl diisocyanate

### Additional Labelling

EUH204

Contains isocyanates. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72-XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
Hexamethylene-1,6-diisocyanate homopolymer Contains: hexamethylene-di-isocyanate <= 0,3 %	28182-81-2 931-274-8 01-2119485796-17-XXXX	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)  Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 1,5 mg/l	>= 0,5 - < 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026

Version 4.3

Print Date 05.06.2026

Date of last issue: 26.02.2026

<p>Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</p>	<p>1065336-91-5 915-687-0 01-2119491304-40-XXXX</p>	<p>Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1</p>	<p>&gt;= 0,25 - &lt; 0,5</p>
<p>Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane</p>	<p>192526-20-8 924-669-1 01-2120768758-32-XXXX</p>	<p>Skin Sens. 1A; H317</p>	<p>&gt;= 0,1 - &lt; 0,5</p>
<p>4,4'-methylenediphenyl diisocyanate</p>	<p>101-68-8 202-966-0 615-005-00-9 01-2119457014-47-XXXX</p>	<p>Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373</p> <hr/> <p>specific concentration limit Eye Irrit. 2; H319 &gt;= 5 %</p> <p>STOT SE 3; H335 &gt;= 5 %</p> <p>Skin Irrit. 2; H315 &gt;= 5 %</p> <p>Resp. Sens. 1; H334 &gt;= 0,1 %</p> <hr/> <p>Acute toxicity estimate</p> <p>Acute inhalation toxicity (dust/mist): 1,5 mg/l</p>	<p>&lt; 0,1</p>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026

Version 4.3

Print Date 05.06.2026

Date of last issue: 26.02.2026

Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17-XXXX		>= 2,5 - < 5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : sensitising effects  
  
May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026

Version 4.3

Print Date 05.06.2026

Date of last issue: 26.02.2026

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026

Version 4.3

Print Date 05.06.2026

Date of last issue: 26.02.2026

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated areas and containers place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	10 mg/m3	DE TRGS 900
Hexamethylene-1,6-diisocyanate homopolymer	28182-81-2	TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		STEL	0,02 mg/m3 (NCO)	98/24/EC I

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

### 8.2 Exposure controls

#### Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Individual protection measures, such as personal protective equipment (PPE)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026

Version 4.3

Print Date 05.06.2026

Date of last issue: 26.02.2026

- Eye/face protection : Safety glasses with side-shields conforming to EN166
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
- Environmental exposure controls**
- General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Form : paste
- Colour : various
- Odour : odourless
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
<b>Viscosity</b>		
Viscosity, dynamic	:	ca. 150 mPa.s (20 °C)
Viscosity, kinematic	:	No data available
<b>Solubility(ies)</b>		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,33 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

### 10.5 Incompatible materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402

##### **Hexamethylene-1,6-diisocyanate homopolymer:**

Acute oral toxicity : LD50 Oral (Rat): > 2.500 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

##### **Pentamethyl piperidylsebacate:**

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

##### **Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

Test atmosphere: dust/mist  
Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

### **Skin corrosion/irritation**

Not classified due to lack of data.

### **Serious eye damage/eye irritation**

Not classified due to lack of data.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

### **Respiratory sensitisation**

Not classified due to lack of data.

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

Not classified due to lack of data.

### **STOT - repeated exposure**

Not classified due to lack of data.

### **Aspiration hazard**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

Not classified due to lack of data.

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

#### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl]-:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l  
Exposure time: 72 h

### **Pentamethyl piperidylsebacate:**

Toxicity to fish : LC50 (Fish): 0,97 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

mation unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA (Cargo) : Not regulated as a dangerous good  
IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026

Version 4.3

Print Date 05.06.2026

Date of last issue: 26.02.2026

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 52: 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)  
Volatile organic compounds (VOC) content: < 0,01% w/w  
no VOC duties

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: < 0,01% w/w

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment). manganese ferrite black spinel

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
98/24/EC I	: Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
98/24/EC I / STEL	: Limit values Short-term
98/24/EC I / TWA	: Limit values 8 hours
DE TRGS 900 / TWA	: Time Weighted Average
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikaflex®-691



Revision Date: 02.06.2026  
Date of last issue: 26.02.2026

Version 4.3

Print Date 05.06.2026

DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Skin Sens. 1	H317
Aquatic Chronic 3	H412

#### Classification procedure:

Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NL / EN