

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Pulastic® Coating 221 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.
Zonnebaan 56
3542 EG Utrecht
Nederland
Telephone : +31-30-2410120
Telefax : +31-30-2414482
E-mail address of person : EHS@nl.sika.com
responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B





Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

Hazard pictograms	:	 
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Hexamethylene diisocyanate, oligomers
2-methoxy-1-methylethyl acetate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hexamethylene diisocyanate, oligomers Contains: hexamethylene-di-isocyanate <= 0,49 %	28182-81-2 Not Assigned	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l	>= 60 - < 80
2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 %	108-65-6 203-603-9 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25 - < 40

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough
Respiratory disorder
Allergic reactions
Headache
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

Risks : irritant effects
sensitising effects

May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024
Date of last issue: 06.09.2024

Version 14.0

Print Date 13.09.2024

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		TWA	50 ppm 275 mg/m ³	2000/39/EC
		TLV-8hr	100 ppm 550 mg/m ³	NL WG

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Colour : yellow
- Odour : hydrocarbon-like
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024
Date of last issue: 06.09.2024

Version 14.0

Print Date 13.09.2024

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit
per flammability limit : 10,8 %(V)

Lower explosion limit / Lower flammability limit : 1,5 %(V)

Flash point : 54 °C
Method: closed cup

Auto-ignition temperature : 333 °C

Decomposition temperature : No data available

pH : Not applicable
substance/mixture reacts with water

Viscosity

Viscosity, kinematic : > 7 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 7 hPa

Density : 1,08 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Hexamethylene diisocyanate, oligomers:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l
Test atmosphere: dust/mist
Method: Calculation method

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hexamethylene diisocyanate, oligomers:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1866

IMDG : UN 1866

IATA : UN 1866

14.2 UN proper shipping name

ADR : RESIN SOLUTION

IMDG : RESIN SOLUTION

IATA : Resin solution

14.3 Transport hazard class(es)

	Class	Subsidiary risks
--	-------	------------------

ADR : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 74: Hexamethylene diisocyanate, oligomers

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 25% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 25% w/w

MAL-Code-Number : 5-6

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H317 : May cause an allergic skin reaction.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
NL WG : Netherlands. Law on Labour conditions - Occupational Exposure Limits
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
NL WG / TLV-8hr : Time Weighted Average
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Pulastic® Coating 221 Part B



Revision Date: 06.09.2024

Version 14.0

Print Date 13.09.2024

Date of last issue: 06.09.2024

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

NL / EN