

Revision Date: 13.03.2025 Date of last issue: - Version 1.0

Print Date 14.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sarnacol® T-660

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Sealant/adhesive, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol[®] T-660



Revision Date: 13.03.2025 Date of last issue: -		V	ersion 1.0	Print Date 14.03.2025
Hazard pictograms	:		!	
Signal word	:	Danger		
Hazard statements	:	H315 Ca H319 Ca H336 Ma	hly flammable liquid and vapour. uses skin irritation. uses serious eye irritation. y cause drowsiness or dizziness. kic to aquatic life with long lasting	effects.
Precautionary statements	:	Prevention:		
		P210 P233 P261 P273	Keep away from heat, hot surfa open flames and other ignition s smoking. Keep container tightly closed. Avoid breathing mist or vapours Avoid release to the environment	sources. No
		Response:		
		P370 + P378	In case of fire: Use dry sand, dr alcohol-resistant foam to exting	
		P391	Collect spillage.	

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sarnacol[®] T-660



Revision Date: 13.03.2025 Date of last issue: - Version 1.0

Print Date 14.03.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	Not Assigned 921-024-6 01-2119475514-35- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 40 - < 60
butanone	78-93-3 201-159-0 01-2119457290-43- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 20 - < 25
zinc oxide	1314-13-2 215-222-5 01-2119463881-32- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.	
If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. 	
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses.	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Date of last issue: -	Version 1.0	Print Date 14.03.2025
	Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	s person.
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms :	Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on and symptoms.	health effects
Risks :	irritant effects	
	Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.	
4.3 Indication of any immediate me	dical attention and special treatment needed	
Treatment :	Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5 3 Advice for firefighters		

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Sarnacol[®] T-660



 Revision Date: 13.03.2025
 Version 1.0
 Print Date 14.03.2025

 Date of last issue: for firefighters

 Further information
 :
 Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

 SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
----------------------	--

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Do not breathe vapours or spray mist.
	Avoid exceeding the given occupational exposure limits (see
	section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Smoking, eating and drinking should be prohibited in the ap-
	plication area.
	Take precautionary measures against static discharge.
	Open drum carefully as content may be under pressure.
	Take necessary action to avoid static electricity discharge
	(which might cause ignition of organic vapours).
	Follow standard hygiene measures when handling chemical

Sarnacol[®] T-660

_



Revision Date: 13.03.2025 Date of last issue: -		Version 1.0	Print Date 14.03.2025
		products	
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away open flames/ hot surfaces. No smoking. Tak measures against electrostatic discharges.	
Hygiene measures	:	Handle in accordance with good industrial hy practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the	nen using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Store in cool place. Containers which are op carefully resealed and kept upright to prever in accordance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and applied as d	irected.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data She use.	et prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Hydrocarbons, C6-C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Not Assigned	TLV-8hr (Mist)	5 mg/m3	NL WG
butanone	78-93-3	TWA	200 ppm 600 mg/m3	2000/39/EC
	Further information: Indicative			
		STEL	300 ppm 900 mg/m3	2000/39/EC
		TLV-8hr	197 ppm 590 mg/m3	NL WG
	Further information: Skin notation			
		TLV-15 min	300 ppm 900 mg/m3	NL WG

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.





e 14.03.2025

Revision Date: 13.03.2025 Date of last issue: -	Version 1.0	Print Date
Personal protective equipment		
Eye/face protection :	Safety glasses with side-shields conforming Eye wash bottle with pure water	g to EN166
Hand protection :	Chemical-resistant, impervious gloves comproved standard must be worn at all times chemical products. Reference number EN a facturer specifications. Suitable for short time use or protection age Butyl rubber/nitrile rubber gloves (> 0,1 mm Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	when handling 374. Follow manu- ainst splashes:
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. long-sleeved working clothing, long trouser and protective boots are additionaly recom and stirring work.	s). Rubber aprons
Respiratory protection	In case of inadequate ventilation wear resp	iratory protection

inadequate ventilation wear respiratory protection. spiratory protection Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid yellow
Odour	:	solvent-like
Melting point/ range / Freez-	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Date of last issue: -	Version 1.0	Print Date 14.03.2025
ing point		
Boiling point/boiling range	: >78 °C	
Flammability (solid, gas)	: No data available	
Upper/lower flammability or	xplosive limits	
Upper explosion limit / Upper flammability limit	-	
Lower explosion limit / Lower flammability limit	: Lower explosion limit 2,1 %(V)	
Flash point	: ca12 °C Method: closed cup	
Auto-ignition temperature	: 460 °C	
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	: ca. 4.700 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: ca. 110 hPa (20 °C)	
Density	: ca. 0,79 g/cm3 (20 °C)	
Relative vapour density	: No data available	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Date of last issue: -	Version 1.0	Print Date 14.03.202
Particle characteristics	: No data available	
9.2 Other information		
No data available		
SECTION 10: Stability and r	activity	
10.1 Reactivity		
No dangerous reaction know	n under conditions of normal use.	
10.2 Chemical stability		
The product is chemically st	ble.	
10.3 Possibility of hazardous r	actions	
Hazardous reactions	: Stable under recommended storage conditions	
	Vapours may form explosive mixture with air.	
10.4 Conditions to avoid		
Conditions to avoid	: Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decompositior	products	
No decomposition if stored a	nd applied as directed.	

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified due to lack of c <u>Components:</u>	lata.	
butanone: Acute oral toxicity	:	LD50 Oral (Rat): 3.300 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 36 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Date of last issue: -	Version 1.0	Print Date 14.03.2025
zinc oxide:		
Acute oral toxicity :	LD50 Oral (Rat): > 15.000 mg/kg	
Acute inhalation toxicity :	LC50 (Rat): > 5,7 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye irritat Causes serious eye irritation.	tion	
Respiratory or skin sensitisati	on	
Skin sensitisation Not classified due to lack of data	l.	
Respiratory sensitisation Not classified due to lack of data	L.	
Germ cell mutagenicity Not classified due to lack of data	ı.	
Carcinogenicity Not classified due to lack of data	I.	
Reproductive toxicity Not classified due to lack of data	l.	
STOT - single exposure May cause drowsiness or dizzine	ess.	
STOT - repeated exposure Not classified due to lack of data		
Aspiration toxicity Not classified due to lack of data	l.	
11.2 Information on other hazards		
Endocrine disrupting propertie	es	
Product:		
Assessment :	The substance/mixture does not contain c ered to have endocrine disrupting properti REACH Article 57(f) or Commission Delec (EU) 2017/2100 or Commission Regulatio levels of 0.1% or higher.	es according to gated regulation



Revision Date: 13.03.2025 Version 1.0 Print Date 14.03.2025 Date of last issue: -**SECTION 12: Ecological information** 12.1 Toxicity **Components:** Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane: Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l Exposure time: 96 h zinc oxide: Toxicity to algae/aquatic : EC50 (Selenastrum capricornutum (green algae)): 0,17 mg/l plants Exposure time: 72 h M-Factor (Acute aquatic tox-: 1 icity) M-Factor (Chronic aquatic : 1 toxicity) 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential No data available 12.4 Mobility in soil No data available 12.5 Results of PBT and vPvB assessment Product: Assessment This substance/mixture contains no components considered : to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher... 12.6 Endocrine disrupting properties **Product:** The substance/mixture does not contain components consid-Assessment ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects Product: Additional ecological infor-An environmental hazard cannot be excluded in the event of :

Sarnacol[®] T-660



Revision Date: 13.03.2025	Version 1.0	Print Date 14.03.2025
Date of last issue: -		

mation

unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. 	
European Waste Catalogue	: 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances	
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances	

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1133	
	IMDG	:	UN 1133	
	ΙΑΤΑ	:	UN 1133	
14.2	UN proper shipping name			
	ADR	:	ADHESIVES	
	IMDG	:	ADHESIVES (naphtha (petroleum))	
	ΙΑΤΑ	:	Adhesives	
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Date of last issue: -	Version 1.0	Print Date 14.03.202
ΙΑΤΑ	: 3	
14.4 Packing group		
ADR		
Packing group	: 111	
Classification Code	: F1	
Labels	: 3	
Tunnel restriction code	: (E)	
Remarks	Transport according to 2.2.3.1.4 ADR.	
IMDG		
Packing group	: 111	
Labels	: 3	
EmS Code	: F-E, S-D	
Remarks	: Transport according to 2.3.2.2 IMDG.	
IATA (Cargo)		
Packing instruction (cargo	: 366	
aircraft)		
Packing instruction (LQ)	: Y344	
Packing group	: 111	
Labels	: Flammable Liquids	
Remarks	: Transport according to 3.3.3.1.1 IATA.	
IATA (Passenger)		
Packing instruction (passen- ger aircraft)	: 355	
Packing instruction (LQ)	: Y344	
Packing group	: 111	
Labels	: Flammable Liquids	
14.5 Environmental hazards		
ADR Environmentally hazardous	: yes	
-	. ,00	
IMDG		
Marine pollutant	: yes	
IATA (Passenger) Environmentally hazardous	: yes	
IATA (Cargo) Environmentally hazardous	·	
Environmentally hazardous	: yes	

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Sarnacol[®] T-660



Revision Date: 13.03.2025 Version 1.0 Print Date 14.03.2025 Date of last issue: -14.7 Maritime transport in bulk according to IMO instruments Not applicable for product as supplied. **SECTION 15: Regulatory information** 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors **REACH Information:** All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on Conditions of restriction for the fol-• the market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 3 Number on list 75 REACH - Candidate List of Substances of Very High None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %).REACH - List of substances subject to authorisation Not applicable ÷ (Annex XIV) Regulation (EU) No 2024/590 on substances that de-: Not applicable plete the ozone layer Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable tants (recast) Regulation (EU) No 649/2012 of the European Parlia-Not applicable ment and the Council concerning the export and import of dangerous chemicals Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 **ENVIRONMENTAL HAZARDS**

P5c

FLAMMABLE LIQUIDS

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Version 1.0 Print Date 14.03.2025 Date of last issue: -34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d) Volatile organic compounds Law on the incentive tax for volatile organic compounds ÷ (VOCV) Volatile organic compounds (VOC) content: 67,65% w/w Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

Volatile organic compounds (VOC) content: 67,65% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

and control)

SECTION 16: Other information

Full text of H-Statements

H225 H304 H315 H319 H336 H400 H410 H411	· · · · · · · · · · · · · · · · · · ·	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ns	
Aquatic Acute Aquatic Chronic Asp. Tox. Eye Irrit. Flam. Liq. Skin Irrit. STOT SE 2000/39/EC NL WG		Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Aspiration hazard Eye irritation Flammable liquids Skin irritation Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values Netherlands. Law on Labour conditions - Occupational Expo- sure Limits
2000/39/EC / TWA 2000/39/EC / STEL NL WG / TLV-8hr NL WG / TLV-15 min ADR	:	Limit Value - eight hours Short term exposure limit Time Weighted Average Short Term Exposure Limit European Agreement concerning the International Carriage of Dangerous Goods by Road

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sarnacol® T-660



Revision Date: 13.03.2025 Version 1.0 Print Date 14.03.2025 Date of last issue: -CAS **Chemical Abstracts Service** : Derived no-effect level DNEL EC50 Half maximal effective concentration GHS Globally Harmonized System International Air Transport Association IATA : International Maritime Code for Dangerous Goods IMDG LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) LC50 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 OEL **Occupational Exposure Limit** PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament REACH and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency SVHC Substances of Very High Concern : vPvB Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN