

Revision Date: 10.01.2025 Date of last issue: 05.01.2024 Version 3.1

Print Date 10.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaBond® TF Plus N

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H317 H334	May cause an allergic skin reaction. May cause allergy or asthma symptoms or breath- ing difficulties if inhaled.



SikaBond[®] TF Plus N

Revision Date: 10.01.2025 Date of last issue: 05.01.2024	V	ersion 3.1	Print Date 10.01.2025
Precautionary statements :	Prevention: P261 P280 P284	Avoid breathing mist or vapours Wear protective gloves. In case of inadequate ventilatior atory protection.	
	Response:		
	P304 + P340	IF INHALED: Remove person to keep comfortable for breathing.	fresh air and
	P333 + P313	If skin irritation or rash occurs: C advice/ attention.	Set medical
	P342 + P311	If experiencing respiratory symp POISON CENTER/ doctor.	toms: Call a
Hazardous components which	n must be listed o	on the label:	

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxvsilane

4,4'-methylenediphenyl diisocyanate m-tolylidene diisocyanate

Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SikaBond[®] TF Plus N

Revision Date: 10.01.2025	
Date of last issue: 05.01.2024	

Version 3.1

Print Date 10.01.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 1 - < 2,5
Reaction product of Hexameth- ylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	192526-20-8 924-669-1 01-2120768758-32- XXXX	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 0,25 - < 0,5



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond[®] TF Plus N

Revision Date: 10.01.2025 Date of last issue: 05.01.2024 Version 3.1



Print Date 10.01.2025

te of last issue: 05.01.2024			
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 %	>= 0,1 - < 0,5
		specific concentration limit STOT SE 3; H335 >= 5 %	
		limit Skin Irrit. 2; H315 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
		>= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond[®] TF Plus N



Revision Date: 10.01.2025 Version 3.1 Print Date 10.01.2025 Date of last issue: 05.01.2024 m-tolylidene diisocyanate 26471-62-5 Acute Tox. 1; H330 >= 0,025 - < 247-722-4 Skin Irrit. 2; H315 0.1 01-2119454791-34-Eye Irrit. 2; H319 XXXX Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 specific concentration limit Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate Acute inhalation toxicity (vapour): 0,107 mg/l

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond® TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024		Version 3.1	Print Date 10.01.2025
Symptoms	:	Asthmatic appearance Allergic reactions See Section 11 for more detailed informat and symptoms.	tion on health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction. May cause allergy or asthma symptoms o ties if inhaled.	or breathing difficul-
4.3 Indication of any immediate n	ne	dical attention and special treatment nee	eded
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/cher extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are ki	nown
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained br	eathing apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	ie I	neasures	
6.1 Personal precautions, protect	tiv	e equipment and emergency procedures	6
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary	v sewer system.
6.3 Methods and material for con	ntai	nment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e.g acid binder, universal binder, sawdust). Keep in suitable, closed containers for dis	-

SikaBond® TF Plus N



Revision Date: 10.01.2025Version 3.1Print Date 10.01.2025Date of last issue: 05.01.2024Version 3.1Print Date 10.01.2025

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
reaction mass of ethylbenzene and xy-	Not Assigned	TWA	50 ppm	2000/39/EC

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SikaBond® TF Plus N

Revision Date: 10.01.2025 Date of last issue: 05.01.2024 Version 3.1

Print Date 10.01.2025

lene		221 mg/m3		
	Further information: Ide	ntifies the possibility of signif	icant uptake	
	through the skin, Indica	through the skin, Indicative		
	STEL	100 ppm 442 mg/m3	2000/39/EC	
	TLV-8hr	47,5 ppm 210 mg/m3	NL WG	
	Further information: Ski	n notation		
	TLV-15	min 100 ppm 442 mg/m3	NL WG	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene diisocyanate, oligomers with Mercap- topropyltrimethoxysilane	Fresh water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment						
Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes:				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond® TF Plus N

_



Revision Date: 10.01.2025 Date of last issue: 05.01.2024	Version 3.1	Print Date 10.01.2025
	Butyl rubber/nitrile rubber gloves (> 0,1 m Contaminated gloves should be removed Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	: Protective clothing (e.g. Safety shoes acc long-sleeved working clothing, long trous and protective boots are additionally recor and stirring work.	ers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear respective response of the selection must be based on known of the selection must be based on known of the selected respirator. Use a properly fitted NIOSH approved air respirator complying with an approved state sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 700 Ensure adequate ventilation. This can be exhaust extraction or by general ventilation ods for determining inhalation exposure). ticular to the mixing / stirring area. In case to keep the concentrations under the occilimits then respiration protection measure 	nown or anticipated uct and the safe work- r-purifying or air-fed andard if a risk as- 10000 ppm e achieved by local on. (EN 689 - Meth- . This applies in par- e this is not sufficent upational exposure
Environmental exposure con	trols	

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste black
Odour	:	very faint
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond® TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024 Version 3.1

Print Date 10.01.2025

Upper/lower flammability or explosive limits Upper explosion limit / Up- : No data available per flammability limit			
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 101 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,26 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond® TF Plus N



Revision Date: 10.01.2025	Version 3.1	Print Date 10.01.2025
Date of last issue: 05.01.2024		
10.2 Chemical stability		
The product is chemically	table.	
10.3 Possibility of hazardous	reactions	
Hazardous reactions	: No hazards to be specially m	nentioned.
10.4 Conditions to avoid		
Conditions to avoid	: Avoid moisture.	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decomposition	n products	
No decomposition if stored	and applied as directed.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402

reaction mass of ethylbenzene and xylene:

Acute oral toxicity	:	LD50 Oral (Rat): 3.52	23 mg/kg
---------------------	---	-----------------------	----------

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
		Method: OECD Test Guideline 401

SikaBond® TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024	Version 3.1	Print Date 10.01.2025
Acute inhalation toxicity	: LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
	Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
m-tolylidene diisocyanate:		
Acute inhalation toxicity	: LC50 (Rat): 0,107 mg/l Exposure time: 4 h Test atmosphere: vapour	
	Acute toxicity estimate: 0,107 mg/l Test atmosphere: vapour Method: Calculation method	
Skin corrosion/irritation		
Not classified due to lack of da	ata.	
Serious eye damage/eye irri Not classified due to lack of da		
Respiratory or skin sensitis	ation	
Skin sensitisation May cause an allergic skin rea	action.	
Respiratory sensitisation	symptoms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified due to lack of da	ata.	
Carcinogenicity Not classified due to lack of da	ata.	
Reproductive toxicity Not classified due to lack of da	ata.	
STOT - single exposure Not classified due to lack of da	ata.	
STOT - repeated exposure Not classified due to lack of da	ata.	
Aspiration toxicity Not classified due to lack of da	ata.	

SikaBond[®] TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024 Version 3.1

Print Date 10.01.2025

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:					
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h			
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h			
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h			
reaction mass of ethylbenzene and xylene:					
Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)			
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)			
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethox- ysilane:					
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203			
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202			
Toxicity to algae/aquatic	:	EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l			

Exposure time: 72 h

plants

SikaBond® TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024 Version 3.1

Print Date 10.01.2025

Method: OECD Test Guideline 201

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

<u>Product:</u> Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

 The generation of waste should be avoided or minimized wherever possible.
 Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 Avoid dispersal of spilled material and runoff and contact with



Revision Date: 10.01.2025 Date of last issue: 05.01.2024		Version 3.1	Print Date 10.01.2025
		soil, waterways, drains and sewers.	
European Waste Catalogue	:	08 04 09* waste adhesives and sealants con solvents or other dangerous substances	ntaining organic
Contaminated packaging	:	15 01 10* packaging containing residues of on by dangerous substances	or contaminated

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.2 UN proper shipping name				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.3 Transport hazard class(es)				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
ΙΑΤΑ	:	Not regulated as a dangerous good		
14.4 Packing group				
ADR	:	Not regulated as a dangerous good		
IMDG	:	Not regulated as a dangerous good		
IATA (Cargo)	:	Not regulated as a dangerous good		
IATA (Passenger)	:	Not regulated as a dangerous good		
14.5 Environmental hazards				
Not regulated as a dangerous good				
14.6 Special precautions for user Not applicable				
14.7 Maritime transport in bulk according to IMO instruments Not applicable for product as supplied.				

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substanc	e or mixture
Country NL 00000600252	15 / 19

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond® TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024	Version	3.1		Print Date 10.01.2025
International Chemical Weapons Schedules of Toxic Chemicals a		:	Not applicable	
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the re - exempted from the re	strea I/or gula	am suppliers, and/or ation, and/or	
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XVI	ngerous substances,	:	Conditions of restricti lowing entries should Number on list 3	
			Number on list 75: Banned and/or restric	cted
REACH - Candidate List of Subs Concern for Authorisation (Article		:	None of the compone (=> 0.1 %).	ents are listed
REACH - List of substances subj (Annex XIV)	ect to authorisation	:	Not applicable	
Regulation (EC) on substances t layer	hat deplete the ozone	:	Not applicable	
Regulation (EU) 2019/1021 on p tants (recast)	ersistent organic pollu-	:	Not applicable	
Regulation (EU) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable	
Seveso III: Directive 2012/18/EU jor-accident hazards involving da		nen	t and of the Council on	the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic com ds (VOC) content: 1,08	-
			4 November 2010 on in ution prevention and co	

SikaBond[®] TF Plus N

Revision Date: 10.01.2025 Date of last issue: 05.01.2024

Volatile organic compounds (VOC) content: 1,08% w/w

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Version 3.1

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

reaction mass of ethylbenzene and xylene manganese ferrite black spinel dibutyltin dilaurate

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 H304 H312 H315 H317 H319 H330		Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Fatal if inhaled.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	÷	Skin irritation
Skin Sens. STOT RE	÷	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
2000/33/20	•	list of indicative occupational exposure limit values



Print Date 10.01.2025

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaBond® TF Plus N



Revision Date: 10.01.2025 Date of last issue: 05.01.2024		Version 3.1	Print Date 10.01.2025
NL WG	:	Netherlands. Law on Labour conditions - o	Occupational Expo-
2000/39/EC / TWA		Limit Value - eight hours	
2000/39/EC / STEL	÷	Short term exposure limit	
NL WG / TLV-8hr	÷	Time Weighted Average	
NL WG / TLV-15 min	÷	Short Term Exposure Limit	
ADR	÷	European Agreement concerning the Inte	rnational Carriage of
		Dangerous Goods by Road	
CAS	:	Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
IATA	:	International Air Transport Association	
IMDG	:	International Maritime Code for Dangerou	s Goods
LD50	:	Median lethal dosis (the amount of a mate	
		once, which causes the death of 50% (on test animals)	
LC50	:	Median lethal concentration (concentration air that kills 50% of the test animals during	
		period)	
MARPOL		International Convention for the Preventio	on of Pollution from
MARTOL	•	Ships, 1973 as modified by the Protocol of	
OEL		Occupational Exposure Limit	
PBT	:	Persistent, bioaccumulative and toxic	
PNEC	:	Predicted no effect concentration	
REACH	:	Regulation (EC) No 1907/2006 of the Eur	opean Parliament
	•	and of the Council of 18 December 2006	
		istration, Evaluation, Authorisation and Re	
		cals (REACH), establishing a European C	
SVHC	•	Substances of Very High Concern	
vPvB		Very persistent and very bioaccumulative	
=			

Further information

Classification of the mixtur	Classification procedure:	
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN

Revision Date: 10.01.2025 Date of last issue: 05.01.2024

Version 3.1

Jika®

Print Date 10.01.2025