
according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaForce®-803 L45 (B) Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.

Zonnebaan 56 3542 EG Utrecht Nederland

 Telephone
 : +31-30-2410120

 Telefax
 : +31-30-2414482

 E-mail address of person
 : EHS@nl.sika.com

responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure if inhaled.

Country NL 100000019819

1 / 17



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breath-

ing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged

or repeated exposure if inhaled.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

4,4'-Methylenediphenyl diisocyanate, oligomers

4,4'-methylenediphenyl diisocyanate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B

Revision Date: 13.12.2024 Version 4.0 Print Date 13.12.2024

Date of last issue: 08.12.2023

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
4,4`-Methylenediphenyl diisocya- nate, oligomers	25686-28-6 500-040-3 01-2119457013-49- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l	>= 20 - < 25

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika

SikaForce®-803 L45 (B) Part B

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 ———————————————————————————————————	>= 0,5 - < 1
		specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
		Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



3-isocvanatomethyl-3.5.5-	4098-71-9	Acute Tox 1: H330	>= 0.1 - < 0.25

3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411	>= 0,1 - < 0,25
		specific concentration limit Resp. Sens. 1; H334 >= 0,5 %	
		specific concentration limit Skin Sens. 1; H317 >= 0,5 %	
		Acute toxicity esti- mate	
		Acute inhalation toxicity (dust/mist): 0,031 mg/l	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

Revision Date: 13.12.2024

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Asthmatic appearance **Symptoms**

Cough

Respiratory disorder Allergic reactions **Excessive lachrymation**

Erythema Headache **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

Risks irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Revision Date: 13.12.2024 Version 4.0 Print Date 13.12.2024

Date of last issue: 08.12.2023

for firefighters

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not

according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-

tion (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

> proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Revision Date: 13.12.2024 Date of last issue: 08.12.2023

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour black

Odour odourless

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 300.000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,21 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

Country NL 100000019819

10 / 17



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

4,4`-Methylenediphenyl diisocyanate, oligomers:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Country NL 100000019819

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

Revision Date: 13.12.2024

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Country NL 100000019819

12 / 17



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Date of last issue: 08.12.2023

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Revision Date: 13.12.2024 Date of last issue: 08.12.2023

> Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaForce®-803 L45 (B) Part B



Revision Date: 13.12.2024 Version 4.0 Print Date 13.12.2024

Date of last issue: 08.12.2023

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 75: Banned and/or restricted

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SikaForce®-803 L45 (B) Part B

Revision Date: 13.12.2024 Version 4.0 Print Date 13.12.2024

Date of last issue: 08.12.2023

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

Causes skin irritation. H315

H317 May cause an allergic skin reaction. Causes serious eye irritation. H319

H330 Fatal if inhaled. Harmful if inhaled. H332

May cause allergy or asthma symptoms or breathing difficul-H334

ties if inhaled.

May cause respiratory irritation. H335 Suspected of causing cancer. H351

May cause damage to organs through prolonged or repeated H373

exposure if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Long-term (chronic) aquatic hazard Aquatic Chronic

Carc. Carcinogenicity Eye irritation Eye Irrit.

Respiratory sensitisation Resp. Sens.

Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure STOT SE

ADR European Agreement concerning the International Carriage of

Dangerous Goods by Road

Chemical Abstracts Service CAS **DNEL** Derived no-effect level

Half maximal effective concentration EC50 **GHS** Globally Harmonized System

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG**

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

Median lethal concentration (concentrations of the chemical in LC50

air that kills 50% of the test animals during the observation

period)

International Convention for the Prevention of Pollution from **MARPOL**

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL**

Persistent, bioaccumulative and toxic **PBT PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SikaForce®-803 L45 (B) Part B

Revision Date: 13.12.2024 Version 4.0 Print Date 13.12.2024

Date of last issue: 08.12.2023

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NL / EN