

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sika® Colora

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special system

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.  
Zonnebaan 56  
3542 EG Utrecht  
Nederland  
Telephone : +31-30-2410120  
Telefax : +31-30-2414482  
E-mail address of person : EHS@nl.sika.com  
responsible for the SDS

### 1.4 Emergency telephone number

+31-57-0854201

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Specific target organ toxicity - repeated exposure, Category 2, Central nervous system	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :  

Signal word : Warning

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025

Version 6.0

Print Date 21.02.2025

Date of last issue: 19.02.2024

Hazard statements	:	H226 H373	Flammable liquid and vapour. May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
		H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b>	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P260	Do not breathe mist or vapours.
		P273	Avoid release to the environment.
		<b>Response:</b>	
		P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
		P314	Get medical advice/ attention if you feel unwell.
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

## Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

## Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 10
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not Assigned 919-446-0 265-185-4 01-2119458049-33-XXXX [corresponding group CAS 64742-82-1]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 5 - < 10
trimethylolpropane	77-99-6 201-074-9 01-2119486799-10-XXXX	Repr. 2; H361fd	>= 0,1 - < 0,5
Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 40 - < 60

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects and symptoms.

Risks : No known significant effects or hazards.

May cause damage to organs through prolonged or repeated exposure if inhaled.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

## 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

ance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

## 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	10 mg/m <sup>3</sup>	DE TRGS 900
n-butyl acetate	123-86-4	TLV-8hr	50 ppm 241 mg/m <sup>3</sup>	NL WG
		TWA	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
		TLV-15 min	150 ppm 723 mg/m <sup>3</sup>	NL WG
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not Assigned	TWA	300 mg/m <sup>3</sup>	DE TRGS 900
	Further information: Group exposure limit for hydrocarbon solvent mixtures			

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.  
Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor (Type A) and particulate filter  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
P1: Inert material; P2, P3: hazardous substances  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

## Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Colour : various  
Odour : ester-like  
Melting point/ range / Freezing point : No data available  
Boiling point/boiling range : No data available  
Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

- Upper explosion limit / Up- : 6,5 %(V)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

---

per flammability limit

Lower explosion limit /  
Lower flammability limit : 0,6 %(V)

Flash point : 34 °C  
Method: closed cup

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

## Viscosity

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

## Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-  
octanol/water : No data available

Vapour pressure : 12,4989 hPa

Density : ca. 1,6 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

## 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

## 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

## 10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

:  
No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23,4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### **trimethylolpropane:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0,85 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 10.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

## **Skin corrosion/irritation**

Not classified due to lack of data.

## **Components:**

### **n-butyl acetate:**

Result : Repeated exposure may cause skin dryness or cracking.

### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : Repeated exposure may cause skin dryness or cracking.

Result : Repeated exposure may cause skin dryness or cracking.

## **Serious eye damage/eye irritation**

Not classified due to lack of data.

## **Respiratory or skin sensitisation**

### **Skin sensitisation**

Not classified due to lack of data.

### **Respiratory sensitisation**

Not classified due to lack of data.

### **Germ cell mutagenicity**

Not classified due to lack of data.

### **Carcinogenicity**

Not classified due to lack of data.

### **Reproductive toxicity**

Not classified due to lack of data.

### **STOT - single exposure**

Not classified due to lack of data.

### **STOT - repeated exposure**

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

### **Aspiration toxicity**

Not classified due to lack of data.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l  
Exposure time: 72 h

##### **trimethylolpropane:**

Toxicity to fish : LC50 (Fish): 1.000 mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1.000 mg/l  
Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADR : PAINT  
IMDG : PAINT  
IATA : Paint

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

### 14.4 Packing group

ADR  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)  
Remarks : Exempted according to 2.2.3.1.5 (Viscous substance exemp-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

tion)

## IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Remarks : Transport in accordance with 2.3.2.5 of the IMDG-Code

## IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 75

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 16,58% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 16,58% w/w

## Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment). reaction mass of ethylbenzene and xylene

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

## SECTION 16: Other information

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H336 : May cause drowsiness or dizziness.  
H361fd : Suspected of damaging fertility. Suspected of damaging the unborn child.  
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
NL WG : Netherlands. Law on Labour conditions - Occupational Exposure Limits  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
DE TRGS 900 / TWA : Time weighted average  
DE TRGS 900 / TWA : Time Weighted Average  
NL WG / TLV-8hr : Time Weighted Average  
NL WG / TLV-15 min : Short Term Exposure Limit  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

**Sika® Colora**



Revision Date: 21.02.2025  
Date of last issue: 19.02.2024

Version 6.0

Print Date 21.02.2025

	air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

## Further information

### Classification of the mixture:

Flam. Liq. 3	H226
STOT RE 2	H373
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

NL / EN