

Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikadur[®]-52 Injection Normal Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Special system, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Nederland B.V.
		Zonnebaan 56
		3542 EG Utrecht
		Nederland
Telephone	:	+31-30-2410120
Telefax	:	+31-30-2414482
E-mail address of person	:	EHS@nl.sika.com
responsible for the SDS		

1.4 Emergency telephone number

+31-57-0854201

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-52 Injection Normal Part B



Revision Date: 23.07.2024 Date of last issue: 27.05.2024			Version 6.	.0	Print Date 23.07.2024
Signal word	:	Danger			
Hazard statements	:	H302 H314 H317 H412	May cause	wallowed. rere skin burns and an allergic skin rea aquatic life with long	ction.
Supplemental Hazard Statements	:	EUH071	Corros	ive to the respirato	ry tract.
Precautionary statements	:	Prevention	:		
		P261 P273 P280	Avoid ı Wear p	breathing mist or va release to the envir protective gloves/ p otection/ face prote	onment. rotective clothing/
		Response:			
		P303 + P36		Il contaminated clo	r): Take off immedi- thing. Rinse skin
		P304 + P34	air and	IF INHALED: Remo I keep comfortable tely call a POISON	
		P305 + P35	1 + P338 + F with wa tact ler tinue ri	P310 IF IN EYES	5: Rinse cautiously outes. Remove con- I easy to do. Con-

Hazardous components which must be listed on the label:

benzyl alcohol 3-aminomethyl-3,5,5-trimethylcyclohexylamine Amines, polyethylenepoly-, triethylenetetramine fraction Adduct IA (epoxy amine adduct)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikadur[®]-52 Injection Normal Part B



Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity esti- mate Acute oral toxicity: 1.200 mg/kg	>= 25 - < 40
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity esti- mate Acute oral toxicity:	>= 10 - < 20
Amines, polyethylenepoly-, tri- ethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13- XXXX	1.030 mg/kgAcute Tox. 4; H302Acute Tox. 4; H312Skin Corr. 1B; H314Skin Sens. 1; H317Aquatic Chronic 3;H412EUH071Acute toxicity estimateAcute oral toxicity:1.716 mg/kgAcute dermal toxicity:1.465 mg/kg	>= 10 - < 20

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikadur[®]-52 Injection Normal Part B

Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

(1-methylethyl)-1,1'-biphenyl Contains: diisopropyl-1,1'-biphenyl >= 9,9 %	25640-78-2 247-156-8 01-2119982993-17- XXXX	Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 10 - < 20
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 5 - < 10
Adduct IA (epoxy amine adduct)	68609-08-5 614-657-1 01-2120106013-80- XXXX	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

Sikadur[®]-52 Injection Normal Part B



Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	: Health injuries may be delayed. corrosive effects sensitising effects
	Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns. Corrosive to the respiratory tract.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment		Treat symptomatically.
ricaunon	•	incal symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- ucts	:	No hazardous combustion products are known

5.3 Advice for firefighters Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters			3 11 1
Further information	:	Standard procedure for chemical fires.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.



Revision Date: 23.07.2024 Date of last issue: 27.05.2024	Version 6.0	Print Date 23.07.2024
6.2 Environmental precautions Environmental precautions	: Do not flush into surface water or sanita If the product contaminates rivers and la respective authorities.	

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling :	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion	Normal measures for preventive fire protection.
	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, inc	luding any incompatibilities
	Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- : age stability	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Jika

Sikadur[®]-52 Injection Normal Part B

Revision Date: 23.07.2024 Date of last issue: 27.05.2024	Version 6.0	Print Date 23.07.2024
Specific use(s)	: Consult most current local Product Da use.	ta Sheet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
------------	---------	----------------------------------	---------------------------	---------

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	No special measures required.
Environmental exposure cont	ols
General advice	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.



Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

I Information on basic physical	l an	d chemical properties
Physical state Colour	:	liquid yellow
Odour	:	amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Upper flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	Not applicable
		No data available
Decomposition temperature	:	No data available
рН	:	> 11 (20 °C) Concentration: 50 %
Viscosity		
Viscosity, dynamic	:	ca. 45 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies) Water solubility		No data available

Water solubility	:	No data available
------------------	---	-------------------

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-52 Injection Normal Part B



Partition coefficient: n- octanol/water	: No data available
Vapour pressure	: 0,07 hPa
Density	: ca. 1,01 g/cm3 (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid	: No data av	ailable
--------------------	--------------	---------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.



Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed.		
Components:		
benzyl alcohol:		
Acute oral toxicity	:	Acute toxicity estimate: 1.200 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.200 mg/kg
3-aminomethyl-3,5,5-trime	ethylc	yclohexylamine:
Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg
Amines, polyethylenepoly	y-, trie	thylenetetramine fraction:
Acute oral toxicity	:	LD50 Oral (Rat): 1.716 mg/kg
		Acute toxicity estimate: 1.716 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.465 mg/kg
		Acute toxicity estimate: 1.465 mg/kg Method: Calculation method
(1-methylethyl)-1,1'-biphe	nyl:	
Acute oral toxicity	•	LD50 Oral (Rat): 4.650 mg/kg Method: OECD Test Guideline 401

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-52 Injection Normal Part B



sion Date: 23.07.2024 of last issue: 27.05.2024	Version 6.0	Print Date 23.07.
Acute oral toxicity	 LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008 	
Adduct IA (epoxy amine ad	lduct):	
Acute oral toxicity	: LD50 Oral (Rat, female): 300 - 2.000 mg/l Method: OECD Test Guideline 423	kg
Skin corrosion/irritation		
Causes severe burns.		
Components:		
2,4,6-tris(dimethylaminom	ethyl)phenol:	
Species	: Rabbit	
Assessment Method	: Corrosive : OECD Test Guideline 404	
Assessment	: irritating	
Remarks	: Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Causes serious eye damage		
Components:		
Components:		
<u>Components:</u> 2,4,6-tris(dimethylaminom	ethyl)phenol:	
Components: 2,4,6-tris(dimethylaminom Species	ethyl)phenol: : Rabbit	
Components: 2,4,6-tris(dimethylaminom Species Assessment	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment	 Ethyl)phenol: Rabbit Causes serious eye damage. irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008 	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks	 Ethyl)phenol: Rabbit Causes serious eye damage. irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008 	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks Respiratory or skin sensiti	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised REGULATION (EC) No 1272/2008 sation	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks Respiratory or skin sensiti Skin sensitisation	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised REGULATION (EC) No 1272/2008 sation	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks Respiratory or skin sensiti Skin sensitisation May cause an allergic skin re	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised REGULATION (EC) No 1272/2008 sation eaction.	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks Respiratory or skin sensiti Skin sensitisation May cause an allergic skin re Respiratory sensitisation Not classified due to lack of Germ cell mutagenicity	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised REGULATION (EC) No 1272/2008 sation eaction.	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks Respiratory or skin sensiti Skin sensitisation May cause an allergic skin re Respiratory sensitisation Not classified due to lack of	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised REGULATION (EC) No 1272/2008 sation eaction.	
Components: 2,4,6-tris(dimethylaminom Species Assessment Assessment Remarks Respiratory or skin sensiti Skin sensitisation May cause an allergic skin re Respiratory sensitisation Not classified due to lack of Germ cell mutagenicity	ethyl)phenol: : Rabbit : Causes serious eye damage. : irritating : Annex VI - Harmonised REGULATION (EC) No 1272/2008 sation eaction. data.	

Sikadur[®]-52 Injection Normal Part B

Jika®

Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:			
benzyl alcohol:			
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h	
3-aminomethyl-3,5,5-trimethy	ylc	cyclohexylamine:	
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h	
		NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h	
(1-methylethyl)-1,1'-biphenyl:			
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 0,167 mg/l Exposure time: 48 h	

Adduct IA (epoxy amine adduct):

Sikadur[®]-52 Injection Normal Part B



Revision Date: 23.07.2024 Date of last issue: 27.05.2024		Version 6.0	Print Date 23.07.202	
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (a Exposure time: 72 h	llgae)): 3,13 mg/l	
Toxicity to fish (Chronic tox- icity)	:	LC50: 1,62 mg/l Exposure time: 96 h Species: Danio rerio (zebra fish)		
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)		EC50: 1,75 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)		
12.2 Persistence and degradabi No data available	lity			
12.3 Bioaccumulative potential No data available				
12.4 Mobility in soil No data available				
12.5 Results of PBT and vPvB a	sses	ssment		
Product:				
Assessment	:	This substance/mixture contains no comp to be either persistent, bioaccumulative ar very persistent and very bioaccumulative 0.1% or higher.	nd toxic (PBT), or	
12.6 Endocrine disrupting prop	ertie	s		
Product:				
Assessment	:	The substance/mixture does not contain of ered to have endocrine disrupting propert REACH Article 57(f) or Commission Deleg (EU) 2017/2100 or Commission Regulation levels of 0.1% or higher.	ies according to gated regulation	
12.7 Other adverse effects				
12.7 Other adverse effects <u>Product:</u>				

SECTION 13: Disposal considerations

:

13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878





Δ

Revision Date: 23.07.2024 Date of last issue: 27.05.2024		Version 6.0	Print Date 23.07.2024
		Empty containers or liners may retain sor This material and its container must be d way. Dispose of surplus and non-recyclable pr waste disposal contractor. Disposal of this product, solutions and an at all times comply with the requirements protection and waste disposal legislation local authority requirements. Avoid dispersal of spilled material and run soil, waterways, drains and sewers.	isposed of in a safe roducts via a licensed by by-products should of environmental and any regional
European Waste Catalogue	:	08 04 09* waste adhesives and sealants solvents or other dangerous substances	containing organic
Contaminated packaging	:	15 01 10* packaging containing residues by dangerous substances	of or contaminated

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 1760	
IMDG	:	UN 1760	
ΙΑΤΑ	:	UN 1760	
14.2 UN proper shipping name			
ADR	:	CORROSIVE LIQUII (3-aminomethyl-3,5,5 methylethyl)-1,1'-bipl	5-trimethylcyclohexylamine, (1-
IMDG	:	CORROSIVE LIQUII (3-aminomethyl-3,5,5 methylethyl)-1,1'-bipl	5-trimethylcyclohexylamine, (1-
ΙΑΤΑ	:	Corrosive liquid, n.o. (3-aminomethyl-3,5,5 methylethyl)-1,1'-bipl	5-trimethylcyclohexylamine, (1-
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	8	
IMDG	:	8	
ΙΑΤΑ	:	8	
14.4 Packing group			
ADR			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikadur[®]-52 Injection Normal Part B

Date: 23.07.2024 R Ľ



Revision Date: 23.07.2024 Date of last issue: 27.05.2024		Version 6.0	Print Date 23.07.2024
Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: II : C9 : 80 : 8 : (E)		
IMDG Packing group Labels EmS Code Remarks	: II : 8 : F-A, S-B : Alkalis		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	: 855 : Y840 : II : Corrosive	9	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 851 : Y840 : II : Corrosive)	
14.5 Environmental hazards			
ADR Environmentally hazardous IMDG Marina pollutant	: no		
Marine pollutant IATA (Passenger) Environmentally hazardous	: no : no		
IATA (Cargo) Environmentally hazardous	: no		
14.6 Special precautions for use			
The transment alogs $f(x, y)$		in and fan infanns at an al mun	

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

Sikadur[®]-52 Injection Normal Part B



Revision Date: 23.07.2024 Date of last issue: 27.05.2024	Version 6	6.0		Print Date 23.07.2024
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	trea /or gula	am suppliers, and/or ition, and/or	
REACH - Restrictions on the mar the market and use of certain dar mixtures and articles (Annex XVII	ngerous substances,	:	Conditions of restrictic lowing entries should l Number on list 3	
			Number on list 75:	
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the component (=> 0.1 %).	nts are listed
REACH - List of substances subj (Annex XIV)	ect to authorisation	:	Not applicable	
Regulation (EC) on substances th layer	nat deplete the ozone	:	Not applicable	
Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu-	:	Not applicable	
Regulation (EU) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable	
Seveso III: Directive 2012/18/EU jor-accident hazards involving dat		nent	t and of the Council on t	the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic comp ds (VOC) content: 37,12	
	emissions (integrated p	coll	4 November 2010 on in ution prevention and co ds (VOC) content: 37,12	ntrol)

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Sikadur[®]-52 Injection Normal Part B



Revision Date: 23.07.2024 Date of last issue: 27.05.2024 Version 6.0

Print Date 23.07.2024

SECTION 16: Other information

Full text of H-Statements	5
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H400	: Very toxic to aquatic life.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
Full text of other abbrev	
Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
ADR	 European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
EB30	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in
2030	air that kills 50% of the test animals during the observation
	period)
MARPOL	: International Convention for the Prevention of Pollution from
MARFOL	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
ountry NL 10000007368	17 / 1



Revision Date: 23.07.2024 Date of last issue: 27.05.2024	Version 6.0	Print Date 23.07.2024
vPvB	: Very persistent and very bioaccumulative	

Further information

Classification of th	Classification procedure:	
Acute Tox. 4	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

NL / EN