according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaForce®-800 Part B



Print Date 07.02.2025

Date of last issue: 27.07.2024

Revision Date: 05.02.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

Version 3.6

1.1 Product identifier

Trade name : SikaForce®-800 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.

Zonnebaan 56 3542 EG Utrecht Nederland

 Telephone
 : +31-30-2410120

 Telefax
 : +31-30-2414482

 E-mail address of person
 : EHS@nl.sika.com

responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure if inhaled.

Country NL 100000005942

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaForce®-800 Part B



Date of last issue: 27.07.2024

Revision Date: 05.02.2025

### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breath-

ing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged

or repeated exposure if inhaled.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

### Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues


### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Chemical name	CAS-No. Classification		Concentration
	EC-No.		(% w/w)
	Registration number		
Diphenylmethanediisocyanate,	9016-87-9	Acute Tox. 4; H332	>=80
isomeres and homologues	Not Assigned	Skin Irrit. 2; H315	
		Eye Irrit. 2; H319	
		Resp. Sens. 1; H334	
		Skin Sens. 1; H317 Carc. 2; H351	
		STOT SE 3; H335	
		(Respiratory system)	
		STOT RE 2; H373	
		specific concentration	
		limit	
		Eye Irrit. 2; H319	
		>= 5 %	
		specific concentration	
		limit	
		Resp. Sens. 1; H334	
		>= 0,1 %	
		specific concentration limit	
		Skin Irrit. 2; H315	
		>= 5 %	
		specific concentration	
		limit	
		STOT SE 3; H335	
		>= 5 %	

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Date of last issue: 27.07.2024

Revision Date: 05.02.2025

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Harmful if inhaled.


May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.


May cause damage to organs through prolonged or repeated

exposure if inhaled.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaForce®-800 Part B



Date of last issue: 27.07.2024

Revision Date: 05.02.2025

### 4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

In case of fire, use water/water spray/water jet/carbon diox-Suitable extinguishing media

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

## 5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

#### SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

### 6.2 Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

Country NL 100000005942

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the application area

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	AGW (Inhalable fraction)	0,05 mg/m3 (MDI)	DE TRGS 900
	Further information: Senate commission for the review of compounds at the work place dangerous for the health has also established a BEI-value for the same OEL value in the 'MAK- and BAT-value list'			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance paste Colour grey

Odour slight

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

: No data available

: > 100 °C Flash point

Method: closed cup

Auto-ignition temperature No data available

Decomposition temperature : No data available

substance/mixture reacts with water pН

**Viscosity** 

Viscosity, dynamic : ca. 35.000 mPa.s (20 °C)

Viscosity, kinematic  $> 20,5 \text{ mm2/s } (40 \,^{\circ}\text{C})$ 

Solubility(ies)

Water solubility insoluble

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Date of last issue: 27.07.2024

Revision Date: 05.02.2025

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,23 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Harmful if inhaled.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Date of last issue: 27.07.2024

### Components:

### Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity LD50 Dermal (Rabbit): > 9.400 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

### **Aspiration toxicity**

Not classified due to lack of data.

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

### **Product:**

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

Country NL 100000005942





according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaForce®-800 Part B



Revision Date: 05.02.2025 Date of last issue: 27.07.2024

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

### Components:

### Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

## 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

Country NL 100000005942



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 05 01\* waste isocyanates

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

: Not applicable

Number on list 56: Diphenylmethanediisocyanate, isomeres and

homologues

Number on list 74: Diphenylmethanediisocyanate, isomeres and

homologues

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



Revision Date: 05.02.2025 Version 3.6 Print Date 07.02.2025

Date of last issue: 27.07.2024

tants (recast)

Regulation (EU) No 649/2012 of the European Parlia: Not applicable

ment and the Council concerning the export and import

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-

jor-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)
Not applicable

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

### Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation

Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B



ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

### Classification of the mixture: Classification procedure:

H332	Calculation method
H315	Calculation method
H319	Calculation method
H334	Calculation method
H317	Calculation method
H351	Calculation method
H335	Calculation method
H373	Calculation method
	H315 H319 H334 H317 H351 H335

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# SikaForce®-800 Part B

Version 3.6



Print Date 07.02.2025

Revision Date: 05.02.2025 Date of last issue: 27.07.2024