according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor®-151 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Nederland B.V.

Zonnebaan 56 3542 EG Utrecht Nederland

 Telephone
 : +31-30-2410120

 Telefax
 : +31-30-2414482

 E-mail address of person
 : EHS@nl.sika.com

responsible for the SDS

1.4 Emergency telephone number

+31-57-0854201

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 1B H360F: May damage fertility.

Long-term (chronic) aquatic hazard, Cat- H411: Toxic to aquatic life with long lasting effects.

egory 2

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika ®

# Sikafloor®-151 Part A

Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical ad-

vice/ attention.

P391 Collect spillage.

### Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Reaction mass of isomers of epoxy resin BFDGE benzyl alcohol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Eye Irrit. 2; H319 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 25 - < 40
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 2,5 - < 5
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate	>= 1 - < 2,5
		Acute oral toxicity: 1.200 mg/kg	

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May damage fertility.

irritant effects sensitising effects

toxic effects for reproduction

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Date of last issue: 23.07.2024

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system. **Environmental precautions** 

If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Pregnant women or women of child-bearing age should not be

exposed to this product.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

chemical products. Reference number EN 374, Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

: No special measures required. Respiratory protection

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance viscous Colour grey

Odour epoxy-like

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

No data available Flammability (solid, gas)

Upper/lower flammability or explosive limits

per flammability limit

Upper explosion limit / Up- : No data available

Lower explosion limit /

Lower flammability limit

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Date of last issue: 23.07.2024

Revision Date: 24.10.2024

Flash point : ca. 89 °C

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : ca. 6

Concentration: 50 %

**Viscosity** 

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,6 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Date of last issue: 23.07.2024

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified due to lack of data.

### **Components:**

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

benzyl alcohol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): 1.200 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Date of last issue: 23.07.2024

Revision Date: 24.10.2024

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

May damage fertility.

### STOT - single exposure

Not classified due to lack of data.

### STOT - repeated exposure

Not classified due to lack of data.

### **Aspiration toxicity**

Not classified due to lack of data.

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

### **Product:**

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Components:**

### bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

### Reaction mass of isomers of epoxy resin BFDGE:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 2,55 mg/l

10 / 16

Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (algae): 1,8 mg/l Exposure time: 72 h plants

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Date of last issue: 23.07.2024

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:** 

: This substance/mixture contains no components considered Assessment

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Endocrine disrupting properties

**Product:** 

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

### **SECTION 14: Transport information**

### 14.1 UN number or ID number

 ADR
 : UN 3082

 IMDG
 : UN 3082

 IATA
 : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

### 14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

### 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Date of last issue: 23.07.2024

Tunnel restriction code : (-)

Remarks : Transport in accordance with special provision 375

**IMDG** 

Packing group : III
Labels : 9
EmS Code : F-A. S-F

Remarks : Transport in accordance with 2.10.2.7 of the IMDG-Code

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

Remarks : Transport in accordance with special regulation A 197

IATA (Passenger)

Packing instruction (passen- : 964

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

**REACH Information:** All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 30: oxirane. mono[(C12-14-alkyloxy)methyl]

derivs.

Number on list 75:

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Netherlands. Substances of very high concern (ZZS-list) : Quartz (SiO2)

Regulation (EU) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

Not applicable

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 **ENVIRONMENTAL HAZARDS** 

Volatile organic compounds Law on the incentive tax for volatile organic compounds

Volatile organic compounds (VOC) content: 3,27% w/w

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-151 Part A



Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,27% w/w

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Contains a substance which is subject to the SZW-list of carcinogenic substances (Ministry of Social Affairs and

Employment).

Contains a substance which is subject to the SZW-list of reproductive toxic substances (Ministry of Social Affairs and Employment).

ethanol

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

### **Full text of H-Statements**

H302 : Harmful if swallowed. H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled. H360F : May damage fertility.

H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods LD50 : Median lethal dosis (the amount of a material, give

Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika®

# Sikafloor®-151 Part A

Revision Date: 24.10.2024 Version 7.0 Print Date 24.10.2024

Date of last issue: 23.07.2024

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

### **Further information**

# Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360F	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

NL / EN